

**Published Date**  
Aug-15-2024

**Revision date**  
Aug-15-2024

**Revision Number**  
2.8

## 1. IDENTIFICATION

**Product identifier**

Product Code(s) **97LF12**  
Product name **Medium Yellow**  
Product category **9700 Series SV Screen Ink**

**Other means of identification**

Synonyms None

**Recommended use of the chemical and restrictions on use**

Recommended use Industrial Printing Operations

**Details of the supplier of the safety data sheet**

UNITED STATES	UNITED KINGDOM
Nazdar Company	Nazdar Limited
8501 Hedge Lane Terrace	Barton Road
Shawnee, KS 66227	Heaton Mersey
Tel: +001-913-422-1888	Stockport, England SK4 3EG
Tel: +001-800-677-4657	Tel: +44 161 442 2111
Fax: +001-913-422-2294	
www.nazdar.com	

**Emergency telephone number**

USA: Chemtrec: +001-800-424-9300  
Outside USA: Chemtrec: +001-703-527-3887  
24 Hour Emergency Phone Number

## 2. HAZARDS IDENTIFICATION

**Classification**

Acute toxicity - Inhalation (Vapors)	Category 3 - (H331)
Acute toxicity - Inhalation (Dusts/Mists)	Category 3 - (H331)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitization	Category 1 - (H317)

**Label elements**



**Signal word**  
Danger

**Hazard statements**

H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation

H331 - Toxic if inhaled

**Precautionary Statements**

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray  
 P280 - Wear protective gloves and eye/face protection  
 P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing  
 P311 - Call a POISON CENTER or doctor  
 P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

**Hazards not otherwise classified (HNOC)**

No information available.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

**Mixture**

Chemical name	CAS No.	Weight-%	Trade secret	Note
2-Butoxyethanol	111-76-2	30 - 60	*	
Resin	Not Available	5 - 10	*	
Titanium Dioxide	13463-67-7	1 - 5	*	

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST-AID MEASURES**

**Description of first aid measures**

<b>General Advice</b>	Show this safety data sheet to the doctor in attendance.
<b>Eye Contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.
<b>Skin Contact</b>	Wash off immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.
<b>Inhalation</b>	Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.
<b>Ingestion</b>	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

**Most important symptoms and effects, both acute and delayed**

None under normal use conditions.

**Indication of any immediate medical attention and special treatment needed**

<b>Notes to Physician</b>	Treat symptomatically.
---------------------------	------------------------

**5. FIRE-FIGHTING MEASURES**

**Suitable Extinguishing Media**

Foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable Extinguishing Media**

No information available.

**Special Provisions**

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

#### **Personal Precautions**

Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

#### **Environmental precautions**

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

#### **Methods and material for containment and cleaning up**

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

#### **Handling**

Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Ensure adequate ventilation.

### Conditions for safe storage, including any incompatibilities

#### **Storage**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep container closed when not in use. Keep out of the reach of children.

#### **Incompatible Products**

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### **Exposure limits**

Chemical name	ACGIH TLV
2-Butoxyethanol 111-76-2	TWA: 20 ppm
Titanium Dioxide 13463-67-7	TWA: 0.2 mg/m <sup>3</sup> nanoscale respirable particulate matter TWA: 2.5 mg/m <sup>3</sup> finescale respirable particulate matter

Chemical name	OSHA PEL
2-Butoxyethanol 111-76-2	TWA: 50 ppm TWA: 240 mg/m <sup>3</sup> Skin
Titanium Dioxide 13463-67-7	TWA: 15 mg/m <sup>3</sup> total dust

Chemical name	OSHA PEL (vacated)
2-Butoxyethanol 111-76-2	TWA: 25 ppm TWA: 120 mg/m <sup>3</sup> Skin
Titanium Dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup> total dust

<b>Chemical name</b>	<b>Ontario TWAEV</b>
2-Butoxyethanol 111-76-2	TWA: 20 ppm
Titanium Dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>

<b>Chemical name</b>	<b>Mexico OEL (TWA)</b>
2-Butoxyethanol 111-76-2	TWA/VLE-PPT: 20 ppm
Titanium Dioxide 13463-67-7	TWA/VLE-PPT: 10 mg/m <sup>3</sup>

### Appropriate engineering controls

#### **Engineering Measures**

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.

#### Individual protection measures, such as personal protective equipment

##### **Eye/Face Protection**

Wear safety glasses with side shields (or goggles). If splashes are likely to occur: Wear suitable face shield. Ensure that eyewash stations and safety showers are close to the workstation location.

##### **Skin Protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

##### **Hand Protection**

Chemical resistant protective gloves.

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding >480 minutes of permeation time): eg. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), polyvinylchloride (0.7 mm) and other

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers. Taking into account the varying conditions, the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Due to different glove types, the manufacturer's directions for use should be observed.

Replace gloves immediately when torn or any change in appearance is noticed such as dimension, color, flexibility.

##### **Respiratory Protection**

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended.

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

#### Information on basic physical and chemical properties

<b>Physical state</b>	Liquid	<b>Appearance</b>	Colored
<b>Odor</b>	Characteristic	<b>Odor threshold</b>	No information available
<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>	
<b>pH</b>		No data available	
<b>Melting point / freezing point</b>	No information available	No data available	
<b>Initial boiling point and boiling range</b>	> 149 °C / 300 °F		

Flash point	62 °C / 143 °F	Pensky Martens Closed Cup (PMCC)
Evaporation rate		No data available
Flammability Limit in Air		
Upper flammability or explosive limits		No data available
Lower flammability or explosive limits		No data available
Vapor pressure		No data available
Relative vapor density		No data available
Specific gravity - VALUE 1	1.03	
Water Solubility		No data available
Solubility in other solvents		No data available
Partition coefficient		No data available
Autoignition temperature	No information available	No data available
Hyphen		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available
Explosive Properties	No data available	
Oxidizing Properties	No data available	

#### Other information

Photochemically Reactive	No
Weight Per Gallon (lbs/gal)	8.55

VOC by weight % (less water)	VOC by volume % (less water)	VOC lbs/gal (less water)	VOC grams/liter (less water)
53.98	57.09	4.62	553.71

## 10. STABILITY AND REACTIVITY

#### Reactivity

No information available.

#### Chemical stability

Stable under normal conditions.

#### Possibility of hazardous reactions

None under normal processing.

#### Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

#### Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

#### Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO<sub>2</sub>). Carbon monoxide.

## 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

<b>Inhalation</b>	Specific test data for the substance or mixture is not available. Toxic if inhaled. (based on components).
<b>Eye Contact</b>	Specific test data for the substance or mixture is not available.
<b>Skin Contact</b>	Specific test data for the substance or mixture is not available.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available.

Chemical name	Oral LD50
2-Butoxyethanol 111-76-2	= 470 mg/kg ( Rat )
Titanium Dioxide 13463-67-7	> 10000 mg/kg ( Rat )

Chemical name	Dermal LD50
2-Butoxyethanol 111-76-2	= 435 mg/kg ( Rabbit )
Resin	> 2000 mg/kg ( Rat )

Chemical name	Inhalation LC50
2-Butoxyethanol 111-76-2	= 450 ppm ( Rat ) 4 h = 486 ppm ( Rat ) 4 h
Titanium Dioxide 13463-67-7	= 5.09 mg/L ( Rat ) 4 h

#### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Specific test data for the substance or mixture is not available.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Skin corrosion/irritation</b>	Specific test data for the substance or mixture is not available. Causes skin irritation (pain, redness and swelling). (based on components).
<b>Eye damage/irritation</b>	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components).
<b>Irritation</b>	Specific test data for the substance or mixture is not available.
<b>Corrosivity</b>	Specific test data for the substance or mixture is not available.
<b>Sensitization</b>	Specific test data for the substance or mixture is not available. May cause an allergic skin reaction. (based on components).
<b>Mutagenic Effects</b>	Specific test data for the substance or mixture is not available.
<b>Carcinogenic effects</b>	Specific test data for the substance or mixture is not available.
<b>Reproductive Effects</b>	Specific test data for the substance or mixture is not available.
<b>STOT - single exposure</b>	Specific test data for the substance or mixture is not available.
<b>STOT - repeated exposure</b>	Specific test data for the substance or mixture is not available.
<b>Chronic Toxicity</b>	Specific test data for the substance or mixture is not available.
<b>Aspiration hazard</b>	Specific test data for the substance or mixture is not available.
<b>Carcinogenicity</b>	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH
2-Butoxyethanol 111-76-2	A3
Titanium Dioxide 13463-67-7	A3

Chemical name	IARC
Titanium Dioxide 13463-67-7	Group 2B

Chemical name	OSHA
Titanium Dioxide 13463-67-7	X

#### Numerical measures of toxicity - Product Information

**Unknown acute toxicity** 0 % of the mixture consists of ingredient(s) of unknown toxicity

**The following values are calculated based on chapter 3.1 of the GHS document**

**ATEmix (oral)** 872.20 mg/kg

ATEmix (dermal)	99,999.00 mg/kg
ATEmix (inhalation-gas)	99,999.00
ATEmix (inhalation-dust/mist)	0.930 mg/l
ATEmix (inhalation-vapor)	5.57 mg/l

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Specific test data for the substance or mixture is not available.

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Fish
2-Butoxyethanol 111-76-2	96h LC50 Lepomis macrochirus: = 1490 mg/L (static) 96h LC50 Lepomis macrochirus: = 2950 mg/L
Resin	96h LC50 Oncorhynchus mykiss: = 11.5 mg/L (static)

Chemical name	Crustacea
2-Butoxyethanol 111-76-2	48h EC50 Daphnia magna: > 1000 mg/L

### Persistence and degradability

No information available.

### Bioaccumulation

Chemical name	Partition coefficient
2-Butoxyethanol 111-76-2	0.81

## 13. DISPOSAL CONSIDERATIONS

### Disposal methods

**Waste Disposal Methods** Contain and dispose of waste according to local regulations.

**Contaminated Packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. TRANSPORT INFORMATION

### Note:

This information is not intended to convey all specific transportation requirements relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation information can be found in the specific regulations for your mode of transportation. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

### DOT

Not regulated

### ICAO / IATA / IMDG / IMO

Not Regulated

## 15. REGULATORY INFORMATION

### International Inventories

All substances are listed as ACTIVE on the TSCA Inventory. For further information, please contact: Supplier (manufacturer/importer/downstream user/distributor).

### US Federal Regulations

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	CAS No.	Weight-%	SARA 313 - Threshold Values %
2-Butoxyethanol	111-76-2	30 - 60	1.0

#### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

### US State Regulations

Chemical name	Massachusetts
2-Butoxyethanol 111-76-2	X
Titanium Dioxide 13463-67-7	X

Chemical name	Minnesota Right To Know
2-Butoxyethanol 111-76-2	X
Titanium Dioxide 13463-67-7	X

Chemical name	New Jersey
2-Butoxyethanol 111-76-2	X
Titanium Dioxide 13463-67-7	X

Chemical name	Pennsylvania
2-Butoxyethanol 111-76-2	X
Titanium Dioxide 13463-67-7	X

#### California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Chemical name	California Proposition 65
Titanium Dioxide	Carcinogen

*This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product.*

### Canada

Chemical name	NPRI - National Pollutant Release Inventory
2-Butoxyethanol 111-76-2	Part 1, Group A Substance Part 5 Substance - Volatile Organic Compounds with Additional Reporting Requirements Part 4 Substance - Criteria Air Contaminants

**16. OTHER INFORMATION****Key or legend to abbreviations and acronyms used in the safety data sheet****Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	Sk*	Skin designation
+	Sensitizers		

**ACGIH: (American Conference of Governmental Industrial Hygienists)**

A1 - Known Human Carcinogen

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

**NTP: (National Toxicity Program)**

Known - Known Carcinogen

Reasonably Anticipated to be a Human Carcinogen

**OSHA: (Occupational Safety & Health Administration)**

X - Present

**Revision date** Aug-15-2024**Pursuant to NOM-018-STPS-2015**

This information within is considered correct but is not exhaustive and will be used for guidance only, which is based on the current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**