

SAFETY DATA SHEET

Published Date May-15-2019 Revision Date May-15-2019 Revision Number 2.5

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier Product code Product name

Product category

2410 LED MO Primrose Yellow 2400 Series UV-LED Screen Ink

Other means of identification Synonyms

Recommended use of the chemical and restrictions on useRecommended usePrinting operations

None

Details of the supplier of the safety data sheet

UNITED STATES Nazdar Company 8501 Hedge Lane Terrace Shawnee, KS 66227 Tel: +001-913-422-1888 Tel: +001-800-677-4657 Fax: +001-913-422-2294 www.nazdar.com UNITED KINGDOM Nazdar Limited Barton Road Heaton Mersey Stockport, England SK4 3EG Tel: +44 161 442 2111

Emergency telephone number

USA: Chemtrec: +001-800-424-9300 Outside USA: Chemtrec: +001-703-527-3887 24 Hour Emergency Phone Number

2. HAZARDS IDENTIFICATION

Classification

Acute toxicity - Oral	Category 4 - (H302)
Skin Corrosion/irritation	Category 1 - (H314)
Serious eye damage/eye irritation	Category 1 - (H318)
Skin sensitization	Category 1A - (H317)
Reproductive toxicity	Category 1B - (H360FD)
Specific target organ toxicity (repeated exposure)	Category 1 - (H372)
Chronic aquatic toxicity	Category 2 - (H411)



Hazard Statements H302 - Harmful if swallowed H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H360FD - May damage fertility. May damage the unborn child

H372 - Causes damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements

P264 - Wash face, hands and any exposed skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P363 - Wash contaminated clothing before reuse

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention

P202 - Do not handle until all safety precautions have been read and understood

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P314 - Get medical advice/attention if you feel unwell

P273 - Avoid release to the environment

Hazards not otherwise classified (HNOC)

Harmful to aquatic life.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Component	CAS-No	Weight %	Trade Secret	Note
Glycol Ether Acrylate	Trade Secret	10 - 30	*	
Vinyl Functional Monomer	Trade Secret	10 - 30	*	
Acrylated Oligomer	Trade Secret	10 - 30	*	
Photoinitiator	Trade Secret	5 - 10	*	
Acrylated Monomer	Trade Secret	1 - 5	*	
Acrylated Oligomer	Trade Secret	1 - 5	*	
Titanium dioxide	13463-67-7	1 - 5	*	
Photoinitiator	Trade Secret	1 - 5	*	
Stabilizer	Trade Secret	< 1	*	
Acrylated Monomer	Trade Secret	< 0.5	*	
Stabilizer	Trade Secret	< 0.5	*	

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General Advice Eye Contact	Show this safety data sheet to the doctor in attendance. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.
Skin Contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.
Inhalation	Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Most important symptoms and effects, both acute and delayed

None under normal use conditions.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

No information available.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions. Hazardous polymerization may take place during a fire due to heat. Closed containers could violently rupture.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions

Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways, Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Ensure adequate ventilation. Conditions for safe storage, including any incompatibilities Storage Keep at temperatures between 18°-32°C (65°-90°F). Keep containers tightly closed in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep out of the reach of children. Protect from direct sunlight. Keep away from open flames, hot surfaces and sources of ignition. Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

Incompatible Products

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits

Component

ACGIH TLV

Titanium dioxide	TWA: 10 mg/m ³
13463-67-7	

Component	OSHA PEL	
Titanium dioxide	TWA: 15 mg/m ³ total dust	
13463-67-7		
Component	OSHA PEL (vacated)	
Titanium dioxide	TWA: 10 mg/m ³ total dust	
13463-67-7		
Component	Ontario TWAEV	
Titanium dioxide	TWA: 10 mg/m ³	
13463-67-7		
Component	Mexico OEL (TWA)	

TWA/VLE-PPT: 10 mg/m³ STEL/PPT-CT: 20 mg/m³

13463-67-7

Appropriate engineering controls

Titanium dioxide

Engineering Measures Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment. Individual protection measures, such as personal protective equipment Wear safety glasses with side shields (or goggles). If splashes are likely to occur:. Wear **Eye/Face Protection** suitable face shield. Ensure that eyewash stations and safety showers are close to the workstation location. **Skin Protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. **Hand Protection** Chemical resistant protective gloves. Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding >480 minutes of permeation time): eg. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), polyvinylchloride (0.7 mm) and other Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers. Taking into account the varying conditions, the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing. Due to different glove types, the manufacturer's directions for use should be observed. Replace gloves immediately when torn or any change in appearance is noticed such as dimension, color, flexibility, If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved **Respiratory Protection** respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material. General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid
Odor	Sweet Mild Acrylic

Appearance Odor Threshold Colored Liquid No information available

<u>Property</u> pH Melting Point / Freezing Point Boiling Point / Boiling Range	<u>Values</u> > 149 °C / 300 °F	Remarks • Method No data available No data available	L
Flash Point Evaporation rate Flammability Limit in Air Upper flammability limit	> 94 °C / > 201 °F	Pensky Martens Clo No data available No data available	sed Cup (PMCC)
Lower flammability limit Vapor Pressure		No data available No data available No data available	
Vapor Density Specific Gravity	1.17	No data available	
Water Solubility Solubility in other solvents	have to a	No data available No data available	
Partition coefficient: n-octanol Autoignition Temperature Decomposition temperature	/water	No data available No data available No data available	
Kinematic viscosity Dynamic viscosity		No data available No data available	
Explosive Properties Oxidizing Properties	No data available No data available		
Other Information			
Photochemically Reactive Weight Per Gallon (Ibs/gal)	No 9.79		
VOC by weight % (less water) 0-1	VOC by volume % (less water) 0-1	VOC Ibs/gal (less water) 0-1	VOC grams/liter (less water) 0-1

10. STABILITY AND REACTIVITY

Reactivity

No information available.

Chemical stability

Stable under normal conditions.

Possibility of Hazardous Reactions

None under normal processing. Do not store for longer periods at temperatures above 93°C (200°F).

Conditions to avoid

Temperatures above 93 °C / 200 °F. Protect from direct sunlight. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO2). Carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	Specific test data for the substance or mixture is not available.
Eye Contact	Specific test data for the substance or mixture is not available.
Skin Contact	Specific test data for the substance or mixture is not available.
Ingestion	Specific test data for the substance or mixture is not available. Harmful if swallowed. (based

on components).

Component	Oral LD50	
Glycol Ether Acrylate	= 4660 µL/kg (Rat)	
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	
Stabilizer	= 2615 mg/kg(Rat)	
Acrylated Monomer	= 548 mg/kg (Rat)	
Component	Dermal LD50	
Acrylated Monomer	= 154 mg/kg (Rabbit)	

Information on toxicological effects

Symptoms	Specific test data for the substance or mixture is not available.
Delayed and immediate effects as	well as chronic effects from short and long-term exposure
Skin corrosion/irritation	Specific test data for the substance or mixture is not available. Causes severe burns. (based on components).
Eye damage/irritation	Specific test data for the substance or mixture is not available. Causes severe eye damage. (based on components).
Irritation	Specific test data for the substance or mixture is not available.
Corrosivity	Specific test data for the substance or mixture is not available.
Sensitization	Specific test data for the substance or mixture is not available. May cause an allergic skin reaction. (based on components).
Mutagenic Effects	Specific test data for the substance or mixture is not available.
Carcinogenic effects	Specific test data for the substance or mixture is not available.
Reproductive Effects	Specific test data for the substance or mixture is not available. May damage fertility. May damage the unborn child. (based on components).
STOT - single exposure	Specific test data for the substance or mixture is not available.
STOT - repeated exposure	Specific test data for the substance or mixture is not available. Causes damage to organs through prolonged or repeated exposure. (based on components).
Chronic Toxicity	Specific test data for the substance or mixture is not available
Target Organ Effects	Liver, Respiratory system.
Aspiration hazard	Specific test data for the substance or mixture is not available.
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

	ARC
Titanium dioxide G 13463-67-7	Group 2B

Component	OSHA
Titanium dioxide	Х
13463-67-7	

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

1,925.00 mg/kg 5,105.00 mg/kg mg/l ATEmix (oral) ATEmix (dermal)

12. ECOLOGICAL INFORMATION

<u>Ecotoxicity</u> Specific test data for the substance or mixture is not available. Toxic to aquatic life with long lasting effects. (based on components).

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Fish
Stabilizer	96h LC50 Lepomis macrochirus: = 0.97 mg/L (static)
Acrylated Monomer	96h LC50 Pimephales promelas: = 4.8 mg/L (flow-through)
Component	Crustacea
Acrylated Monomer	48h EC50 Daphnia magna: = 0.78 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

No information available

Component	Partition coefficient
Stabilizer	0.37
Acrylated Monomer	0.21

Other adverse effects

No information available

	13. DISPOSAL CONSIDERATIONS	
Waste treatment methods		
Waste Disposal Methods	Contain and dispose of waste according to local regulations.	
Contaminated Packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.	
	14. TRANSPORT INFORMATION	
Note:	This information is not intended to convey all specific transportation requirements relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation information can be found in the specific regulations for your mode of transportation. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.	
<u>DOT</u>	Not regulated Exception: In the US and Canada except when all or part of the transportation is by vessel, containers 119 gallons/ 450 Liters and less are not regulated [see 49CFR 171.4 (c)(1)] If in quantities of 5L or less (per inner packaging) for liquids or 5KG or less (per inner packaging) for solids these items may be shipped as not regulated [additional general packaging requirements must be met see 49CFR 173.24] [see 49CFR 171.4 (c)(2)]	
<u>ICAO / IATA / IMDG / IMO</u>	Not Regulated Exception: If in quantities of 5L or less (per inner packaging) for liquids or 5KG or less (per inner packaging) for solids these items may be shipped as not regulated [additional general packaging requirements must be met see ICAO/IATA special provision A197] Exception: If in quantities of 5L or less (per inner packaging) for liquids or 5KG or less (per inner packaging) for solids these items may be shipped as not regulated [additional general	

packaging requirements must be met see IMDG code 2.10.2.7]

15. REGULATORY INFORMATION

International Inventories

All components are listed on the TSCA Inventory. For further information, please contact:. Supplier (manufacturer/importer/downstream user/distributor).

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS-No	Weight %	SARA 313 - Threshold Values
Glycol Ether Acrylate	Trade Secret	10 - 30	1.0

The above glycol ether acrylate is considered a reactive chemical in ultraviolet curable inks. Once initiated by a high dose of ultraviolet light, this glycol ether acrylate rapidly polymerizes (i.e. hardens) and becomes part of the ink film. The polymerization process of UV curable inks is measured in milliseconds.

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:

Component	CAS-No	Weight %
Glycol Ether Acrylate	Trade Secret	10 - 30

U.S. State Regulations

Component	Massachusetts Right To Know
Titanium dioxide	Х
13463-67-7	
Acrylated Monomer	X
1	

	Minnesota Right To Know
Titanium dioxide	X
13463-67-7	

Component	New Jersey Right To Know
Glycol Ether Acrylate	×
Titanium dioxide 13463-67-7	x
Acrylated Monomer	x

	Pennsylvania
	Right To Know
Glycol Ether Acrylate	X
Titanium dioxide 13463-67-7	X
Acrylated Monomer	X

California Prop. 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other

reproductive harm	
-------------------	--

Component	California Prop. 65
Titanium dioxide	Carcinogen

- This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

<u>Canada</u>

No information available

16. OTHER INFORMATION				
HMIS:	Health 2	Flammability 1	Reactivity 1	Personal Protection X
Key or legend to abbreviations and acronyms used in the safety data sheet				
Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTIONTWATWA (time-weighted average)STELSTEL (Short Term Exposure Limit)CeilingMaximum limit value				
ACGIH: (American Conference of Governmental Industrial Hygienists) A1 - Known Human Carcinogen A2 - Suspected Human Carcinogen A3 - Animal Carcinogen IARC: (International Agency for Research on Cancer) Group 1 - Carcinogenic to Humans Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans NTP: (National Toxicity Program) Known - Known Carcinogen Reasonably Anticipated to be a Human Carcinogen OSHA: (Occupational Safety & Health Administration) X - Present				

Revision Date

May-15-2019

Pursuant to NOM-018-STPS-2015

This information within is considered correct but is not exhaustive and will be used for guidance only, which is based on the current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet