

Print Date  
May-30-2015

Revision Date  
May-30-2015

Revision Number  
1

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

**Product identifier**

Product code **3529**  
Product name **Overprint Clear**  
Product category **3500 Series UV Durable Graphic Screen Ink**

**Other means of identification**

Synonyms None

**Recommended use of the chemical and restrictions on use**

Recommended use Printing operations

**Details of the supplier of the safety data sheet**

UNITED STATES	UNITED KINGDOM
Nazdar Company	Nazdar Limited
8501 Hedge Lane Terrace	Barton Road
Shawnee, KS 66227	Heaton Mersey
Tel: 1-913-422-1888	Stockport, England SK4 3EG
Tel: 1-800-677-4657	Tel: +44 161 442 2111
Fax: 1-913-422-2294	
<a href="http://www.nazdar.com">www.nazdar.com</a>	

**Emergency telephone number**

USA: Chemtrec: 1-800-424-9300  
Outside USA: Chemtrec: 1-703-527-3887  
24 Hour Emergency Phone Number

**2. HAZARDS IDENTIFICATION**

**Classification**

Skin Corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitization	Category 1B - (H317)
Specific target organ toxicity (repeated exposure)	Category 1 - (H372)
Chronic aquatic toxicity	Category 3 - (H412)

**Label elements**



**Signal Word**  
Danger

**Hazard Statements**

H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation

H372 - Causes damage to organs through prolonged or repeated exposure  
 H412 - Harmful to aquatic life with long lasting effects

P280 - Wear eye protection/ face protection  
 P260 - Do not breathe dust/fume/gas/mist/vapors/spray  
 P273 - Avoid release to the environment

**Hazards not otherwise classified (HNOC)**

May be harmful if swallowed. Harmful to aquatic life.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Mixture**

Component	CAS-No	Weight %	Trade Secret	Note
Acrylated Oligomer	Trade Secret	10 - 30	*	
Acrylated Oligomer	Trade Secret	10 - 30	*	
Glycol Ether Acrylate	Trade Secret	10 - 30	*	
Vinyl Functional Monomer	Trade Secret	10 - 30	*	
Glycol Ether Acrylate	Trade Secret	5 - 10	*	
Acrylated Monomer	Trade Secret	1 - 5	*	
Acrylated Monomer	Trade Secret	1 - 5	*	
Acrylated Oligomer	Trade Secret	1 - 5	*	
Photoinitiator	Trade Secret	1 - 5	*	

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**Description of first aid measures**

<b>General Advice</b>	Show this safety data sheet to the doctor in attendance.
<b>Eye Contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.
<b>Skin Contact</b>	Wash off immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.
<b>Inhalation</b>	Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.
<b>Ingestion</b>	DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

**Most important symptoms and effects, both acute and delayed**

None under normal use conditions.

**Indication of any immediate medical attention and special treatment needed**

**Notes to Physician** Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media**

Foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable Extinguishing Media**

No information available.

**Specific Hazards Arising from the Chemical**

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions. Hazardous polymerization may take place during a fire due to heat. Closed containers could violently rupture.

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

## **6. ACCIDENTAL RELEASE MEASURES**

### **Personal precautions, protective equipment and emergency procedures**

#### **Personal Precautions**

Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

#### **Environmental precautions**

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

#### **Methods and material for containment and cleaning up**

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

## **7. HANDLING AND STORAGE**

### **Precautions for safe handling**

#### **Handling**

Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Ensure adequate ventilation.

### **Conditions for safe storage, including any incompatibilities**

#### **Storage**

Keep at temperatures between 18°-32°C (65°-90°F). Keep containers tightly closed in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep out of the reach of children. Protect from direct sunlight. Keep away from open flames, hot surfaces and sources of ignition.

#### **Incompatible Products**

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

## **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

### **Control parameters**

#### **Exposure limits**

This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies

### **Appropriate engineering controls**

#### **Engineering Measures**

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.

### **Individual protection measures, such as personal protective equipment**

#### **Eye/face Protection**

Wear safety glasses with side shields (or goggles). If splashes are likely to occur. Wear

suitable face shield. Ensure that eyewash stations and safety showers are close to the workstation location.

**Skin Protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory Protection**

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.

**General Hygiene Considerations**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

<b>Physical State</b>	Liquid	<b>Appearance</b>	Colored Liquid
<b>Odor</b>	Mild Sweet Acrylic	<b>Odor Threshold</b>	No information available

**Property****Values****Remarks • Method**

pH		No data available	
Melting point/freezing point		No data available	
Boiling point/Boiling Range	> 149 °C / 300 °F		
Flash Point	> 94 °C / > 201 °F		Pensky Martens Closed Cup (PMCC)
Evaporation rate			No data available
Flammability Limit in Air			
Upper flammability limit			No data available
Lower flammability limit			No data available
Vapor Pressure			No data available
Vapor Density			No data available
Specific Gravity	1.08		
Water Solubility			No data available
Solubility in other solvents			No data available
Partition coefficient: n-octanol/water			No data available
Autoignition Temperature			No data available
Decomposition temperature			No data available
Kinematic viscosity			No data available
Dynamic viscosity			No data available

**Explosive Properties** No data available

**Oxidizing Properties** No data available

**Other Information**

**Photochemically Reactive** No  
**Weight Per Gallon (lbs/gal)** 9.01

VOC by weight % (less water)	VOC by volume % (less water)	VOC lbs/gal (less water)	VOC grams/liter (less water)
0-1	0-1	0-1	0-1

## 10. STABILITY AND REACTIVITY

**Reactivity**

No information available.

**Chemical stability**

Stable under normal conditions.

**Possibility of Hazardous Reactions**

None under normal processing. Do not store for longer periods at temperatures above 93°C (200°F).

**Conditions to avoid**

Temperatures above 93 °C / 200 °F. Protect from direct sunlight. Keep away from open flames, hot surfaces and sources of ignition.

**Incompatible materials**

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

**Hazardous Decomposition Products**

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO<sub>2</sub>). Carbon monoxide.

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure**

<b>Inhalation</b>	There is no data for this product.
<b>Eye Contact</b>	There is no data for this product.
<b>Skin Contact</b>	There is no data for this product.
<b>Ingestion</b>	There is no data for this product.

Component	Oral LD50
Glycol Ether Acrylate	4660 µL/kg ( Rat )
Acrylated Monomer	5 g/kg ( Rat )

Component	LD50 Dermal
Glycol Ether Acrylate	2540 µL/kg ( Rabbit )
Acrylated Monomer	13 g/kg ( Rabbit )
Acrylated Monomer	3600 µL/kg ( Rabbit )

**Information on toxicological effects**

**Symptoms** There is no data for this product.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

<b>Skin corrosion/irritation</b>	There is no data for this product.
<b>Eye damage/irritation</b>	There is no data for this product.
<b>Irritation</b>	There is no data for this product.
<b>Corrosivity</b>	There is no data for this product.
<b>Sensitisation</b>	There is no data for this product.
<b>Mutagenic Effects</b>	There is no data for this product.
<b>Reproductive Effects</b>	There is no data for this product.
<b>STOT - single exposure</b>	There is no data for this product.
<b>STOT - repeated exposure</b>	There is no data for this product.
<b>Chronic Toxicity</b>	There is no data for this product.
<b>Aspiration hazard</b>	There is no data for this product.
<b>Carcinogenicity</b>	This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 3,431.00 mg/kg

ATEmix (dermal)

8,623.00 mg/kg mg/l

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

None known

0% of the mixture consists of components(s) of unknown hazards to the aquatic environment

### Persistence and Degradability

No information available.

### Bioaccumulation

No information available.

### Other adverse effects

No information available

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

#### **Waste Disposal Methods**

Contain and dispose of waste according to local regulations.

#### **Contaminated Packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. TRANSPORT INFORMATION

### DOT

Proper Shipping Name

Not regulated

Printing Ink

### ICAO / IATA / IMDG / IMO

Proper Shipping Name

Not Regulated

Printing Ink

## 15. REGULATORY INFORMATION

### International Inventories

All components are listed on the TSCA Inventory. For further information, please contact: Supplier (manufacturer/importer/downstream user/distributor).

### U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS-No	Weight %	SARA 313 - Threshold Values
Glycol Ether Acrylate	Trade Secret	10 - 30	1.0
Glycol Ether Acrylate	Trade Secret	5 - 10	1.0

*The above glycol ether acrylate is considered a reactive chemical in ultraviolet curable inks. Once initiated by a high dose of ultraviolet light, this glycol ether acrylate rapidly polymerizes (i.e. hardens) and becomes part of the ink film. The polymerization process of UV curable inks is measured in milliseconds.*

### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:

Component	CAS-No	Weight %
Glycol Ether Acrylate	Trade Secret	10 - 30
Glycol Ether Acrylate	Trade Secret	5 - 10

### U.S. State Regulations

Component	Minnesota Right To Know
Acrylated Monomer	X

Component	New Jersey Right To Know
Glycol Ether Acrylate	X
Glycol Ether Acrylate	X

Component	Pennsylvania Right To Know
Glycol Ether Acrylate	X
Glycol Ether Acrylate	X

### California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects

### Canada

No information available

## 16. OTHER INFORMATION

HMIS:	Health	Flammability	Reactivity	Personal Protection
	2	1	1	X

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### **Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

TWA TWA (time-weighted average)  
 STEL STEL (Short Term Exposure Limit)  
 Ceiling Maximum limit value

#### **ACGIH: (American Conference of Governmental Industrial Hygienists)**

A1 - Known Human Carcinogen  
 A2 - Suspected Human Carcinogen  
 A3 - Animal Carcinogen

#### **IARC: (International Agency for Research on Cancer)**

Group 1 - Carcinogenic to Humans  
 Group 2A - Probably Carcinogenic to Humans  
 Group 2B - Possibly Carcinogenic to Humans

#### **NTP: (National Toxicity Program)**

Known - Known Carcinogen  
 Reasonably Anticipated to be a Human Carcinogen

#### **OSHA: (Occupational Safety & Health Administration)**

X - Present

Revision Date

May-30-2015

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of MSDS**