

Published Date  
Feb-06-2020

Revision Date  
Feb-06-2020

Revision Number  
2.6

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

**Product identifier**

Product code **36EC151**  
Product name **Econo Halftone Cyan Dense (MTR)**  
Product category **Vinyl Banner UV Screen Ink**

**Other means of identification**

Synonyms None

**Recommended use of the chemical and restrictions on use**

Recommended use Printing operations

**Details of the supplier of the safety data sheet**

UNITED STATES	UNITED KINGDOM
Nazdar Company	Nazdar Limited
8501 Hedge Lane Terrace	Barton Road
Shawnee, KS 66227	Heaton Mersey
Tel: +001-913-422-1888	Stockport, England SK4 3EG
Tel: +001-800-677-4657	Tel: +44 161 442 2111
Fax: +001-913-422-2294	
www.nazdar.com	

**Emergency telephone number**

USA: Chemtrec: +001-800-424-9300  
Outside USA: Chemtrec: +001-703-527-3887  
24 Hour Emergency Phone Number

**2. HAZARDS IDENTIFICATION**

**Classification**

Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitization	Category 1A - (H317)
Reproductive toxicity	Category 2 - (H361)
Specific target organ toxicity (repeated exposure)	Category 2 - (H373)
Chronic aquatic toxicity	Category 2 - (H411)

**Label elements**



**Signal Word**  
Warning

**Hazard Statements**

H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation  
H361fd - Suspected of damaging fertility. Suspected of damaging the unborn child  
H373 - May cause damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects

#### Precautionary Statements

P264 - Wash face, hands and any exposed skin thoroughly after handling

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P337 + P313 - If eye irritation persists: Get medical advice/attention

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention

P202 - Do not handle until all safety precautions have been read and understood

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P314 - Get medical advice/attention if you feel unwell

P273 - Avoid release to the environment

#### Hazards not otherwise classified (HNOC)

Causes mild skin irritation.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixture

Component	CAS-No	Weight %	Trade Secret	Note
Acrylated Monomer	Trade Secret	10 - 30	*	
Glycol Ether Acrylate	Trade Secret	10 - 30	*	
Vinyl Functional Monomer	Trade Secret	5 - 10	*	
Acrylated Monomer	Trade Secret	1 - 5	*	
Triethanolamine	102-71-6	1 - 5	*	
Glycol Ether Acrylate	Trade Secret	1 - 5	*	
Photoinitiator	Trade Secret	1 - 5	*	
Photoinitiator	Trade Secret	1 - 5	*	
Acrylated Monomer	Trade Secret	< 1	*	
Additive	Trade Secret	< 1	*	

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

#### Description of first aid measures

##### General Advice

Show this safety data sheet to the doctor in attendance.

##### Eye Contact

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.

##### Skin Contact

Wash off immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.

##### Inhalation

Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.

##### Ingestion

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

#### Most important symptoms and effects, both acute and delayed

None under normal use conditions.

#### Indication of any immediate medical attention and special treatment needed

##### Notes to Physician

Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media**

Foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable Extinguishing Media**

No information available.

**Specific Hazards Arising from the Chemical**

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions. Hazardous polymerization may take place during a fire due to heat. Closed containers could violently rupture.

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures****Personal Precautions**

Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

**Environmental precautions**

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

**Methods and material for containment and cleaning up**

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

## 7. HANDLING AND STORAGE

**Precautions for safe handling****Handling**

Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Ensure adequate ventilation.

**Conditions for safe storage, including any incompatibilities****Storage**

Keep at temperatures between 18°-32°C (65°-90°F). Keep containers tightly closed in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep out of the reach of children. Protect from direct sunlight. Keep away from open flames, hot surfaces and sources of ignition.

**Incompatible Products**

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters****Exposure limits**

Component	ACGIH TLV
Triethanolamine 102-71-6	TWA: 5 mg/m <sup>3</sup>

Component	Ontario TWAEV
Triethanolamine 102-71-6	TWA: 0.5 ppm TWA: 3.1 mg/m <sup>3</sup>

**Appropriate engineering controls****Engineering Measures**

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.

**Individual protection measures, such as personal protective equipment****Eye/Face Protection**

Wear safety glasses with side shields (or goggles). If splashes are likely to occur: Wear suitable face shield. Ensure that eyewash stations and safety showers are close to the workstation location.

**Skin Protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Hand Protection**

Chemical resistant protective gloves.  
Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding >480 minutes of permeation time): eg. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), polyvinylchloride (0.7 mm) and other  
Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers. Taking into account the varying conditions, the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.  
Due to different glove types, the manufacturer's directions for use should be observed. Replace gloves immediately when torn or any change in appearance is noticed such as dimension, color, flexibility.

**Respiratory Protection**

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material.

**General Hygiene Considerations**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES****Information on basic physical and chemical properties**

<b>Physical State</b>	Liquid	<b>Appearance</b>	Colored
<b>Odor</b>	Sweet Mild Acrylic	<b>Odor Threshold</b>	No information available
<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>	
pH		No data available	
Melting Point / Freezing Point		No data available	
Boiling Point / Boiling Range	> 149 °C / 300 °F		
Flash Point	> 94 °C / > 201 °F	Pensky Martens Closed Cup (PMCC)	
Evaporation rate		No data available	
Flammability Limit in Air			
Upper flammability limit		No data available	
Lower flammability limit		No data available	
Vapor Pressure		No data available	
Vapor Density		No data available	
Specific Gravity	1.11		
Water Solubility		No data available	
Solubility in other solvents		No data available	
Partition coefficient: n-octanol/water		No data available	
Autoignition Temperature		No data available	

Decomposition temperature No data available  
 Kinematic viscosity No data available  
 Dynamic viscosity No data available

Explosive Properties No data available  
 Oxidizing Properties No data available

**Other Information**

Photochemically Reactive No  
 Weight Per Gallon (lbs/gal) 9.22

VOC by weight % (less water)	VOC by volume % (less water)	VOC lbs/gal (less water)	VOC grams/liter (less water)
0-1	No information available	0-1	3.93

**10. STABILITY AND REACTIVITY****Reactivity**

No information available.

**Chemical stability**

Stable under normal conditions.

**Possibility of Hazardous Reactions**

None under normal processing. Do not store for longer periods at temperatures above 93°C (200°F).

**Conditions to avoid**

Temperatures above 93 °C / 200 °F. Protect from direct sunlight. Keep away from open flames, hot surfaces and sources of ignition.

**Incompatible materials**

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

**Hazardous Decomposition Products**

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO<sub>2</sub>). Carbon monoxide.

**11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

**Inhalation** Specific test data for the substance or mixture is not available.  
**Eye Contact** Specific test data for the substance or mixture is not available.  
**Skin Contact** Specific test data for the substance or mixture is not available.  
**Ingestion** Specific test data for the substance or mixture is not available.

Component	Oral LD50
Glycol Ether Acrylate	= 4660 µL/kg ( Rat )
Acrylated Monomer	= 5 g/kg ( Rat )
Triethanolamine 102-71-6	= 4190 mg/kg ( Rat )
Photoinitiator	= 1694 mg/kg ( Rat )

Component	Dermal LD50
Acrylated Monomer	= 3600 mg/kg ( Rabbit )
Triethanolamine 102-71-6	> 20000 mg/kg ( Rabbit )

Information on toxicological effects

**Symptoms** Specific test data for the substance or mixture is not available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Specific test data for the substance or mixture is not available.  
**Eye damage/irritation** Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components).  
**Irritation** Specific test data for the substance or mixture is not available.  
**Corrosivity** Specific test data for the substance or mixture is not available.  
**Sensitization** Specific test data for the substance or mixture is not available. May cause an allergic skin reaction. (based on components).  
**Mutagenic Effects** Specific test data for the substance or mixture is not available.  
**Carcinogenic effects** Specific test data for the substance or mixture is not available.  
**Reproductive Effects** Specific test data for the substance or mixture is not available. Suspected of damaging fertility. Suspected of damaging the unborn child. (based on components).  
**STOT - single exposure** Specific test data for the substance or mixture is not available.  
**STOT - repeated exposure** Specific test data for the substance or mixture is not available. May cause damage to organs through prolonged or repeated exposure. (based on components).  
**Chronic Toxicity** Specific test data for the substance or mixture is not available  
**Target Organ Effects** Liver, Respiratory system.  
**Aspiration hazard** Specific test data for the substance or mixture is not available.  
**Carcinogenicity** This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.

Numerical measures of toxicity - Product Information

**Unknown Acute Toxicity** 0 % of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (oral)** 4,687.00 mg/kg  
**ATEmix (dermal)** 8,162.00 mg/kg

**12. ECOLOGICAL INFORMATION**Ecotoxicity

Specific test data for the substance or mixture is not available. Toxic to aquatic life with long lasting effects. (based on components).

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Algae/aquatic plants
Triethanolamine 102-71-6	96h EC50 <i>Desmodesmus subspicatus</i> : = 169 mg/L 72h EC50 <i>Desmodesmus subspicatus</i> : = 216 mg/L

Component	Fish
Acrylated Monomer	96h LC50 <i>Danio rerio</i> : = 1.95 mg/L [static]
Vinyl Functional Monomer	96h LC50 <i>Danio rerio</i> : = 307 mg/L [static]
Triethanolamine 102-71-6	96h LC50 <i>Pimephales promelas</i> : > 1000 mg/L (static) 96h LC50 <i>Lepomis macrochirus</i> : 450 - 1000 mg/L (static) 96h LC50 <i>Pimephales promelas</i> : 10600 - 13000 mg/L (flow-through)
Acrylated Monomer	96h LC50 <i>Danio rerio</i> : = 5.74 mg/L [static]

**Persistence and Degradability**

No information available.

**Bioaccumulation**

No information available

Component	Partition coefficient
Triethanolamine 102-71-6	-2.53

**Other adverse effects**

No information available

### 13. DISPOSAL CONSIDERATIONS

**Waste treatment methods****Waste Disposal Methods**

Contain and dispose of waste according to local regulations.

**Contaminated Packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. TRANSPORT INFORMATION

**Note:**

This information is not intended to convey all specific transportation requirements relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation information can be found in the specific regulations for your mode of transportation. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

**DOT**

Not regulated

Exception: In the US and Canada except when all or part of the transportation is by vessel, containers 119 gallons/ 450 Liters and less are not regulated [see 49CFR 171.4 (c)(1)]  
If in quantities of 5L or less (per inner packaging) for liquids or 5KG or less (per inner packaging) for solids these items may be shipped as not regulated [additional general packaging requirements must be met see 49CFR 173.24] [see 49CFR 171.4 (c)(2)]

**ICAO / IATA / IMDG / IMO**

Not Regulated

Exception: If in quantities of 5L or less (per inner packaging) for liquids or 5KG or less (per inner packaging) for solids these items may be shipped as not regulated [additional general packaging requirements must be met see ICAO/IATA special provision A197]  
Exception: If in quantities of 5L or less (per inner packaging) for liquids or 5KG or less (per inner packaging) for solids these items may be shipped as not regulated [additional general packaging requirements must be met see IMDG code 2.10.2.7]

### 15. REGULATORY INFORMATION

**International Inventories**

All components are listed on the TSCA Inventory. For further information, please contact: Supplier (manufacturer/importer/downstream user/distributor).

**U.S. Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS-No	Weight %	SARA 313 - Threshold Values
Glycol Ether Acrylate	Trade Secret	10 - 30	1.0

Glycol Ether Acrylate	Trade Secret	1 - 5	1.0
-----------------------	--------------	-------	-----

The above glycol ether acrylate is considered a reactive chemical in ultraviolet curable inks. Once initiated by a high dose of ultraviolet light, this glycol ether acrylate rapidly polymerizes (i.e. hardens) and becomes part of the ink film. The polymerization process of UV curable inks is measured in milliseconds.

### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:

Component	CAS-No	Weight %
Glycol Ether Acrylate	Trade Secret	10 - 30
Glycol Ether Acrylate	Trade Secret	1 - 5
Xylenes (o-, m-, p- isomers)	1330-20-7	< 0.5

### U.S. State Regulations

Component	Massachusetts Right To Know
Triethanolamine 102-71-6	X

Component	Minnesota Right To Know
Acrylated Monomer	X
Triethanolamine 102-71-6	X

Component	New Jersey Right To Know
Glycol Ether Acrylate	X
Triethanolamine 102-71-6	X
Glycol Ether Acrylate	X

Component	Pennsylvania Right To Know
Glycol Ether Acrylate	X
Triethanolamine 102-71-6	X
Glycol Ether Acrylate	X

### California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects

### Canada

Component	NPRI - National Pollutant Release Inventory
Triethanolamine 102-71-6	Part 4 Substance

## 16. OTHER INFORMATION

<b>HMIS:</b>	<b>Health</b>	<b>Flammability</b>	<b>Reactivity</b>	<b>Personal Protection</b>
	2	1	1	X

### Key or legend to abbreviations and acronyms used in the safety data sheet

Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION



TWA TWA (time-weighted average)  
STEL STEL (Short Term Exposure Limit)  
Ceiling Maximum limit value

**ACGIH: (American Conference of Governmental Industrial Hygienists)**

A1 - Known Human Carcinogen  
A2 - Suspected Human Carcinogen  
A3 - Animal Carcinogen

**IARC: (International Agency for Research on Cancer)**

Group 1 - Carcinogenic to Humans  
Group 2A - Probably Carcinogenic to Humans  
Group 2B - Possibly Carcinogenic to Humans

**NTP: (National Toxicity Program)**

Known - Known Carcinogen  
Reasonably Anticipated to be a Human Carcinogen

**OSHA: (Occupational Safety & Health Administration)**

X - Present

**Revision Date**

Feb-06-2020

**Pursuant to NOM-018-STPS-2015**

This information within is considered correct but is not exhaustive and will be used for guidance only, which is based on the current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**