

# **SAFETY DATA SHEET**

Published Date May-15-2019 Revision Date May-15-2019 Revision Number 2.5

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier Product code Product name Product category

43358 Tinting White 4300 Series UV Screen Ink

Other means of identification Synonyms

Recommended use of the chemical and restrictions on useRecommended usePrinting operations

None

#### Details of the supplier of the safety data sheet

UNITED STATES Nazdar Company 8501 Hedge Lane Terrace Shawnee, KS 66227 Tel: +001-913-422-1888 Tel: +001-800-677-4657 Fax: +001-913-422-2294 www.nazdar.com UNITED KINGDOM Nazdar Limited Barton Road Heaton Mersey Stockport, England SK4 3EG Tel: +44 161 442 2111

#### Emergency telephone number

USA: Chemtrec: +001-800-424-9300 Outside USA: Chemtrec: +001-703-527-3887 24 Hour Emergency Phone Number

# 2. HAZARDS IDENTIFICATION

#### **Classification**

Skin Corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitization	Category 1A - (H317)
Reproductive toxicity	Category 1B - (H360FD)
Chronic aquatic toxicity	Category 3 - (H412)

#### Label elements



Signal Word Danger

Hazard Statements

H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H360FD - May damage fertility. May damage the unborn child

H412 - Harmful to aquatic life with long lasting effects

#### **Precautionary Statements**

P264 - Wash face, hands and any exposed skin thoroughly after handling

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P337 + P313 - If eye irritation persists: Get medical advice/attention

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention

P202 - Do not handle until all safety precautions have been read and understood

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P273 - Avoid release to the environment

#### Hazards not otherwise classified (HNOC)

Harmful to aquatic life.

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### <u>Mixture</u>

Component	CAS-No	Weight %	Trade Secret	Note
Acrylated Monomer	Trade Secret	10 - 30	*	
Titanium dioxide	13463-67-7	10 - 30	*	
Acrylated Monomer	Trade Secret	10 - 30	*	
Glycol Ether Acrylate	Trade Secret	5 - 10	*	
Silicon dioxide, amorphous	7631-86-9	5 - 10	*	
Photoinitiator	Trade Secret	1 - 5	*	
Photoinitiator	Trade Secret	1 - 5	*	
Photoinitiator	Trade Secret	1 - 5	*	

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

#### **Description of first aid measures**

General Advice Eye Contact	Show this safety data sheet to the doctor in attendance. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.
Skin Contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.
Inhalation	Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Most important symptoms and effects, both acute and delayed

None under normal use conditions.

# Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

# **5. FIRE-FIGHTING MEASURES**

#### Suitable Extinguishing Media

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

#### Unsuitable Extinguishing Media

No information available.

#### Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions. Hazardous polymerization may take place during a fire due to heat. Closed containers could violently rupture.

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

# 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

```
Personal Precautions
```

Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

#### Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

#### Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

Handling	Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Ensure adequate ventilation.	
Conditions for safe storage, including any incompatibilities		
Storage	Keep at temperatures between 18°-32°C (65°-90°F). Keep containers tightly closed in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep out of the reach of children. Protect from direct sunlight. Keep away from open flames, hot surfaces and sources of ignition.	
Incompatible Products	Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.	

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

#### Exposure limits

Component	ACGIH TLV	
Titanium dioxide	TWA: 10 mg/m <sup>3</sup>	
13463-67-7		
Component	OSHA PEL	
Titanium dioxide	TWA: 15 mg/m <sup>3</sup> total dust	
13463-67-7		
Component	OSHA PEL (vacated)	
Titanium dioxide	TWA: 10 mg/m <sup>3</sup> total dust	
13463-67-7		
Silicon dioxide, amorphous	TWA: 6 mg/m <sup>3</sup>	

7631-86-9		
Component	Ontario TWAEV	
Titanium dioxide	TWA: 10 mg/m <sup>3</sup>	
13463-67-7		

Component	Mexico OEL (TWA)
Titanium dioxide	TWA/VLE-PPT: 10 mg/m <sup>3</sup>
13463-67-7	STEL/PPT-CT: 20 mg/m <sup>3</sup>

# Appropriate engineering controls

Engineering Measures	Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.	
Individual protection measures, su	uch as personal protective equipment	
Eye/Face Protection	Wear safety glasses with side shields (or goggles). If splashes are likely to occur:. Wear suitable face shield. Ensure that eyewash stations and safety showers are close to the workstation location.	
Skin Protection	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.	
Hand Protection	Chemical resistant protective gloves. Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding >480 minutes of permeation time): eg. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), polyvinylchloride (0.7 mm) and other Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers. Taking into account the varying conditions, the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing. Due to different glove types, the manufacturer's directions for use should be observed. Replace gloves immediately when torn or any change in appearance is noticed such as dimension, color, flexibility.	
Respiratory Protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material.	
General Hygiene Consideration	<b>ns</b> Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended.	

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and Physical State Odor	<u>d chemical properties</u> Liquid Sweet Mild Acrylic	Appearance Odor Threshold	Colored Liquid No information available
<u>Property</u> pH Melting Point / Freezing Point Boiling Point / Boiling Range Flash Point Evaporation rate Flammability Limit in Air Upper flammability limit	<u>Values</u> > 149 °C / 300 °F > 94 °C / > 201 °F	Remarks • Method No data available No data available Pensky Martens Close No data available No data available	ed Cup (PMCC)

VOC by weight %	VOC by volume %	VOC lbs/gal	,
Weight Per Gallon (lbs/gal)	10.96		
Photochemically Reactive	No		
Other Information			
Oxidizing Properties	No data available		
Explosive Properties	No data available		
Dynamic viscosity		No data available	
Kinematic viscosity		No data available	
Autoignition Temperature Decomposition temperature		No data available No data available	
Partition coefficient: n-octanol/water		No data available	
Solubility in other solvents		No data available	
Water Solubility		No data available	
Specific Gravity	1.32		
Vapor Density		No data available	
Lower flammability limit Vapor Pressure		No data available No data available	

VOC by weight %<br/>(less water)<br/>0-1VOC by volume %<br/>(less water)<br/>0-1VOC lbs/gal<br/>(less water)<br/>0-1VOC grams/liter<br/>(less water)<br/>0-1

# **10. STABILITY AND REACTIVITY**

## **Reactivity**

No information available.

#### Chemical stability

Stable under normal conditions.

#### Possibility of Hazardous Reactions

None under normal processing. Do not store for longer periods at temperatures above 93°C (200°F).

# Conditions to avoid

Temperatures above 93 °C / 200 °F. Protect from direct sunlight. Keep away from open flames, hot surfaces and sources of ignition.

#### Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

# Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO2). Carbon monoxide.

# **11. TOXICOLOGICAL INFORMATION**

## Information on likely routes of exposure

Inhalation	Specific test data for the substance or mixture is not available.
Eye Contact	Specific test data for the substance or mixture is not available.
Skin Contact	Specific test data for the substance or mixture is not available.
Ingestion	Specific test data for the substance or mixture is not available.

Component	Oral LD50
Acrylated Monomer	= 5 g/kg (Rat)
Titanium dioxide	> 10000 mg/kg (Rat)
13463-67-7	
Acrylated Monomer	= 5190 mg/kg (Rat)
Glycol Ether Acrylate	= 4660 µL/kg (Rat)

Silicon dioxide, amorphous 7631-86-9	= 7900 mg/kg (Rat)
Photoinitiator	= 1694 mg/kg (Rat)

Component	Dermal LD50
Acrylated Monomer	= 3600 mg/kg (Rabbit)
Acrylated Monomer	= 5000 mg/kg (Rabbit)
Silicon dioxide, amorphous 7631-86-9	> 2000 mg/kg (Rabbit)

Component	Inhalation LC50
Silicon dioxide, amorphous	> 2.2 mg/L (Rat) 1 h
7631-86-9	

# Information on toxicological effects

Symptoms	Specific test data for the substance or mixture is not available.		
Delayed and immediate effects as well as chronic effects from short and long-term exposure			
Skin corrosion/irritation	Specific test data for the substance or mixture is not available. Causes skin irritation (pain, redness and swelling). (based on components).		
Eye damage/irritation	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components).		
Irritation	Specific test data for the substance or mixture is not available.		
Corrosivity	Specific test data for the substance or mixture is not available.		
Sensitization	Specific test data for the substance or mixture is not available. May cause an allergic skin reaction. (based on components).		
Mutagenic Effects	Specific test data for the substance or mixture is not available.		
Carcinogenic effects	Specific test data for the substance or mixture is not available.		
Reproductive Effects	Specific test data for the substance or mixture is not available. May damage fertility. May damage the unborn child. (based on components).		
STOT - single exposure	Specific test data for the substance or mixture is not available.		
STOT - repeated exposure	Specific test data for the substance or mixture is not available.		
Chronic Toxicity	Specific test data for the substance or mixture is not available		
Aspiration hazard	Specific test data for the substance or mixture is not available.		
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.		

Component IAR	NRC
Titanium dioxide Grou 13463-67-7	roup 2B

Component	OSHA
Titanium dioxide 13463-67-7	X
Acrylated Monomer	X

## Numerical measures of toxicity - Product Information

**Unknown Acute Toxicity** 

0 % of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document<br/>ATEmix (oral)38,605.00 mg/kg mg/l

# **12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

Specific test data for the substance or mixture is not available. Harmful to aquatic life with long lasting effects. (based on components).

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Algae/aquatic plants	
Silicon dioxide, amorphous	72h EC50 Pseudokirchneriella subcapitata: = 440 mg/L	
7631-86-9		
Component	Fish	
Silicon dioxide, amorphous	96h LC50 Brachydanio rerio: = 5000 mg/L (static)	
7631-86-9		
Component	Crustacea	
Silicon dioxide, amorphous	48h EC50 Ceriodaphnia dubia: = 7600 mg/L	
7631-86-9		

#### Persistence and Degradability

No information available.

## **Bioaccumulation**

No information available

#### Other adverse effects

No information available

# **13. DISPOSAL CONSIDERATIONS**

Waste treatment methods		
Waste Disposal Methods	Contain and dispose of waste according to local regulations.	
Contaminated Packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.	
	14. TRANSPORT INFORMATION	
Note:	This information is not intended to convey all specific transportation requirements relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation information can be found in the specific regulations for your mode of transportation. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.	
DOT Proper Shipping Name	Not regulated Printing Ink	
ICAO / IATA / IMDG / IMO Proper Shipping Name	Not Regulated Printing Ink	

# 15. REGULATORY INFORMATION

# International Inventories

All components are listed on the TSCA Inventory. For further information, please contact:. Supplier (manufacturer/importer/downstream user/distributor).

# U.S. Federal Regulations

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS-No	Weight %	SARA 313 - Threshold Values
Glycol Ether Acrylate	Trade Secret	5 - 10	1.0

The above glycol ether acrylate is considered a reactive chemical in ultraviolet curable inks. Once initiated by a high dose of ultraviolet light, this glycol ether acrylate rapidly polymerizes (i.e. hardens) and becomes part of the ink film. The polymerization process of UV curable inks is measured in milliseconds.

#### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:.

Component	CAS-No	Weight %
Glycol Ether Acrylate	Trade Secret	5 - 10
Xylenes (o-, m-, p- isomers)	1330-20-7	< 0.5

# U.S. State Regulations

	Massachusetts Right To Know
Titanium dioxide 13463-67-7	X
Silicon dioxide, amorphous 7631-86-9	X

	Minnesota Right To Know
Acrylated Monomer	X
Titanium dioxide 13463-67-7	X
Acrylated Monomer	X
Silicon dioxide, amorphous 7631-86-9	X

Component	New Jersey		
	Right To Know		
Titanium dioxide	X		
13463-67-7			
Glycol Ether Acrylate	X		

	Pennsylvania	
	Right To Know	
Titanium dioxide	X	
13463-67-7		
Glycol Ether Acrylate	X	
Silicon dioxide, amorphous	X	
7631-86-9		

#### California Prop. 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

Titanium dioxide Carcinogen	Component	California Prop. 65
	Titanium dioxide	

- This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

# <u>Canada</u>

No information available

16. OTHER INFORMATION								
HMIS:	Health	Flammability	Reactivity	Personal Protection				
	2	1	1	X				
Key or legend to abbreviations and acronyms used in the safety data sheet								
Legend - Section 8: EXPC TWA STEL Ceiling	TWA (time-	weighted average) t Term Exposure Limit)						
ACGIH: (American Conferent A1 - Known Human Carcinoger A2 - Suspected Human Carcino A3 - Animal Carcinogen IARC: (International Agency Group 1 - Carcinogenic to Hum Group 2A - Probably Carcinoge Group 2B - Possibly Carcinoge NTP: (National Toxicity Progr Known - Known Carcinogen Reasonably Anticipated to be a OSHA: (Occupational Safety X - Present	n ogen <b>for Research on Cancer)</b> ans enic to Humans nic to Humans <b>am)</b> Human Carcinogen							
Revision Date	May-15-201	9						

# **Revision Date**

#### Pursuant to NOM-018-STPS-2015

This information within is considered correct but is not exhaustive and will be used for guidance only, which is based on the current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

#### **End of Safety Data Sheet**