

# SAFETY DATA SHEET

Print DateRevision DateRevision NumberMay-30-2015May-30-20151

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Product identifier** 

Product code 16140

Product name Halftone Extender Base (MTR)

Product category 1600 PowerPrint® Series UV Screen Ink

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use
Recommended use Printing operations

Details of the supplier of the safety data sheet

UNITED STATES
UNITED KINGDOM
Nazdar Company
Nazdar Limited
8501 Hedge Lane Terrace
Shawnee, KS 66227
Barton Road
Heaton Mersey

Tel: 1-913-422-1888 Stockport, England SK4 3EG
Tel: 1-800-677-4657 Tel: +44 161 442 2111

Fax: 1-913-422-2294 www.nazdar.com

Emergency telephone number

USA: Chemtrec: 1-800-424-9300

Outside USA: Chemtrec: 1-703-527-3887 24 Hour Emergency Phone Number

# 2. HAZARDS IDENTIFICATION

### Classification

| Skin Corrosion/irritation         | Category 2 - (H315) |
|-----------------------------------|---------------------|
| Serious eye damage/eye irritation | Category 2 - (H319) |
| Skin sensitization                | Category 1 - (H317) |

#### Label elements



Signal Word Warning

### **Hazard Statements**

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

P280 - Wear eye protection/ face protection

#### Hazards not otherwise classified (HNOC)

No information available.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### <u>Mixture</u>

Inhalation

| Component             | CAS-No       | Weight % | Trade<br>Secret | Note |
|-----------------------|--------------|----------|-----------------|------|
| Acrylated Monomer     | Trade Secret | 30 - 60  | *               |      |
| Glycol Ether Acrylate | Trade Secret | 10 - 30  | *               |      |
| Acrylated Monomer     | Trade Secret | 10 - 30  | *               |      |
| Triethanolamine       | 102-71-6     | 1 - 5    | *               |      |
| Photoinitiator        | Trade Secret | 1 - 5    | *               |      |

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

#### Description of first aid measures

**General Advice** Show this safety data sheet to the doctor in attendance.

**Eye Contact** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Get medical attention if irritation develops and

persists.

**Skin Contact** Wash off immediately with soap and plenty of water for at least 15 minutes. Remove

contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention. Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or

stopped, administer artificial respiration. Get medical attention immediately.

**Ingestion** DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a

physician or poison control center immediately.

### Most important symptoms and effects, both acute and delayed

None under normal use conditions.

### Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

#### Suitable Extinguishing Media

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

### **Unsuitable Extinguishing Media**

No information available.

### Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions. Hazardous polymerization may take place during a fire due to heat. Closed containers could violently rupture.

# **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Revision Date May-30-2015

**Personal Precautions** 

Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people

away from and upwind of spill/leak.

### **Environmental precautions**

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

### Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

### 7. HANDLING AND STORAGE

# Precautions for safe handling

Handling Use personal protective equipment as required. Do not eat, drink or smoke when using this

product. Ensure adequate ventilation.

#### Conditions for safe storage, including any incompatibilities

Keep at temperatures between 18°-32°C (65°-90°F). Keep containers tightly closed in a dry, Storage

cool and well-ventilated place. Keep container closed when not in use. Keep out of the reach of children. Protect from direct sunlight. Keep away from open flames, hot surfaces

and sources of ignition.

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent. **Incompatible Products** 

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### **Exposure limits**

| Component                   | ACGIH TLV                |
|-----------------------------|--------------------------|
| Triethanolamine<br>102-71-6 | TWA: 5 mg/m <sup>3</sup> |

| Component       | Ontario TWAEV              |
|-----------------|----------------------------|
| Triethanolamine | TWA: 0.5 ppm               |
| 102-71-6        | TWA: 3.1 mg/m <sup>3</sup> |

#### Appropriate engineering controls

**Engineering Measures** Provide a good standard of general ventilation. Natural ventilation is from doors, windows

etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In

case of insufficient ventilation, wear suitable respiratory equipment.

### Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). If splashes are likely to occur:. Wear **Eye/face Protection** 

suitable face shield. Ensure that eyewash stations and safety showers are close to the

workstation location.

**Skin Protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls,

as appropriate, to prevent skin contact.

Revision Date May-30-2015

\_\_\_\_\_

Respiratory Protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Respiratory protection must be provided in

accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before

eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of

equipment, work area and clothing is recommended.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Liquid Appearance Colored Liquid

Odor Mild Sweet Acrylic Odor Threshold No information available

Property Values Remarks • Method

pH No data available

Melting point/freezing point No data available

Boiling point/Boiling Range  $> 149 \, ^{\circ}\text{C} \, / \, 300 \, ^{\circ}\text{F}$ 

Flash Point > 94 °C / > 201 °F Pensky Martens Closed Cup (PMCC)

Evaporation rate No data available

Flammability Limit in Air

Upper flammability limit

Lower flammability limit

No data available
No data available

Vapor PressureNo data availableVapor DensityNo data available

Specific Gravity 1.09

Water SolubilityNo data availableSolubility in other solventsNo data availablePartition coefficient: n-octanol/waterNo data availableAutoignition TemperatureNo data availableDecomposition temperatureNo data available

Autoignition TemperatureNo data availableDecomposition temperatureNo data availableKinematic viscosityNo data availableDynamic viscosityNo data available

Explosive Properties No data available Oxidizing Properties No data available

**Other Information** 

Photochemically Reactive No Weight Per Gallon (lbs/gal) 9.09

| VOC by weight % | VOC by volume %          | VOC lbs/gal  | VOC grams/liter |
|-----------------|--------------------------|--------------|-----------------|
| (less water)    | (less water)             | (less water) | (less water)    |
| 0-1             | No information available | 0-1          | 0-1             |

# 10. STABILITY AND REACTIVITY

#### Reactivity

No information available.

#### Chemical stability

Stable under normal conditions.

#### Possibility of Hazardous Reactions

None under normal processing. Do not store for longer periods at temperatures above 93°C (200°F).

### Conditions to avoid

Temperatures above 93 °C / 200 °F. Protect from direct sunlight. Keep away from open flames, hot surfaces and sources of ignition.

Revision Date May-30-2015

#### Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

### **Hazardous Decomposition Products**

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO2). Carbon monoxide.

### 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

InhalationThere is no data for this product.Eye ContactThere is no data for this product.Skin ContactThere is no data for this product.IngestionThere is no data for this product.

| Component                   | Oral LD50        |
|-----------------------------|------------------|
| Acrylated Monomer           | 5 g/kg(Rat)      |
| Glycol Ether Acrylate       | 4660 μL/kg(Rat)  |
| Acrylated Monomer           | 5190 μL/kg(Rat)  |
| Triethanolamine<br>102-71-6 | 4190 mg/kg (Rat) |

| Component                   | LD50 Dermal                             |  |  |
|-----------------------------|---|--|--|
| Acrylated Monomer           | 3600 μL/kg(Rabbit)                      |  |  |
| Glycol Ether Acrylate       | 2540 μL/kg (Rabbit)                     |  |  |
| Acrylated Monomer           | 5000 mg/kg (Rabbit)                     |  |  |
| Triethanolamine<br>102-71-6 | >16 mL/kg (Rat)<br>>2000 mg/kg (Rabbit) |  |  |

# Information on toxicological effects

**Symptoms** There is no data for this product.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation There is no data for this product. Eye damage/irritation There is no data for this product. Irritation There is no data for this product. Corrosivity There is no data for this product. Sensitisation There is no data for this product. There is no data for this product. **Mutagenic Effects** There is no data for this product. **Reproductive Effects** STOT - single exposure There is no data for this product. STOT - repeated exposure There is no data for this product. There is no data for this product **Chronic Toxicity** There is no data for this product. **Aspiration hazard** 

Carcinogenicity This product does not contain any carcinogens or potential carcinogens as listed by OSHA,

IARC or NTP.

### Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (oral)** 13,001.00 mg/kg

ATEmix (dermal) 25,185.00 mg/kg mg/l

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

None known

0% of the mixture consists of components(s) of unknown hazards to the aquatic environment

| Component       | Algae/aquatic plants                       |  |
|-----------------|--|--|
| Triethanolamine | 96h EC50 Desmodesmus subspicatus: 169 mg/L |  |
| 102-71-6        | 72h EC50 Desmodesmus subspicatus: 216 mg/L |  |

| Component       | Fish   |  |  |
|-----------------|--|--|--|
| Triethanolamine | 96h LC50 Pimephales promelas: 10600 - 13000 mg/L       |  |  |
| 102-71-6        | [flow-through]   |  |  |
|                 | 96h LC50 Lepomis macrochirus: 450 - 1000 mg/L [static] |  |  |
|                 | 96h LC50 Pimephales promelas: >1000 mg/L [static]      |  |  |

| Component       | Crustacea                         |
|-----------------|-----------------------------------|
| Triethanolamine | 24h EC50 Daphnia magna: 1386 mg/L |
| 102-71-6        |                                   |

### **Persistence and Degradability**

No information available.

#### **Bioaccumulation**

No information available.

| Component       | Partition coefficient |
|-----------------|-----------------------|
| Triethanolamine | -2.53                 |
| 102-71-6        |                       |

### Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

Waste Disposal Methods Contain and dispose of waste according to local regulations.

Contaminated Packaging Empty containers should be taken to an approved waste handling site for recycling or

disposal.

### 14. TRANSPORT INFORMATION

DOTNot regulatedProper Shipping NamePrinting Ink

ICAO / IATA / IMDG / IMONot RegulatedProper Shipping NamePrinting Ink

# 15. REGULATORY INFORMATION

# **International Inventories**

All components are listed on the TSCA Inventory. For further information, please contact:. Supplier (manufacturer/importer/downstream user/distributor).

### U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

| Component             | CAS-No       | Weight % | SARA 313 - Threshold<br>Values |
|-----------------------|--------------|----------|--------------------------------|
| Glycol Ether Acrylate | Trade Secret | 10 - 30  | 1.0                            |

The above glycol ether acrylate is considered a reactive chemical in ultraviolet curable inks. Once initiated by a high dose of ultraviolet light, this glycol ether acrylate rapidly polymerizes (i.e. hardens) and becomes part of the ink film. The polymerization process of UV curable inks is measured in milliseconds.

# Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:.

| Component             | CAS-No       | Weight % |
|-----------------------|--------------|----------|
| Glycol Ether Acrylate | Trade Secret | 10 - 30  |

### U.S. State Regulations

| Component                   | Massachusetts<br>Right To Know |
|-----------------------------|--------------------------------|
| Triethanolamine<br>102-71-6 | X                              |

| Component                   | Minnesota<br>Right To Know |
|-----------------------------|----------------------------|
| Acrylated Monomer           | X                          |
| Acrylated Monomer           | Х                          |
| Triethanolamine<br>102-71-6 | Х                          |

| Component                   | New Jersey<br>Right To Know |
|-----------------------------|-----------------------------|
| Glycol Ether Acrylate       | X                           |
| Triethanolamine<br>102-71-6 | X                           |

| Component                   | Pennsylvania<br>Right To Know |  |
|-----------------------------|-------------------------------|--|
| Glycol Ether Acrylate       | X                             |  |
| Triethanolamine<br>102-71-6 | X                             |  |

### California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects

# **Canada**

| Component       | NPRI - National Pollutant Release Inventory                    |  |
|-----------------|--|--|
| Triethanolamine | Part 4 Substance as set out in Section 65 of the List of Toxic |  |
| 102-71-6        | Substances in Schedule 1 of the Canadian Environmental         |  |
|                 | Protection Act, 1999   |  |

| 16. OTHER INFORMATION |               |              |            |                     |  |
|-----------------------|---------------|--------------|------------|---------------------|--|
| HMIS:                 | <b>Health</b> | Flammability | Reactivity | Personal Protection |  |
|                       | 2             | 1            | 1          | X                   |  |

# Key or legend to abbreviations and acronyms used in the safety data sheet

### Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value

#### ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated to be a Human Carcinogen
OSHA: (Occupational Safety & Health Administration)

X - Present

Revision Date May-30-2015

### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of MSDS**