

# SAFETY DATA SHEET

Published Date Jan-16-2023 Revision Date Jan-16-2023 Revision Number 2.7

### **1. IDENTIFICATION**

### Product identifier Product code 26363 **Product name** LED GR Rubine Red **Product category** 2600 Series UV-LED Screen Ink Other means of identification None Synonyms Recommended use of the chemical and restrictions on use **Recommended use** Industrial Printing Operations Details of the supplier of the safety data sheet UNITED KINGDOM UNITED STATES Nazdar Company Nazdar Limited Barton Road 8501 Hedge Lane Terrace Shawnee, KS 66227 Heaton Mersey Tel: +001-913-422-1888 Stockport, England SK4 3EG

Fax: +001-913-422-2294 www.nazdar.com

Tel: +001-800-677-4657

### Emergency telephone number

USA: Chemtrec: +001-800-424-9300 Outside USA: Chemtrec: +001-703-527-3887 24 Hour Emergency Phone Number

### 2. HAZARDS IDENTIFICATION

Tel: +44 161 442 2111

### **Classification**

Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitization	Category 1A - (H317)
Reproductive toxicity	Category 1B - (H360FD)
Specific target organ toxicity (repeated exposure)	Category 1 - (H372)
Chronic aquatic toxicity	Category 2 - (H411)

### Label elements



Danger

### Hazard statements

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H360FD - May damage fertility. May damage the unborn child

H372 - Causes damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects

### **Precautionary Statements**

P201 - Obtain special instructions before use

P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P273 - Avoid release to the environment

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P308 + P313 - IF exposed or concerned: Get medical advice/attention

### Hazards not otherwise classified (HNOC)

Causes mild skin irritation. Toxic to aquatic life.

### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

### Mixture

Chemical name	CAS No	Weight-%	Trade	Note
			secret	
Glycol Ether Acrylate	Not Available	30 - 60	*	
Vinyl Functional Monomer	Not Available	10 - 30	*	
Acrylated Monomer	Not Available	5 - 10	*	
Photoinitiator	Not Available	1 - 5	*	
Photoinitiator	Not Available	0.1 - < 1	*	
Photoinitiator	Not Available	0.1 - < 1	*	
Glycol Ether Acrylate	Not Available	0.1 - < 1	*	

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### **4. FIRST-AID MEASURES**

### Description of first aid measures

General Advice Eye Contact	Show this safety data sheet to the doctor in attendance. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.
Skin Contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.
Inhalation	If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately. Remove person to fresh air and keep comfortable for breathing.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

### Most important symptoms and effects, both acute and delayed

None under normal use conditions.

### Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

### **Suitable Extinguishing Media**

Water spray. Carbon dioxide (CO2). Foam. Dry chemical. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

### **Unsuitable Extinguishing Media**

No information available.

Specific Hazards Arising from the Chemical Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions. Hazardous

polymerization may take place during a fire due to heat. Closed containers could violently rupture.

### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Sealed containers may rupture when heated. Cool containers / tanks with water spray.

### 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

### Personal Precautions

Evacuate personnel to safe areas. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Avoid contact with eyes, skin and clothing. Ventilate the area. Avoid breathing dust or vapor.

### Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained. Keep out of drains, sewers, ditches and waterways.

### Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

### 7. HANDLING AND STORAGE

### Precautions for safe handling

Handling

Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Use personal protective equipment as required.

### Conditions for safe storage, including any incompatibilities

StorageKeep at temperatures between 18°-32°C (65°-90°F). Keep containers tightly closed in a dry,<br/>cool and well-ventilated place. Keep container closed when not in use. Keep out of the<br/>reach of children. Protect from direct sunlight. Keep away from open flames, hot surfaces<br/>and sources of ignition.

**Incompatible Products** 

Strong oxidizing agents. Strong acids. Strong bases. Reducing agent.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

### **Exposure limits**

Chemical name	Ontario TWAEV
Glycol Ether Acrylate	TWA: 25 ppm
	TWA: 141 mg/m <sup>3</sup>
	Skin

### Appropriate engineering controls

# **Engineering Measures** In case of insufficient ventilation, wear suitable respiratory equipment. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values.

### Individual protection measures, such as personal protective equipment

Eye/Face Protection	Wear safety glasses with side shields (or goggles). Ensure that eyewash stations and safety showers are close to the workstation location. If splashes are likely to occur:. Wear suitable face shield.
Skin Protection	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
Hand Protection	Chemical resistant protective gloves. Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding >480 minutes of permeation time): eg. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), polyvinylchloride (0.7 mm) and other Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers. Taking into account the varying conditions, the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing. Due to different glove types, the manufacturer's directions for use should be observed. Replace gloves immediately when torn or any change in appearance is noticed such as dimension, color, flexibility.
Respiratory Protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material.
General Hygiene Consideration	Is Handle in accordance with good industrial hygiene and safety practice. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and c			
Physical state	Liquid	Appearance	Colored
Odor	Mild Sweet Acrylic	Odor Threshold	No information available
Property_	Values	Remarks • Method	
рН		No data available	
Melting Point / Freezing Point	No information available	No data available	
Boiling Point / Boiling Range	> 149 °C / 300 °F		
Flash Point	> 94 °C / > 201 °F	Pensky Martens Closed	Cup (PMCC)
Evaporation rate		No data available	
Flammability Limit in Air			
Upper flammability limit		No data available	
Lower flammability limit		No data available	
Vapor Pressure		No data available	
Vapor Density		No data available	
Specific Gravity	1.09		
Water Solubility		No data available	
Solubility in other solvents		No data available	
Partition coefficient: n-octanol/water		No data available	
Autoignition Temperature	No information available	No data available	
Hyphen		No data available	
Kinematic viscosity		No data available	
Dynamic viscosity		No data available	
Explosive Properties	No data available		
Oxidizing Properties	No data available		
Other information			

Photochemically Reactive	No		
Weight Per Gallon (Ibs/gal)	9.06		

VOC by weight %	VOC by volume %	VOC lbs/gal	VOC grams/liter
(less water)	(less water)	(less water)	(less water)
0-1	0-1	0-1	4.78

### **10. STABILITY AND REACTIVITY**

### Reactivity

No information available.

### Chemical stability

Stable under normal conditions.

### Possibility of hazardous reactions

None under normal processing. Do not store for longer periods at temperatures above 93°C (200°F).

### **Conditions to avoid**

Temperatures above 93 °C / 200 °F. Protect from direct sunlight. Keep away from open flames, hot surfaces and sources of ignition.

### Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases. Reducing agent.

<u>Hazardous decomposition products</u> Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide. Carbon dioxide (CO2).

### **11. TOXICOLOGICAL INFORMATION**

### Information on likely routes of exposure

Inhalation	Specific test data for the substance or mixture is not available.
Eye Contact	Specific test data for the substance or mixture is not available.
Skin Contact	Specific test data for the substance or mixture is not available.
Ingestion	Specific test data for the substance or mixture is not available.

Oral LD50
= 4660 µL/kg (Rat)
= 4890 mg/kg (Rat)
= 1850 mg/kg (Rat)

Dermal LD50
= 1700 mg/kg (Rabbit)
> 3000 mg/kg (Rabbit)
> 2000 mg/kg (Rat)
> 2000 mg/kg (Rat)
> 2000 mg/kg (Rat)
= 5 mL/kg (Rabbit)

Chemical name	Inhalation LC50
Vinyl Functional Monomer	> 1.6 mg/L (Rat)8 h
Glycol Ether Acrylate	> 0.057 mg/L (Rat)8 h

Symptoms related to the physical, chemical and toxicological characteristics			
Symptoms	Specific test data for the substance or mixture is not available.		
Delayed and immediate effects	as well as chronic effects from short and long-term exposure		
Skin corrosion/irritation Eye damage/irritation	Specific test data for the substance or mixture is not available. Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components).		
Irritation Corrosivity Sensitization	Specific test data for the substance or mixture is not available. Specific test data for the substance or mixture is not available. Specific test data for the substance or mixture is not available. May cause an allergic skin reaction. (based on components).		
Mutagenic Effects Carcinogenic effects Reproductive Effects	Specific test data for the substance or mixture is not available. Specific test data for the substance or mixture is not available. Specific test data for the substance or mixture is not available. May damage fertility. May damage the unborn child. (based on components).		
STOT - single exposure STOT - repeated exposure	Specific test data for the substance or mixture is not available. Specific test data for the substance or mixture is not available. Causes damage to organs through prolonged or repeated exposure. (based on components).		
Chronic Toxicity Target organ effects Aspiration hazard Carcinogenicity	Specific test data for the substance or mixture is not available Liver, Respiratory system. Specific test data for the substance or mixture is not available. This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.		

### Numerical measures of toxicity - Product Information

Unknown acute toxicity	0 % of the mixture consists of ingredient(s) of unknown toxicity
The following values are calculated	based on chapter 3.1 of the GHS document
ATEmix (oral)	2,073.30
ATEmix (dermal)	7,049.30

## **12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

Specific test data for the substance or mixture is not available. Toxic to aquatic life with long lasting effects. (based on components).

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants
2-Phenoxyethanol	72h EC50 Desmodesmus subspicatus: > 500 mg/L
122-99-6	
Chemical name	Fish
N-vinylcaprolactam	96h LC50 Danio rerio: = 307 mg/L (static)
2235-00-9	
Isobornyl acrylate	96h LC50 Danio rerio: = 0.704 mg/L (semi-static)
5888-33-5	
1-Propanone, 2-methyl-1-[4-(methylthio)phenyl]-2-(4-morpholinyl)-	96h LC50 Danio rerio: = 9 mg/L (static)
71868-10-5	
2-Phenoxyethanol	96h LC50 Pimephales promelas: 337 - 352 mg/L (flow-through)
122-99-6	96h LC50 Pimephales promelas: = 366 mg/L (static)

Chemical name	Crustacea
2-Phenoxyethanol	48h EC50 Daphnia magna: > 500 mg/L
122-99-6	

### Persistence and Degradability

No information available.

### **Bioaccumulation**

No information available

Chemical name	Partition coefficient
Glycol Ether Acrylate	1.13

### **13. DISPOSAL CONSIDERATIONS** Waste treatment methods Waste Disposal Methods Contain and dispose of waste according to local regulations. Empty containers should be taken to an approved waste handling site for recycling or **Contaminated Packaging** disposal. **14. TRANSPORT INFORMATION** Note: This information is not intended to convey all specific transportation requirements relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation information can be found in the specific regulations for your mode of transportation. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material. Not regulated DOT Exception: In the US and Canada except when all or part of the transportation is by vessel. containers 119 gallons/ 450 Liters and less are not regulated [see 49CFR 171.4 (c)(1)] 49CFR 171.4 (c)(2) applies only to marine pollutants. These items may be shipped as "not regulated" and no marine pollutant mark is required if in guantities of 5L or less (per inner packaging) for liquids or 5KG or less (per inner packaging) for solids and the packaging used meets the defined standards [see 49CFR 173.24 for general packaging requirements]. Not Regulated ICAO / IATA / IMDG / IMO ICAO/IATA Special Provision A197 applies only to environmentally hazardous substances, UN3077 and UN3082. These items may be shipped as "not regulated" if in quantities of 5L or less (per inner packaging) for liquids or 5KG or less (per inner packaging) for solids and the packaging used meets the defined standards. IMDG code 2.10.2.7 applies only to marine pollutants. These items may be shipped as "not regulated" and no marine pollutant mark is required if in guantities of 5L or less (per inner packaging) for liquids or 5KG or less (per inner packaging) for solids and the packaging used meets the defined standards.

## **15. REGULATORY INFORMATION**

International Inventories

For further information, please contact:. All components are listed on the TSCA Inventory. Supplier (manufacturer/importer/downstream user/distributor).

### U.S. Federal Regulations

### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

······	SARA 313 - Threshold Values %
Available 30 - 60	1.0
	AS No Weight-% Available 30 - 60

The above glycol ether acrylate is considered a reactive chemical in ultraviolet curable inks. Once initiated by a high dose of ultraviolet light, this glycol ether acrylate rapidly polymerizes (i.e. hardens) and becomes part of the ink film. The polymerization process of UV curable inks is measured in milliseconds.

<u>Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)</u> This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:.

Chemical name	CAS No	Weight-%
Glycol Ether Acrylate	Not Available	30 - 60
Xylenes (o-, m-, p- isomers)	1330-20-7	0.1 - < 1
Glycol Ether Acrylate	Not Available	0.1 - < 1

### **US State Regulations**

Chemical name	New	w Jersey
Glycol Ether Acrylate	X	
Glycol Ether Acrylate	X	

Chemical name	Pennsylvania
Glycol Ether Acrylate	X
Glycol Ether Acrylate	X

### **California Proposition 65**

This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects

### **Canada**

No information available

Chemical name	NPRI - National Pollutant Release Inventory
Glycol Ether Acrylate	Part 4 Substance (as set out in Section 65 of the List of Toxic
	Substances in Schedule 1 of the Canadian Environmental
	Protection Act, 1999)

16. OTHER INFORMATION					
<u>HMIS</u>	Health hazards 2	Flammability 1	Reactivity 1	Personal Protection X	
Key or legend to abbreviations and acronyms used in the safety data sheet					
Legend - Section	8: EXPOSURE CONTROLS/PER	SONAL PROTECTION			
TWĂ					
STEL	STEL (Short	STEL (Short Term Exposure Limit)			
Ceiling	Maximum lim	it value			
ACGIH: (American C	conference of Governmental Indust	trial Hygienists)			

A1 - Known Human Carcinogen
A2 - Suspected Human Carcinogen
A3 - Animal Carcinogen
IARC: (International Agency for Research on Cancer)
Group 1 - Carcinogenic to Humans
Group 2A - Probably Carcinogenic to Humans
Group 3 - Not Classifiable as to Carcinogenicity in Humans
NTP: (National Toxicity Program)
Known - Known Carcinogen
Reasonably Anticipated to be a Human Carcinogen
OSHA: (Occupational Safety & Health Administration)
X - Present

Revision Date Jan-16-2023

### Pursuant to NOM-018-STPS-2015

This information within is considered correct but is not exhaustive and will be used for guidance only, which is based on the current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

### **End of Safety Data Sheet**