

# SAFETY DATA SHEET

Published DateRevision DateRevision NumberJan-16-2023Jan-16-20232.7

# 1. IDENTIFICATION

**Product identifier** 

Product code 26HTM

Product name LED GR Halftone Magenta

Product category 2600 Series UV-LED Screen Ink

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use
Recommended use Industrial Printing Operations

Details of the supplier of the safety data sheet

UNITED STATES
UNITED KINGDOM
Nazdar Company
Nazdar Limited
8501 Hedge Lane Terrace
Shawnee, KS 66227
Barton Road
Heaton Mersey

Tel: +001-913-422-1888 Stockport, England SK4 3EG Tel: +001-800-677-4657 Tel: +44 161 442 2111

Fax: +001-913-422-2294 www.nazdar.com

Emergency telephone number

USA: Chemtrec: +001-800-424-9300

Outside USA: Chemtrec: +001-703-527-3887

24 Hour Emergency Phone Number

# 2. HAZARDS IDENTIFICATION

### Classification

Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitization	Category 1A - (H317)
Reproductive toxicity	Category 1B - (H360FD)
Specific target organ toxicity (repeated exposure)	Category 1 - (H372)
Chronic aquatic toxicity	Category 2 - (H411)

### Label elements







### Signal word Danger

# **Hazard statements**

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H360FD - May damage fertility. May damage the unborn child

H372 - Causes damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects

### **Precautionary Statements**

P201 - Obtain special instructions before use

P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P273 - Avoid release to the environment

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P308 + P313 - IF exposed or concerned: Get medical advice/attention

#### Hazards not otherwise classified (HNOC)

Causes mild skin irritation. Toxic to aquatic life.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixture

Chemical name	CAS No	Weight-%	Trade secret	Note
Glycol Ether Acrylate	Not Available	30 - 60	*	
Vinyl Functional Monomer	Not Available	10 - 30	*	
Acrylated Monomer	Not Available	5 - 10	*	
Photoinitiator	Not Available	1 - 5	*	
Photoinitiator	Not Available	0.1 - < 1	*	
Additive	Not Available	0.1 - < 1	*	
Photoinitiator	Not Available	0.1 - < 1	*	

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST-AID MEASURES

#### Description of first aid measures

**General Advice** Show this safety data sheet to the doctor in attendance.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Get medical attention if irritation develops and

persists.

**Skin Contact** Wash off immediately with soap and plenty of water for at least 15 minutes. Remove

contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.

Inhalation If breathing is irregular or stopped, administer artificial respiration. Get medical attention

immediately. Remove person to fresh air and keep comfortable for breathing.

**Ingestion** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a

physician or poison control center immediately.

# Most important symptoms and effects, both acute and delayed

None under normal use conditions.

# Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

# **Suitable Extinguishing Media**

Water spray. Carbon dioxide (CO2). Foam. Dry chemical. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

# **Unsuitable Extinguishing Media**

No information available.

# **Specific Hazards Arising from the Chemical**

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions. Hazardous

polymerization may take place during a fire due to heat. Closed containers could violently rupture.

### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Sealed containers may rupture when heated. Cool containers / tanks with water spray.

# 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

**Personal Precautions** Evacuate personnel to safe areas. Remove all sources of ignition. Keep people away from

and upwind of spill/leak. Avoid contact with eyes, skin and clothing. Ventilate the area. Avoid

breathing dust or vapor.

#### **Environmental precautions**

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained. Keep out of drains, sewers, ditches and waterways.

# Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

# 7. HANDLING AND STORAGE

### Precautions for safe handling

Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Use Handling

personal protective equipment as required.

# Conditions for safe storage, including any incompatibilities

Keep at temperatures between 18°-32°C (65°-90°F). Keep containers tightly closed in a dry, Storage

> cool and well-ventilated place. Keep container closed when not in use. Keep out of the reach of children. Protect from direct sunlight. Keep away from open flames, hot surfaces

and sources of ignition.

Strong oxidizing agents. Strong acids. Strong bases. Reducing agent. **Incompatible Products** 

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# Control parameters

#### **Exposure limits**

This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies

# **Appropriate engineering controls**

**Engineering Measures** In case of insufficient ventilation, wear suitable respiratory equipment. Provide a good

standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to

consider national Occupational Exposure Limits or other equivalent values.

#### Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Ensure that eyewash stations and safety **Eye/Face Protection** 

showers are close to the workstation location. If splashes are likely to occur:. Wear suitable

face shield.

**Skin Protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as

appropriate, to prevent skin contact.

**Hand Protection** Chemical resistant protective gloves.

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding >480 minutes of permeation time): eg. nitrile rubber (0.4 mm), chloroprene

rubber (0.5 mm), polyvinylchloride (0.7 mm) and other

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers. Taking into account the varying conditions, the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time

determined through testing.

Due to different glove types, the manufacturer's directions for use should be observed. Replace gloves immediately when torn or any change in appearance is noticed such as

dimension, color, flexibility.

**Respiratory Protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of

the material.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before eating, drinking or

No data available

smoking. Wash contaminated clothing before reuse.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid Appearance Colored

Odor Mild Sweet Acrylic Odor Threshold No information available

PropertyValuesRemarks • MethodpHNo data available

Melting Point / Freezing PointNo information availableBoiling Point / Boiling Range> 149 °C / 300 °F

Flash Point > 94 °C / > 201 °F Pensky Martens Closed Cup (PMCC)

Evaporation rate No data available

Flammability Limit in Air

Upper flammability limitNo data availableLower flammability limitNo data availableVapor PressureNo data available

Vapor Pressure
No data available
No data available

Specific Gravity

1.1

Water Solubility

No data available

Solubility in other solvents

No data available
Partition coefficient: n-octanol/water

No data available

Autoignition TemperatureNo information availableNo data availableHyphenNo data available

HyphenNo data availableKinematic viscosityNo data availableDynamic viscosityNo data available

Explosive PropertiesNo data availableOxidizing PropertiesNo data available

Other information

Photochemically Reactive No Weight Per Gallon (lbs/gal) 9.15

VOC by weight %	VOC by volume %	VOC lbs/gal	VOC grams/liter
(less water)	(less water)	(less water)	(less water)
0-1	No information available	0-1	

# 10. STABILITY AND REACTIVITY

#### Reactivity

No information available.

### **Chemical stability**

Stable under normal conditions.

# Possibility of hazardous reactions

None under normal processing. Do not store for longer periods at temperatures above 93°C (200°F).

#### Conditions to avoid

Temperatures above 93 °C / 200 °F. Protect from direct sunlight. Keep away from open flames, hot surfaces and sources of ignition.

### **Incompatible materials**

Strong oxidizing agents. Strong acids. Strong bases. Reducing agent.

#### Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide. Carbon dioxide (CO2).

# 11. TOXICOLOGICAL INFORMATION

# Information on likely routes of exposure

Inhalation Specific test data for the substance or mixture is not available. **Eye Contact** Specific test data for the substance or mixture is not available. **Skin Contact** Specific test data for the substance or mixture is not available. Specific test data for the substance or mixture is not available. Ingestion

Chemical name	Oral LD50
Glycol Ether Acrylate	= 4660 μL/kg (Rat)
Acrylated Monomer	= 4890 mg/kg(Rat)

Chemical name	Dermal LD50
Vinyl Functional Monomer	= 1700 mg/kg(Rabbit)
Acrylated Monomer	> 3000 mg/kg(Rabbit)
Photoinitiator	> 2000 mg/kg(Rat)
Photoinitiator	> 2000 mg/kg(Rat)
Photoinitiator	> 2000 mg/kg(Rat)

Chemical name	Inhalation LC50
Vinyl Functional Monomer	> 1.6 mg/L (Rat)8 h

### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Specific test data for the substance or mixture is not available.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Specific test data for the substance or mixture is not available. Skin corrosion/irritation

**Eye damage/irritation** Specific test data for the substance or mixture is not available. Causes serious eye irritation.

(based on components).

IrritationSpecific test data for the substance or mixture is not available.CorrosivitySpecific test data for the substance or mixture is not available.

Sensitization Specific test data for the substance or mixture is not available. May cause an allergic skin

reaction. (based on components).

Mutagenic EffectsSpecific test data for the substance or mixture is not available.Carcinogenic effectsSpecific test data for the substance or mixture is not available.

Reproductive Effects Specific test data for the substance or mixture is not available. May damage fertility. May

damage the unborn child. (based on components).

**STOT - single exposure** Specific test data for the substance or mixture is not available.

STOT - repeated exposure Specific test data for the substance or mixture is not available. Causes damage to organs

through prolonged or repeated exposure. (based on components).

Chronic Toxicity Specific test data for the substance or mixture is not available

Target organ effects Liver, Respiratory system.

**Aspiration hazard** Specific test data for the substance or mixture is not available.

Carcinogenicity This product does not contain any carcinogens or potential carcinogens as listed by OSHA,

IARC or NTP.

# Numerical measures of toxicity - Product Information

**Unknown acute toxicity** 0 % of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (oral)** 2,036.70 mg/kg **ATEmix (dermal)** 6,924.70 mg/kg mg/l

### 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

Specific test data for the substance or mixture is not available. Toxic to aquatic life with long lasting effects. (based on components).

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Fish
N-vinylcaprolactam	96h LC50 Danio rerio: = 307 mg/L (static)
2235-00-9	
Isobornyl acrylate	96h LC50 Danio rerio: = 0.704 mg/L (semi-static)
5888-33-5	
1-Propanone, 2-methyl-1-[4-(methylthio)phenyl]-2-(4-morpholinyl)-	96h LC50 Danio rerio: = 9 mg/L (static)
71868-10-5	

# Persistence and Degradability

No information available.

### Bioaccumulation

No information available

# 13. DISPOSAL CONSIDERATIONS

# Waste treatment methods

**Waste Disposal Methods** 

Contain and dispose of waste according to local regulations.

**Contaminated Packaging** 

Empty containers should be taken to an approved waste handling site for recycling or

disposal.

# 14. TRANSPORT INFORMATION

Note:

This information is not intended to convey all specific transportation requirements relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation information can be found in the specific regulations for your mode of transportation. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

DOT

Not regulated

Exception: In the US and Canada except when all or part of the transportation is by vessel, containers 119 gallons/ 450 Liters and less are not regulated [see 49CFR 171.4 (c)(1)]

49CFR 171.4 (c)(2) applies only to marine pollutants. These items may be shipped as "not regulated" and no marine pollutant mark is required if in quantities of 5L or less (per inner packaging) for liquids or 5KG or less (per inner packaging) for solids and the packaging used meets the defined standards [see 49CFR 173.24 for general packaging requirements].

# ICAO / IATA / IMDG / IMO

Not Regulated

ICAO/IATA Special Provision A197 applies only to environmentally hazardous substances, UN3077 and UN3082. These items may be shipped as "not regulated" if in quantities of 5L or less (per inner packaging) for liquids or 5KG or less (per inner packaging) for solids and the packaging used meets the defined standards.

IMDG code 2.10.2.7 applies only to marine pollutants. These items may be shipped as "not regulated" and no marine pollutant mark is required if in quantities of 5L or less (per inner packaging) for liquids or 5KG or less (per inner packaging) for solids and the packaging used meets the defined standards.

# 15. REGULATORY INFORMATION

#### **International Inventories**

For further information, please contact:. All components are listed on the TSCA Inventory. Supplier (manufacturer/importer/downstream user/distributor).

# **U.S. Federal Regulations**

# **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Glycol Ether Acrylate	Not Available	30 - 60	1.0

The above glycol ether acrylate is considered a reactive chemical in ultraviolet curable inks. Once initiated by a high dose of ultraviolet light, this glycol ether acrylate rapidly polymerizes (i.e. hardens) and becomes part of the ink film. The polymerization process of UV curable inks is measured in milliseconds.

# Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:.

Chemical name	CAS No	Weight-%
Glycol Ether Acrylate	Not Available	30 - 60

# **US State Regulations**

Chemical name	New Jersey
Glycol Ether Acrylate	X

Chemical name	Pennsylvania
Glycol Ether Acrylate	X

#### **California Proposition 65**

This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects

#### Canada

No information available

# **16. OTHER INFORMATION**

HMIS Health hazards Flammability Reactivity Personal Protection

# Key or legend to abbreviations and acronyms used in the safety data sheet

# Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value

# ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen
A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

# IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated to be a Human Carcinogen OSHA: (Occupational Safety & Health Administration)

X - Present

Revision Date Jan-16-2023

### Pursuant to NOM-018-STPS-2015

This information within is considered correct but is not exhaustive and will be used for guidance only, which is based on the current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**