

SAFETY DATA SHEET

Published DateRevision DateRevision NumberAug-09-2023Aug-09-20232.6

1. IDENTIFICATION

Product identifier

Product code PA21
Product name Yellow

Product category PA Series SV Screen Ink

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use
Recommended use Industrial Printing Operations

Details of the supplier of the safety data sheet

UNITED STATES
UNITED KINGDOM
Nazdar Company
Nazdar Limited
8501 Hedge Lane Terrace
Shawnee, KS 66227
Barton Road
Heaton Mersey

Tel: +001-913-422-1888 Stockport, England SK4 3EG
Tel: +001-800-677-4657 Tel: +44 161 442 2111

Fax: +001-913-422-2294 www.nazdar.com

Emergency telephone number

USA: Chemtrec: +001-800-424-9300

Outside USA: Chemtrec: +001-703-527-3887

24 Hour Emergency Phone Number

2. HAZARDS IDENTIFICATION

Classification

Carcinogenicity	Category 2 - (H351)
Aspiration hazard	Category 1 - (H304)
Chronic aquatic toxicity	Category 2 - (H411)
Flammable liquids	Category 3 - (H226)

Label elements







Signal word Danger

Hazard statements

H226 - Flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H351 - Suspected of causing cancer

H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P273 - Avoid release to the environment

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor

P331 - Do NOT induce vomiting

P403 + P235 - Store in a well-ventilated place. Keep cool

Hazards not otherwise classified (HNOC)

Causes mild skin irritation. Toxic to aquatic life.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical name	CAS No	Weight-%	Trade secret	Note
Solvent naphtha, petroleum, heavy aromatic	64742-94-5	30 - 60	*	
Titanium Dioxide	13463-67-7	5 - 10	*	
Solvent naphtha, petroleum, light aromatic	64742-95-6	1 - 5	*	
Naphthalene (constituent)	91-20-3	1 - 5	*	1
Xylenes (o-, m-, p- isomers)	1330-20-7	1 - 5	*	
1,2,4-Trimethylbenzene (constituent)	95-63-6	1 - 5	*	1
Ethyl benzene (constituent)	100-41-4	0.1 - < 1	*	1

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

Note

Inhalation

4. FIRST-AID MEASURES

Description of first aid measures

General Advice Show this safety data sheet to the doctor in attendance.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Get medical attention if irritation develops and

persists.

Skin Contact Wash off immediately with soap and plenty of water for at least 15 minutes. Remove

contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention. Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or

stopped, administer artificial respiration. Get medical attention immediately.

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a

physician or poison control center immediately.

Most important symptoms and effects, both acute and delayed

None under normal use conditions.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

^{1.} Hazardous Constituent contained in Complex Substance(s) required for disclosure

No information available.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and

clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people

away from and upwind of spill/leak.

Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Use personal protective equipment as required. Do not eat, drink or smoke when using this

product. Ensure adequate ventilation.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open

flames, hot surfaces and sources of ignition. Keep container closed when not in use. Keep

out of the reach of children.

Incompatible Products Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits

Chemical name	ACGIH TLV
Titanium Dioxide	TWA: 0.2 mg/m³ nanoscale respirable particulate matter
13463-67-7	TWA: 2.5 mg/m³ finescale respirable particulate matter
Naphthalene (constituent)	TWA: 10 ppm
91-20-3	Skin
Xylenes (o-, m-, p- isomers)	TWA: 20 ppm
1330-20-7	
1,2,4-Trimethylbenzene (constituent)	TWA: 10 ppm
95-63-6	
Ethyl benzene (constituent)	TWA: 20 ppm
100-41-4	

Chemical name	OSHA PEL

Titanium Dioxide 13463-67-7	TWA: 15 mg/m³ total dust
1 ' ' '	TWA: 10 ppm TWA: 50 mg/m ³
	TWA: 100 ppm TWA: 435 mg/m ³
, , ,	TWA: 100 ppm TWA: 435 mg/m³

Chemical name	OSHA PEL (vacated)
Titanium Dioxide	TWA: 10 mg/m³ total dust
13463-67-7	
Naphthalene (constituent)	TWA: 10 ppm
91-20-3	TWA: 50 mg/m ³
	STEL: 15 ppm
	STEL: 75 mg/m³
Xylenes (o-, m-, p- isomers)	TWA: 100 ppm
1330-20-7	TWA: 435 mg/m ³
	STEL: 150 ppm
	STEL: 655 mg/m ³
Ethyl benzene (constituent)	TWA: 100 ppm
100-41-4	TWA: 435 mg/m ³
	STEL: 125 ppm
	STEL: 545 mg/m ³

Chemical name	Ontario TWAEV
Titanium Dioxide	TWA: 10 mg/m ³
13463-67-7	
Naphthalene (constituent)	TWA: 10 ppm
91-20-3	Skin
Xylenes (o-, m-, p- isomers)	TWA: 100 ppm
1330-20-7	STEL: 150 ppm
Ethyl benzene (constituent)	TWA: 20 ppm
100-41-4	

Chemical name	Mexico OEL (TWA)
	TWA/VLE-PPT: 10 mg/m ³
13463-67-7	
Naphthalene (constituent)	TWA/VLE-PPT: 10 ppm
91-20-3	STEL/PPT-CT: 15 ppm
Xylenes (o-, m-, p- isomers)	TWA/VLE-PPT: 100 ppm
1330-20-7	STEL/PPT-CT: 150 ppm
Ethyl benzene (constituent)	TWA/VLE-PPT: 20 ppm
100-41-4	

Appropriate engineering controls

Engineering Measures

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Wear safety glasses with side shields (or goggles). If splashes are likely to occur:. Wear

suitable face shield. Ensure that eyewash stations and safety showers are close to the

workstation location.

Skin Protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as

appropriate, to prevent skin contact.

Hand Protection Chemical resistant protective gloves.

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6,

corresponding >480 minutes of permeation time): eg. nitrile rubber (0.4 mm), chloroprene

rubber (0.5 mm), polyvinylchloride (0.7 mm) and other

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers. Taking into account the varying conditions, the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Due to different glove types, the manufacturer's directions for use should be observed. Replace gloves immediately when torn or any change in appearance is noticed such as dimension, color, flexibility.

Respiratory Protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid **Appearance** Colored

Odor Threshold No information available Odor Characteristic

Remarks • Method **Property** Values

No data available pН **Melting Point / Freezing Point** No information available No data available

Boiling Point / Boiling Range > 149 °C / 300 °F 49 °C / 120 °F Flash Point Setaflash closed cup

No data available **Evaporation rate**

Flammability Limit in Air

Upper flammability limit No data available Lower flammability limit No data available

Vapor Pressure No data available **Vapor Density** No data available

Specific Gravity 1.04

Water Solubility No data available Solubility in other solvents No data available Partition coefficient: n-octanol/water No data available

No information available No data available **Autoignition Temperature** Hyphen

No data available No data available Kinematic viscosity No data available **Dynamic viscosity**

Explosive Properties No data available **Oxidizing Properties** No data available

Other information

Photochemically Reactive Yes Weight Per Gallon (lbs/gal) 8.68

VOC by weight % (less water)	VOC by volume % (less water)	VOC lbs/gal (less water)	VOC grams/liter (less water)	
` 51.14 <i>´</i>	` 54.93	4.44	` 532.49 ´	

10. STABILITY AND REACTIVITY

Reactivity

No information available.

Chemical stability

Stable under normal conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO2). Carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

InhalationSpecific test data for the substance or mixture is not available.Eye ContactSpecific test data for the substance or mixture is not available.Skin ContactSpecific test data for the substance or mixture is not available.IngestionSpecific test data for the substance or mixture is not available.

Chemical name	Oral LD50
Solvent naphtha, petroleum, heavy aromatic	> 5000 mg/kg (Rat)
64742-94-5	
Titanium Dioxide	> 10000 mg/kg (Rat)
13463-67-7	
Solvent naphtha, petroleum, light aromatic	= 8400 mg/kg (Rat)
64742-95-6	
Naphthalene (constituent)	= 1110 mg/kg (Rat)
91-20-3	
Xylenes (o-, m-, p- isomers)	= 3500 mg/kg (Rat)
1330-20-7	
1,2,4-Trimethylbenzene (constituent)	= 3280 mg/kg (Rat)
95-63-6	
Ethyl benzene (constituent)	= 3500 mg/kg (Rat)
100-41-4	

Chemical name	Dermal LD50
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	> 2000 mg/kg (Rabbit)
Solvent naphtha, petroleum, light aromatic 64742-95-6	> 2000 mg/kg (Rabbit)
Naphthalene (constituent) 91-20-3	= 1120 mg/kg (Rabbit)
Xylenes (o-, m-, p- isomers) 1330-20-7	> 4350 mg/kg (Rabbit)
1,2,4-Trimethylbenzene (constituent) 95-63-6	> 3160 mg/kg (Rabbit)
Ethyl benzene (constituent) 100-41-4	= 15400 mg/kg (Rabbit)

Chemical name	Inhalation LC50
Solvent naphtha, petroleum, heavy aromatic	> 590 mg/m ³ (Rat) 4 h
64742-94-5	
Titanium Dioxide	= 5.09 mg/L (Rat) 4 h
13463-67-7	
Solvent naphtha, petroleum, light aromatic	= 3400 ppm (Rat) 4 h

64742-95-6	
Naphthalene (constituent)	> 0.4 mg/L (Rat)4 h
91-20-3	
Xylenes (o-, m-, p- isomers)	= 29.08 mg/L (Rat)4 h
1330-20-7	
1,2,4-Trimethylbenzene (constituent)	$= 18 \text{ g/m}^3 \text{ (Rat) 4 h}$
95-63-6	
Ethyl benzene (constituent)	= 17.4 mg/L (Rat) 4 h
100-41-4	

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Specific test data for the substance or mixture is not available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationSpecific test data for the substance or mixture is not available.Eye damage/irritationSpecific test data for the substance or mixture is not available.IrritationSpecific test data for the substance or mixture is not available.CorrosivitySpecific test data for the substance or mixture is not available.SensitizationSpecific test data for the substance or mixture is not available.Mutagenic EffectsSpecific test data for the substance or mixture is not available.

Carcinogenic effects Specific test data for the substance or mixture is not available. Suspected of causing

cancer. (based on components).

Reproductive Effects
Specific test data for the substance or mixture is not available.
STOT - single exposure
STOT - repeated exposure
Chronic Toxicity
Specific test data for the substance or mixture is not available.
Specific test data for the substance or mixture is not available.
Specific test data for the substance or mixture is not available.

Aspiration hazard Specific test data for the substance or mixture is not available. May be fatal if swallowed and

enters airways. (based on components).

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

	The family was a second and a second a second and a second a second and a second a second and a second and a second and a		
Chemical name		ACGIH	
Titanium Dioxide		A3	
13463-67-7			
Naphthalene (constituent)		A3	
91-20-3			
Ethyl benzene (constituent)		A3	
100-41-4			

Chemical name	IARC
Titanium Dioxide	Group 2B
13463-67-7	
Naphthalene (constituent)	Group 2B
91-20-3	
Ethyl benzene (constituent)	Group 2B
100-41-4	

Chemical name	NTP
Naphthalene (constituent)	Reasonably Anticipated
91-20-3	

Chemical name	OSHA
Titanium Dioxide	X
13463-67-7	
Naphthalene (constituent)	X
91-20-3	
Ethyl benzene (constituent)	X
100-41-4	

Numerical measures of toxicity - Product Information

Page 7/12

Unknown acute toxicity 0 % of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 31,987.80 mg/kg

 ATEmix (dermal)
 41,326.70 mg/kg

 ATEmix (inhalation-gas)
 99,999.00

 ATEmix (inhalation-dust/mist)
 28.50 mg/l

 ATEmix (inhalation-vapor)
 209.00 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Specific test data for the substance or mixture is not available. Toxic to aquatic life with long lasting effects. (based on components).

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	
Ethyl benzene (constituent)	72h EC50 Pseudokirchneriella subcapitata: = 4.6 mg/L	
100-41-4	96h EC50 Pseudokirchneriella subcapitata: > 438 mg/L	
	72h EC50 Pseudokirchneriella subcapitata: 2.6 - 11.3 mg/L static	
	96h EC50 Pseudokirchneriella subcapitata: 1.7 - 7.6 mg/L static	

Chemical name	Fish		
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	96h LC50 Pimephales promelas: = 19 mg/L (static) 96h LC50 Oncorhynchus mykiss: = 2.34 mg/L 96h LC50 Lepomis macrochirus: = 1740 mg/L (static)		
	96h LC50 Pimephales promelas: = 45 mg/L (flow-through) 96h LC50 Pimephales promelas: = 41 mg/L		
Solvent naphtha, petroleum, light aromatic 64742-95-6	96h LC50 Oncorhynchus mykiss: = 9.22 mg/L		
Naphthalene (constituent) 91-20-3	96h LC50 Oncorhynchus mykiss: = 1.6 mg/L (flow-through) 96h LC50 Oncorhynchus mykiss: 0.91 - 2.82 mg/L (static) 96h LC50 Pimephales promelas: = 1.99 mg/L (static) 96h LC50 Lepomis macrochirus: = 31.0265 mg/L (static) 96h LC50 Pimephales promelas: 5.74 - 6.44 mg/L (flow-through)		
Xylenes (o-, m-, p- isomers) 1330-20-7	96h LC50 Pimephales promelas: = 13.4 mg/L (flow-through) 96h LC50 Oncorhynchus mykiss: 2.661 - 4.093 mg/L (static) 96h LC50 Oncorhynchus mykiss: 13.5 - 17.3 mg/L 96h LC50 Poecilia reticulata: 30.26 - 40.75 mg/L (static) 96h LC50 Lepomis macrochirus: 13.1 - 16.5 mg/L (flow-through) 96h LC50 Lepomis macrochirus: = 19 mg/L 96h LC50 Lepomis macrochirus: 7.711 - 9.591 mg/L (static) 96h LC50 Pimephales promelas: 23.53 - 29.97 mg/L (static) 96h LC50 Cyprinus carpio: = 780 mg/L (semi-static) 96h LC50 Cyprinus carpio: > 780 mg/L		
1,2,4-Trimethylbenzene (constituent) 95-63-6	96h LC50 Pimephales promelas: 7.19 - 8.28 mg/L (flow-through)		
Ethyl benzene (constituent) 100-41-4	96h LC50 Oncorhynchus mykiss: 11.0 - 18.0 mg/L (static) 96h LC50 Oncorhynchus mykiss: = 4.2 mg/L (semi-static) 96h LC50 Pimephales promelas: 7.55 - 11 mg/L (flow-through) 96h LC50 Lepomis macrochirus: = 32 mg/L (static) 96h LC50 Pimephales promelas: 9.1 - 15.6 mg/L (static) 96h LC50 Poecilia reticulata: = 9.6 mg/L (static)		

Chemical name	Crustacea
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	48h EC50 Daphnia magna: = 0.95 mg/L
Solvent naphtha, petroleum, light aromatic 64742-95-6	48h EC50 Daphnia magna: = 6.14 mg/L
Naphthalene (constituent) 91-20-3	48h EC50 Daphnia magna: 1.09 - 3.4 mg/L Static 48h EC50 Daphnia magna: = 1.96 mg/L Flow through 48h LC50 Daphnia magna: = 2.16 mg/L

	48h EC50 water flea: = 3.82 mg/L 48h LC50 Gammarus lacustris: = 0.6 mg/L
1,2,4-Trimethylbenzene (constituent) 95-63-6	48h EC50 Daphnia magna: = 6.14 mg/L
Ethyl benzene (constituent) 100-41-4	48h EC50 Daphnia magna: 1.8 - 2.4 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

Chemical name	Partition coefficient
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	2.9 - 6.1
Naphthalene (constituent) 91-20-3	3.6
Xylenes (o-, m-, p- isomers) 1330-20-7	2.77 - 3.15
1,2,4-Trimethylbenzene (constituent) 95-63-6	3.63
Ethyl benzene (constituent) 100-41-4	3.2

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste Disposal Methods Contain and dispose of waste according to local regulations.

Contaminated Packaging Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. TRANSPORT INFORMATION

Note: This information is not intended to convey all specific transportation requirements relating to

this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation information can be found in the specific regulations for your mode of transportation. It is the responsibility of the transporting organization to follow all applicable laws, regulations and

rules relating to the transportation of the material.

DOT In the U.S. and Canada, this material may be reclassified as a combustible liquid and is not

regulated, via surface transportation, in containers less than 119 gallons or 450 liters [per 49 CFR 173.150 (f)] [per Transportation of Dangerous Goods Regulations/Clear Language Part

1.33].

UN/ID no UN1210
Proper Shipping Name Printing Ink

Transport hazard class(es) 3
Packing Group |||

ICAO / IATA / IMDG / IMO

UN1210
Proper Shipping Name
UN1210
Printing Ink

Transport hazard class(es) 3
Packing Group |||

Page 9/12

15. REGULATORY INFORMATION

International Inventories

All substances are listed as ACTIVE on the TSCA Inventory. For further information, please contact:. Supplier (manufacturer/importer/downstream user/distributor).

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Naphthalene (constituent)	91-20-3	1 - 5	0.1
Xylenes (o-, m-, p- isomers)	1330-20-7	1 - 5	1.0
1,2,4-Trimethylbenzene (constituent)	95-63-6	1 - 5	1.0
Ethyl benzene (constituent)	100-41-4	0.1 - < 1	0.1

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:.

Chemical name	CAS No	Weight-%
Naphthalene (constituent)	91-20-3	1 - 5
Xylenes (o-, m-, p- isomers)	1330-20-7	1 - 5
Ethyl benzene (constituent)	100-41-4	0.1 - < 1
Chlorobenzene	108-90-7	0.1 - < 1
Xylenes (o-, m-, p- isomers) (constituent)	1330-20-7	0.1 - < 1

US State Regulations

Chemical name	Massachusetts
Titanium Dioxide	X
13463-67-7	
Naphthalene (constituent)	X
91-20-3	
Xylenes (o-, m-, p- isomers)	X
1330-20-7	
1,2,4-Trimethylbenzene (constituent)	X
95-63-6	
Ethyl benzene (constituent)	X
100-41-4	

Chemical name	Minnesota Right To Know
Titanium Dioxide 13463-67-7	X
Naphthalene (constituent) 91-20-3	X
Xylenes (o-, m-, p- isomers) 1330-20-7	x
1,2,4-Trimethylbenzene (constituent) 95-63-6	x
Ethyl benzene (constituent) 100-41-4	x

Chemical name	New Jersey
Titanium Dioxide	X
13463-67-7	
Naphthalene (constituent)	X
91-20-3	
Xylenes (o-, m-, p- isomers)	X
1330-20-7	

1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Ethyl benzene (constituent) 100-41-4	X

Chemical name	Pennsylvania
Titanium Dioxide	X
13463-67-7	
Naphthalene (constituent)	X
91-20-3	
Xylenes (o-, m-, p- isomers)	X
1330-20-7	
1,2,4-Trimethylbenzene (constituent)	X
95-63-6	
Ethyl benzene (constituent)	X
100-41-4	

California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

Chemical name	California Proposition 65
Titanium Dioxide	Carcinogen
Naphthalene (constituent)	Carcinogen
Ethyl benzene (constituent)	Carcinogen

Canada

Chemical name	NPRI - National Pollutant Release Inventory
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	Part 5 Substance - Volatile Organic Compounds with Additional Reporting Requirements Part 4 Substance - Criteria Air Contaminants
Solvent naphtha, petroleum, light aromatic 64742-95-6	Part 5 Substance - Volatile Organic Compounds with Additional Reporting Requirements
Naphthalene (constituent) 91-20-3	Part 1, Group A Substance Part 4 Substance - Criteria Air Contaminants
Xylenes (o-, m-, p- isomers) 1330-20-7	Part 1, Group A Substance Part 5 Substance - Volatile Organic Compounds with Additional Reporting Requirements Part 4 Substance - Criteria Air Contaminants
1,2,4-Trimethylbenzene (constituent) 95-63-6	Part 1, Group A Substance Part 5 Substance - Volatile Organic Compounds with Additional Reporting Requirements Part 4 Substance - Criteria Air Contaminants
Ethyl benzene (constituent) 100-41-4	Part 1, Group A Substance Part 4 Substance - Criteria Air Contaminants

16. OTHER INFORMATION

Health hazards Flammability Reactivity Personal Protection 2 * 0 X

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average)
STEL (Short Term Exposure Limit)

Ceiling Maximum limit value

ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen A2 - Suspected Human Carcinogen A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP: (National Toxicity Program) Known - Known Carcinogen Reasonably Anticipated to be a Human Carcinogen OSHA: (Occupational Safety & Health Administration) X - Present

Revision Date

Aug-09-2023

Pursuant to NOM-018-STPS-2015

This information within is considered correct but is not exhaustive and will be used for guidance only, which is based on the current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Page 12/12