

# **SAFETY DATA SHEET**

Published Date May-15-2019 Revision Date May-15-2019 Revision Number 2.5

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier Product code Product name Product category

15104 Halftone Black Dense 1500 Series UV Screen Ink

<u>Other means of identification</u> Synonyms

Recommended use of the chemical and restrictions on useRecommended usePrinting operations

None

### Details of the supplier of the safety data sheet

UNITED STATES Nazdar Company 8501 Hedge Lane Terrace Shawnee, KS 66227 Tel: +001-913-422-1888 Tel: +001-800-677-4657 Fax: +001-913-422-2294 www.nazdar.com UNITED KINGDOM Nazdar Limited Barton Road Heaton Mersey Stockport, England SK4 3EG Tel: +44 161 442 2111

### Emergency telephone number

USA: Chemtrec: +001-800-424-9300 Outside USA: Chemtrec: +001-703-527-3887 24 Hour Emergency Phone Number

### 2. HAZARDS IDENTIFICATION

### **Classification**

Skin Corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitization	Category 1A - (H317)
Reproductive toxicity	Category 1B - (H360FD)
Specific target organ toxicity (repeated exposure)	Category 1 - (H372)
Chronic aquatic toxicity	Category 2 - (H411)

#### Label elements



Danger

**Hazard Statements** 

H315 - Causes skin irritation H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation

H360FD - May damage fertility. May damage the unborn child

H372 - Causes damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects

#### **Precautionary Statements**

P264 - Wash face, hands and any exposed skin thoroughly after handling

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P337 + P313 - If eye irritation persists: Get medical advice/attention

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention

P202 - Do not handle until all safety precautions have been read and understood

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P270 - Do not eat, drink or smoke when using this product

P314 - Get medical advice/attention if you feel unwell

P273 - Avoid release to the environment

### Hazards not otherwise classified (HNOC)

Toxic to aquatic life.

### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

### <u>Mixture</u>

Component	CAS-No	Weight %	Trade Secret	Note
Glycol Ether Acrylate	Trade Secret	10 - 30	*	
Vinyl Functional Monomer	Trade Secret	10 - 30	*	
Acrylated Monomer	Trade Secret	10 - 30	*	
Photoinitiator	Trade Secret	1 - 5	*	
Carbon black	1333-86-4	1 - 5	*	
Photoinitiator	Trade Secret	1 - 5	*	
Additive	Trade Secret	< 0.5	*	

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

#### Description of first aid measures

General Advice Eye Contact	Show this safety data sheet to the doctor in attendance. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.
Skin Contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.
Inhalation	Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Most important symptoms and effects, both acute and delayed

None under normal use conditions.

#### Indication of any immediate medical attention and special treatment needed

#### Notes to Physician

Treat symptomatically.

### **5. FIRE-FIGHTING MEASURES**

### Suitable Extinguishing Media

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

### **Unsuitable Extinguishing Media**

No information available.

### Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions. Hazardous polymerization may take place during a fire due to heat. Closed containers could violently rupture.

### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

### 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal Precautions** Remove all sources of ignition. Ventilate the area. Avoid contact with eves, skin and clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

#### Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

### Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

### 7. HANDLING AND STORAGE

### Precautions for safe handling

Handling Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Ensure adequate ventilation.

#### Conditions for safe storage, including any incompatibilities

Keep at temperatures between 18°-32°C (65°-90°F). Keep containers tightly closed in a dry, Storage cool and well-ventilated place. Keep container closed when not in use. Keep out of the reach of children. Protect from direct sunlight. Keep away from open flames, hot surfaces and sources of ignition. Incompatible Products

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### **Exposure limits**

Component	ACGIH TLV
Carbon black 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable particulate matter
Component	OSHA PEL
Carbon black	TWA: 3.5 mg/m <sup>3</sup>
1333-86-4	

Component	OSHA PEL (vacated)	
Carbon black 1333-86-4	TWA: 3.5 mg/m³	
1333 00 4		
Component	Ontario TWAEV	
Carbon black	TWA: 3 mg/m <sup>3</sup> inhalable	
1333-86-4		
Component		
Carbon black 1333-86-4	TWA/VLE-PPT: 3.5 mg/m <sup>3</sup> STEL/PPT-CT: 7 mg/m <sup>3</sup>	
1555 66 4	OTEDT TOT. T IIght	
Appropriate engineering contro	ls	
	—	
Engineering Measures	Provide a good standard of general ventilation. Natural ventilation is from doors, windows	
	etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are	
	advised to consider national Occupational Exposure Limits or other equivalent values. In	
	case of insufficient ventilation, wear suitable respiratory equipment.	
Individual protection measures	such as personal protective equipment	
individual protection measures,	such as personal protective equipment	
Eye/Face Protection	Wear safety glasses with side shields (or goggles). If splashes are likely to occur:. Wear	
,	suitable face shield. Ensure that eyewash stations and safety showers are close to the	
	workstation location.	
Skin Protection	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls,	
	as appropriate, to prevent skin contact.	
Hand Protection	Chamical registent protective alouge	
Hand Flotection	Chemical resistant protective gloves. Suitable materials also with prolonged, direct contact (Recommended: Protective index 6,	
	corresponding >480 minutes of permeation time): eg. nitrile rubber (0.4 mm), chloroprene	
	rubber (0.5 mm), polyvinylchloride (0.7 mm) and other	
	Supplementary note: The specifications are based on tests, literature data and information	
	of glove manufacturers. Taking into account the varying conditions, the practical usage of a	
	chemical-protective glove in practice may be much shorter than the permeation time	
	determined through testing.	
	Due to different glove types, the manufacturer's directions for use should be observed.	
	Replace gloves immediately when torn or any change in appearance is noticed such as	
	dimension, color, flexibility.	
Respiratory Protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved	
	respiratory protection should be worn. Respiratory protection must be provided in	
	accordance with current local regulations. Selection of air-purifying or positive-pressure	
	supplied-air will depend on the specific operation and the potential airborne concentration of	
	the material.	
Conoral Hygiana Considered	tions Handle in accordance with good industrial bygions and safety practice. Wash hands before	
General hygiene Considerat	tions Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with	
	eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of	
	equipment, work area and clothing is recommended.	
	equipment, noncarea and eleming to recommended.	

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical an	d chemical properties		
Physical State	Liquid	Appearance	Colored Liquid
Odor	Sweet Mild Acrylic	Odor Threshold	No information available
<u>Property</u>	Values	Remarks • Method	
рН		No data available	
Melting Point / Freezing Point		No data available	
Boiling Point / Boiling Range	> 149 °C / 300 °F		
Flash Point	> 94 °C / > 201 °F	Pensky Martens Close	ed Cup (PMCC)

Evaporation rate Flammability Limit in Air		No data available	
Upper flammability limit		No data available	
Lower flammability limit		No data available	
Vapor Pressure		No data available	
Vapor Density	1.00	No data available	
Specific Gravity	1.09	No data available	
Water Solubility Solubility in other solvents		No data available	
Partition coefficient: n-octanol	/water	No data available	
Autoignition Temperature		No data available	
Decomposition temperature		No data available	
Kinematic viscosity		No data available	
Dynamic viscosity		No data available	
Explosive Properties	No data available		
Oxidizing Properties	No data available		
Other Information			
Photochemically Reactive	No		
Weight Per Gallon (lbs/gal)	9.1		
	1	1	
VOC by weight %	VOC by volume %	VOC lbs/gal	VOC grams/liter
(less water)	(less water) No information available	(less water)	(less water)
0-1	No information available	0-1	1.93

### **10. STABILITY AND REACTIVITY**

### **Reactivity**

No information available.

#### Chemical stability

Stable under normal conditions.

### Possibility of Hazardous Reactions

None under normal processing. Do not store for longer periods at temperatures above 93°C (200°F).

### Conditions to avoid

Temperatures above 93 °C / 200 °F. Protect from direct sunlight. Keep away from open flames, hot surfaces and sources of ignition.

### Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

### Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO2). Carbon monoxide.

### **11. TOXICOLOGICAL INFORMATION**

### Information on likely routes of exposure

Inhalation	Specific test data for the substance or mixture is not available.
Eye Contact	Specific test data for the substance or mixture is not available.
Skin Contact	Specific test data for the substance or mixture is not available.
Ingestion	Specific test data for the substance or mixture is not available.

Component	Oral LD50
Glycol Ether Acrylate	= 4660 μL/kg (Rat)
Acrylated Monomer	= 4890 mg/kg (Rat)
Carbon black	> 15400 mg/kg (Rat)

1333-86-4

### Information on toxicological effects

Symptoms	Specific test data for the substance or mixture is not available.		
Delayed and immediate effects as	well as chronic effects from sho	rt and long-term exposure	
Skin corrosion/irritation	Specific test data for the substar redness and swelling). (based or	nce or mixture is not available. Causes sk n components).	in irritation (pain,
Eye damage/irritation		nce or mixture is not available. Causes se	rious eye irritation.
Irritation	Specific test data for the substar	nce or mixture is not available.	
Corrosivity	Specific test data for the substar		
Sensitization	Specific test data for the substar reaction. (based on components	Specific test data for the substance or mixture is not available. May cause an allergic skin reaction. (based on components).	
Mutagenic Effects	Specific test data for the substar	nce or mixture is not available.	
Carcinogenic effects		Specific test data for the substance or mixture is not available.	
Reproductive Effects	Specific test data for the substance or mixture is not available. May damage fertility. May damage the unborn child. (based on components).		
STOT - single exposure	Specific test data for the substar		
STOT - repeated exposure	Specific test data for the substance or mixture is not available. Causes damage to organs through prolonged or repeated exposure. (based on components).		
Chronic Toxicity	Specific test data for the substar	Specific test data for the substance or mixture is not available	
Target Organ Effects	Liver, Respiratory system.		
Aspiration hazard	Specific test data for the substance or mixture is not available.		
Carcinogenicity	The table below indicates wheth	The table below indicates whether each agency has listed any ingredient as a carcinogen.	
Component		ACGIH	
Carbon black 1333-86-4		A3	
Component			

Component	IARC
	Group 2B
1333-86-4	

Component	OSHA
Carbon black	X
1333-86-4	

### Numerical measures of toxicity - Product Information

**Unknown Acute Toxicity** 0 % of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated	based on chapter 3.1 of the GHS document	
ATEmix (oral)	2,381.00 mg/kg	
ATEmix (dermal)	5,501.00 mg/kg mg/l	

### **12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

Specific test data for the substance or mixture is not available. Toxic to aquatic life with long lasting effects. (based on components).

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

#### Persistence and Degradability No information available.

### **Bioaccumulation**

No information available

### Other adverse effects

No information available

	13. DISPOSAL CONSIDERATIONS
Waste treatment methods	
Waste Disposal Methods	Contain and dispose of waste according to local regulations.
Contaminated Packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.
	14. TRANSPORT INFORMATION
Note:	This information is not intended to convey all specific transportation requirements relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation information can be found in the specific regulations for your mode of transportation. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.
<u>DOT</u>	Not regulated Exception: In the US and Canada except when all or part of the transportation is by vessel, containers 119 gallons/ 450 Liters and less are not regulated [see 49CFR 171.4 (c)(1)] If in quantities of 5L or less (per inner packaging) for liquids or 5KG or less (per inner packaging) for solids these items may be shipped as not regulated [additional general packaging requirements must be met see 49CFR 173.24] [see 49CFR 171.4 (c)(2)]
ICAO / IATA / IMDG / IMO	Not Regulated Exception: If in quantities of 5L or less (per inner packaging) for liquids or 5KG or less (per inner packaging) for solids these items may be shipped as not regulated [additional general packaging requirements must be met see ICAO/IATA special provision A197] Exception: If in quantities of 5L or less (per inner packaging) for liquids or 5KG or less (per inner packaging) for solids these items may be shipped as not regulated [additional general packaging requirements must be met see IMDG code 2.10.2.7]

### 15. REGULATORY INFORMATION

### International Inventories

All components are listed on the TSCA Inventory. For further information, please contact:. Supplier (manufacturer/importer/downstream user/distributor).

### U.S. Federal Regulations

### <u>SARA 313</u>

 Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

 Component
 CAS-No
 Weight %
 SARA 313 - Threshold Values

			Values
Glycol Ether Acrylate	Trade Secret	10 - 30	1.0

The above glycol ether acrylate is considered a reactive chemical in ultraviolet curable inks. Once initiated by a high dose of ultraviolet light, this glycol ether acrylate rapidly polymerizes (i.e. hardens) and becomes part of the ink film. The polymerization process of UV curable inks is measured in milliseconds.

<u>Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)</u> This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:

Component	CAS-No	Weight %
Glycol Ether Acrylate	Trade Secret	10 - 30

### U.S. State Regulations

	Massachusetts Right To Know
Carbon black 1333-86-4	X

	Minnesota Right To Know
Carbon black	X
1333-86-4	

Component	New Jersey Right To Know
Glycol Ether Acrylate	X
Carbon black 1333-86-4	X

	Pennsylvania
	Right To Know
Glycol Ether Acrylate	X
Carbon black	X
1333-86-4	

#### California Prop. 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

Component	California Prop. 65	
Carbon black	Carcinogen	

- This product contains carbon black in a non-respirable form. Inhalation of carbon black is unlikely to occur from exposure to this product

### Canada

No information available

16. OTHER INFORMATION					
HMIS:	Health 2	Flammability 1	Reactivity 1	Personal Protection X	
Key or legend to abl	previations and acrony	rms used in the safety d	ata sheet		
Legend - Section 8: E	XPOSURE CONTROLS/P	ERSONAL PROTECTION			
TŴĂ	TWA (time-weighted average)				
STEL	STEL (Short Term Exposure Limit)				
Ceiling	Maximum limit value				
ACGIH: (American Confe A1 - Known Human Carcin A2 - Suspected Human Ca	5	ustrial Hygienists)			

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans **NTP: (National Toxicity Program)** Known - Known Carcinogen Reasonably Anticipated to be a Human Carcinogen **OSHA: (Occupational Safety & Health Administration)** X - Present

Revision Date May-15-2019

### Pursuant to NOM-018-STPS-2015

This information within is considered correct but is not exhaustive and will be used for guidance only, which is based on the current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.

### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet