

Print Date
May-30-2015

Revision Date
May-30-2015

Revision Number
1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product code **55LF44**
Product name **Scarlet Red**
Product category **5500 Series Flat Poster Screen Ink**

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended use Printing operations

Details of the supplier of the safety data sheet

| | |
|--|----------------------------|
| UNITED STATES | UNITED KINGDOM |
| Nazdar Company | Nazdar Limited |
| 8501 Hedge Lane Terrace | Barton Road |
| Shawnee, KS 66227 | Heaton Mersey |
| Tel: 1-913-422-1888 | Stockport, England SK4 3EG |
| Tel: 1-800-677-4657 | Tel: +44 161 442 2111 |
| Fax: 1-913-422-2294 | |
| www.nazdar.com | |

Emergency telephone number

USA: Chemtrec: 1-800-424-9300
Outside USA: Chemtrec: 1-703-527-3887
24 Hour Emergency Phone Number

2. HAZARDS IDENTIFICATION

Classification

| | |
|-----------------------------------|---------------------|
| Serious eye damage/eye irritation | Category 2 - (H319) |
| Aspiration toxicity | Category 1 - (H304) |
| Flammable liquids | Category 3 - (H226) |

Label elements



Signal Word
Danger

Hazard Statements

H304 - May be fatal if swallowed and enters airways
H319 - Causes serious eye irritation
H226 - Flammable liquid and vapor

P331 - Do NOT induce vomiting

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Hazards not otherwise classified (HNOC)

May be harmful in contact with skin.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

| Component | CAS-No | Weight % | Trade Secret | Note |
|--------------------------------------|--------------|----------|--------------|------|
| Stoddard solvent | 8052-41-3 | 10 - 30 | * | |
| Petroleum naphtha, light aromatic | 64742-95-6 | 10 - 30 | * | |
| 1,2,4-Trimethylbenzene (constituent) | 95-63-6 | 5 - 10 | * | 1 |
| Crystalline silica (cristobalite) | 14464-46-1 | 5 - 10 | * | |
| Ethylene glycol monopropyl ether | 2807-30-9 | 5 - 10 | * | |
| Talc | 14807-96-6 | 5 - 10 | * | |
| Inert Pigment | Trade Secret | 5 - 10 | * | |
| 1,3,5-Trimethylbenzene (constituent) | 108-67-8 | 1 - 5 | * | 1 |
| Cumene (constituent) | 98-82-8 | 1 - 5 | * | 1 |
| Titanium dioxide | 13463-67-7 | < 1 | * | |
| Quartz, crystalline silica | 14808-60-7 | < 0.5 | * | |

*The exact percentage (concentration) of composition has been withheld as a trade secret.

Note 1. Type of chemical: Constituent

4. FIRST AID MEASURES

Description of first aid measures

General Advice

Show this safety data sheet to the doctor in attendance.

Eye Contact

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.

Skin Contact

Wash off immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.

Inhalation

Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.

Ingestion

DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Most important symptoms and effects, both acute and delayed

None under normal use conditions.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Foam. Carbon dioxide (CO₂). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

No information available.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures**Personal Precautions**

Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

Precautions for safe handling**Handling**

Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Ensure adequate ventilation.

Conditions for safe storage, including any incompatibilities**Storage**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep container closed when not in use. Keep out of the reach of children.

Incompatible Products

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters**Exposure limits**

| Component | ACGIH TLV |
|---|--|
| Stoddard solvent 8052-41-3 | TWA: 100 ppm |
| Crystalline silica (cristobalite) 14464-46-1 | TWA: 0.025 mg/m ³ (respirable fraction) |
| Talc 14807-96-6 | TWA: 2 mg/m ³ (particulate matter) |
| Cumene (constituent) 98-82-8 | TWA: 50 ppm |
| Titanium dioxide 13463-67-7 | TWA: 10 mg/m ³ |
| Quartz, crystalline silica 14808-60-7 | TWA: 0.025 mg/m ³ (respirable fraction) |

| Component | OSHA PEL |
|---|---|
| Stoddard solvent 8052-41-3 | TWA: 100 ppm TWA: 525 mg/m ³ TWA: 500 ppm TWA: 2900 mg/m ³ |
| Crystalline silica (cristobalite) 14464-46-1 | TWA: 0.05 mg/m ³ (respirable dust) |

| | |
|--|--|
| Talc 14807-96-6 | TWA: 2 mg/m ³ (respirable dust) |
| Cumene (constituent) 98-82-8 | TWA: 50 ppm TWA: 245 mg/m ³ Skin |
| Titanium dioxide 13463-67-7 | TWA: 10 mg/m ³ (total dust) TWA: 15 mg/m ³ (total dust) |
| Quartz, crystalline silica 14808-60-7 | TWA: 0.1 mg/m ³ (respirable dust) |

| Component | Ontario TWAEV |
|---|---|
| Stoddard solvent 8052-41-3 | TWA: 525 mg/m ³ |
| Crystalline silica (cristobalite) 14464-46-1 | TWA: 0.05 mg/m ³ (respirable) |
| Ethylene glycol monopropyl ether 2807-30-9 | TWA: 25 ppm TWA: 110 mg/m ³ Skin |
| Talc 14807-96-6 | TWA: 2 mg/m ³ (respirable) |
| Cumene (constituent) 98-82-8 | TWA: 50 ppm |
| Titanium dioxide 13463-67-7 | TWA: 10 mg/m ³ (total dust) |
| Quartz, crystalline silica 14808-60-7 | TWA: 0.10 mg/m ³ (respirable) |

| Component | Mexico OEL (TWA) |
|---|---|
| Stoddard solvent 8052-41-3 | TWA/LMPE-PPT: 100 ppm TWA/LMPE-PPT: 523 mg/m ³ STEL/LMPE-CT: 200 ppm STEL/LMPE-CT: 1050 mg/m ³ |
| Crystalline silica (cristobalite) 14464-46-1 | TWA/LMPE-PPT: 0.05 mg/m ³ (respirable fraction) |
| Talc 14807-96-6 | TWA/LMPE-PPT: 2 mg/m ³ (respirable fraction) |
| Cumene (constituent) 98-82-8 | TWA/LMPE-PPT: 50 ppm TWA/LMPE-PPT: 245 mg/m ³ STEL/LMPE-CT: 75 ppm STEL/LMPE-CT: 365 mg/m ³ |
| Titanium dioxide 13463-67-7 | TWA/LMPE-PPT: 10 mg/m ³ (as Ti) STEL/LMPE-CT: 20 mg/m ³ (as Ti) |
| Quartz, crystalline silica 14808-60-7 | TWA/LMPE-PPT: 0.1 mg/m ³ (respirable fraction) |

Appropriate engineering controls

Engineering Measures

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.

Individual protection measures, such as personal protective equipment

Eye/face Protection

Wear safety glasses with side shields (or goggles). If splashes are likely to occur. Wear suitable face shield. Ensure that eyewash stations and safety showers are close to the workstation location.

Skin Protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory Protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | | | |
|-----------------------|----------------|-----------------------|--------------------------|
| Physical State | Liquid | Appearance | Colored Liquid |
| Odor | Characteristic | Odor Threshold | No information available |

| <u>Property</u> | <u>Values</u> | <u>Remarks • Method</u> |
|--|-------------------|----------------------------------|
| pH | | No data available |
| Melting point/freezing point | | No data available |
| Boiling point/Boiling Range | > 149 °C / 300 °F | |
| Flash Point | 29 °C / 85 °F | Pensky Martens Closed Cup (PMCC) |
| Evaporation rate | | No data available |
| Flammability Limit in Air | | |
| Upper flammability limit | | No data available |
| Lower flammability limit | | No data available |
| Vapor Pressure | | No data available |
| Vapor Density | | No data available |
| Specific Gravity | 1.04 | |
| Water Solubility | | No data available |
| Solubility in other solvents | | No data available |
| Partition coefficient: n-octanol/water | | No data available |
| Autoignition Temperature | | No data available |
| Decomposition temperature | | No data available |
| Kinematic viscosity | | No data available |
| Dynamic viscosity | | No data available |

| | |
|-----------------------------|-------------------|
| Explosive Properties | No data available |
| Oxidizing Properties | No data available |

Other Information

| | |
|------------------------------------|------|
| Photochemically Reactive | Yes |
| Weight Per Gallon (lbs/gal) | 8.67 |

| VOC by weight % (less water) | VOC by volume % (less water) | VOC lbs/gal (less water) | VOC grams/liter (less water) |
|---------------------------------|---------------------------------|-----------------------------|---------------------------------|
| 57.66 | 70.52 | 5 | 599.58 |

10. STABILITY AND REACTIVITY

Reactivity

No information available.

Chemical stability

Stable under normal conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO₂). Carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

| | |
|---------------------|------------------------------------|
| Inhalation | There is no data for this product. |
| Eye Contact | There is no data for this product. |
| Skin Contact | There is no data for this product. |
| Ingestion | There is no data for this product. |

| Component | Oral LD50 |
|--|----------------------|
| Petroleum naphtha, light aromatic 64742-95-6 | 8400 mg/kg (Rat) |
| 1,2,4-Trimethylbenzene (constituent) 95-63-6 | 3400 mg/kg (Rat) |
| Ethylene glycol monopropyl ether 2807-30-9 | 3089 mg/kg (Rat) |
| 1,3,5-Trimethylbenzene (constituent) 108-67-8 | 5000 mg/kg (Rat) |
| Cumene (constituent) 98-82-8 | 1400 mg/kg (Rat) |
| Titanium dioxide 13463-67-7 | >10000 mg/kg (Rat) |
| Quartz, crystalline silica 14808-60-7 | 500 mg/kg (Rat) |

| Component | LD50 Dermal |
|---|------------------------|
| Petroleum naphtha, light aromatic 64742-95-6 | >2000 mg/kg (Rabbit) |
| 1,2,4-Trimethylbenzene (constituent) 95-63-6 | >3160 mg/kg (Rabbit) |
| Ethylene glycol monopropyl ether 2807-30-9 | 960 µL/kg (Rabbit) |
| Cumene (constituent) 98-82-8 | >3160 mg/kg (Rabbit) |

| Component | Inhalation LC50 |
|--|---|
| Petroleum naphtha, light aromatic 64742-95-6 | 3400 ppm (Rat) 4 h >5.2 mg/L (Rat) 4 h |
| 1,2,4-Trimethylbenzene (constituent) 95-63-6 | 18 g/m ³ (Rat) 4 h |
| 1,3,5-Trimethylbenzene (constituent) 108-67-8 | 24 g/m ³ (Rat) 4 h |
| Cumene (constituent) 98-82-8 | 39000 mg/m ³ (Rat) 4 h |

Information on toxicological effects

Symptoms There is no data for this product.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

| | |
|----------------------------------|--|
| Skin corrosion/irritation | There is no data for this product. |
| Eye damage/irritation | There is no data for this product. |
| Irritation | There is no data for this product. |
| Corrosivity | There is no data for this product. |
| Sensitisation | There is no data for this product. |
| Mutagenic Effects | There is no data for this product. |
| Reproductive Effects | There is no data for this product. |
| STOT - single exposure | There is no data for this product. |
| STOT - repeated exposure | There is no data for this product. |
| Chronic Toxicity | There is no data for this product. |
| Aspiration hazard | There is no data for this product. |
| Carcinogenicity | The table below indicates whether each agency has listed any ingredient as a carcinogen. |

| Component | IARC |
|---|----------|
| Crystalline silica (cristobalite) 14464-46-1 | Group 1 |
| Cumene (constituent) 98-82-8 | Group 2B |
| Titanium dioxide 13463-67-7 | Group 2B |
| Quartz, crystalline silica 14808-60-7 | Group 1 |

| Component | NTP |
|--|-------|
| Quartz, crystalline silica 14808-60-7 | Known |

| Component | OSHA |
|---|------|
| Crystalline silica (cristobalite) 14464-46-1 | X |
| Cumene (constituent) 98-82-8 | X |
| Titanium dioxide 13463-67-7 | X |
| Quartz, crystalline silica 14808-60-7 | X |

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

| | |
|--------------------------------------|-----------------|
| ATEmix (oral) | 14,228.00 mg/kg |
| ATEmix (dermal) | 5,493.00 mg/kg |
| ATEmix (inhalation-dust/mist) | 26.20 mg/l |

12. ECOLOGICAL INFORMATION

Ecotoxicity

None known

0% of the mixture consists of components(s) of unknown hazards to the aquatic environment

| Component | Algae/aquatic plants |
|---------------------------------|--|
| Cumene (constituent) 98-82-8 | 72h EC50 Pseudokirchneriella subcapitata: 2.6 mg/L |

| Component | Fish |
|--|--|
| Petroleum naphtha, light aromatic 64742-95-6 | 96h LC50 Oncorhynchus mykiss: 9.22 mg/L |
| 1,2,4-Trimethylbenzene (constituent) 95-63-6 | 96h LC50 Pimephales promelas: 7.19 - 8.28 mg/L [flow-through] |
| Talc 14807-96-6 | 96h LC50 Brachydanio rerio: >100 g/L [semi-static] |
| 1,3,5-Trimethylbenzene (constituent) 108-67-8 | 96h LC50 Pimephales promelas: 3.48 mg/L |
| Cumene (constituent) 98-82-8 | 96h LC50 Pimephales promelas: 6.04 - 6.61 mg/L [flow-through] 96h LC50 Oncorhynchus mykiss: 2.7 mg/L [semi-static] 96h LC50 Oncorhynchus mykiss: 4.8 mg/L [flow-through] 96h LC50 Poecilia reticulata: 5.1 mg/L [semi-static] |

| Component | Crustacea |
|--|--|
| 1,2,4-Trimethylbenzene (constituent) 95-63-6 | 48h EC50 Daphnia magna: 6.14 mg/L |
| 1,3,5-Trimethylbenzene (constituent) 108-67-8 | 24h EC50 Daphnia magna: 50 mg/L |
| Cumene (constituent) 98-82-8 | 48h EC50 Daphnia magna: 7.9 - 14.1 mg/L [static] 48h EC50 Daphnia magna: 0.6 mg/L |

Persistence and Degradability

No information available.

Bioaccumulation

No information available.

| Component | Partition coefficient |
|---|-----------------------|
| 1,2,4-Trimethylbenzene (constituent) 95-63-6 | 3.63 |
| Cumene (constituent) 98-82-8 | 3.55 |

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods**Waste Disposal Methods**

Contain and dispose of waste according to local regulations.

Contaminated Packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION

DOT

| | |
|-----------------------------|--------------|
| UN/ID no. | UN1210 |
| Proper Shipping Name | Printing Ink |
| Hazard Class | 3 |
| Packing Group | III |

ICAO / IATA / IMDG / IMO

| | |
|-----------------------------|--------------|
| UN/ID no. | UN1210 |
| Proper Shipping Name | Printing Ink |
| Hazard Class | 3 |
| Packing Group | III |

15. REGULATORY INFORMATION

International Inventories

All components are listed on the TSCA Inventory. For further information, please contact: Supplier (manufacturer/importer/downstream user/distributor).

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

| Component | CAS-No | Weight % | SARA 313 - Threshold Values |
|--------------------------------------|-----------|----------|-----------------------------|
| 1,2,4-Trimethylbenzene (constituent) | 95-63-6 | 5 - 10 | 1.0 |
| Ethylene glycol monopropyl ether | 2807-30-9 | 5 - 10 | 1.0 |
| Cumene (constituent) | 98-82-8 | 1 - 5 | 1.0 |

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:.

| Component | CAS-No | Weight % |
|----------------------------------|-----------|----------|
| Ethylene glycol monopropyl ether | 2807-30-9 | 5 - 10 |
| Cumene (constituent) | 98-82-8 | 1 - 5 |

U.S. State Regulations

| Component | Massachusetts Right To Know |
|--|--|
| Stoddard solvent 8052-41-3 | X |
| 1,2,4-Trimethylbenzene (constituent) 95-63-6 | X |
| Crystalline silica (cristobalite) 14464-46-1 | X |
| Talc 14807-96-6 | X |
| 1,3,5-Trimethylbenzene (constituent) 108-67-8 | X |
| Cumene (constituent) 98-82-8 | X |
| Titanium dioxide 13463-67-7 | X |
| Quartz, crystalline silica 14808-60-7 | X |

| Component | Minnesota Right To Know |
|---|------------------------------------|
| Stoddard solvent 8052-41-3 | X |
| 1,2,4-Trimethylbenzene (constituent) 95-63-6 | X |
| Crystalline silica (cristobalite) 14464-46-1 | X |
| Talc 14807-96-6 | X |
| Cumene (constituent) 98-82-8 | X |
| Titanium dioxide 13463-67-7 | X |
| Quartz, crystalline silica 14808-60-7 | X |

| Component | New Jersey Right To Know |
|---|-------------------------------------|
| Stoddard solvent 8052-41-3 | X |
| 1,2,4-Trimethylbenzene (constituent) 95-63-6 | X |
| Crystalline silica (cristobalite) 14464-46-1 | X |
| Ethylene glycol monopropyl ether 2807-30-9 | X |
| Talc 14807-96-6 | X |
| Cumene (constituent) 98-82-8 | X |
| Titanium dioxide 13463-67-7 | X |
| Quartz, crystalline silica 14808-60-7 | X |

| Component | Pennsylvania Right To Know |
|---|---------------------------------------|
| Stoddard solvent 8052-41-3 | X |
| 1,2,4-Trimethylbenzene (constituent) 95-63-6 | X |
| Crystalline silica (cristobalite) 14464-46-1 | X |
| Ethylene glycol monopropyl ether | X |

| | |
|--|---|
| 2807-30-9 | |
| Talc 14807-96-6 | X |
| Inert Pigment | X |
| Cumene (constituent) 98-82-8 | X |
| Titanium dioxide 13463-67-7 | X |
| Quartz, crystalline silica 14808-60-7 | X |

California Prop. 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

| Component | California Prop. 65 |
|----------------------------|---------------------|
| Cumene (constituent) | Carcinogen |
| Titanium dioxide | Carcinogen |
| Quartz, crystalline silica | Carcinogen |

*This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product
This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product*

Canada

| Component | NPRI - National Pollutant Release Inventory |
|--|--|
| Stoddard solvent 8052-41-3 | Part 5, Other Groups and Mixtures |
| Petroleum naphtha, light aromatic 64742-95-6 | Part 5, Other Groups and Mixtures |
| 1,2,4-Trimethylbenzene (constituent) 95-63-6 | Part 1, Group A Substance Part 5, Individual Substances Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999 |
| Ethylene glycol monopropyl ether 2807-30-9 | Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999 |
| 1,3,5-Trimethylbenzene (constituent) 108-67-8 | Part 5, Isomer Groups total of 1,2,3-Trimethylbenzene, CAS No. 526-73-8, and 1,3,5-Trimethylbenzene, CAS No. 108-67-8, except 1,2,4-Trimethylbenzene, CAS No. 95-63-6 Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999 |
| Cumene (constituent) 98-82-8 | Part 1, Group A Substance Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999 |

16. OTHER INFORMATION

| | | | | |
|--------------|---------------|---------------------|-------------------|----------------------------|
| HMIS: | Health | Flammability | Reactivity | Personal Protection |
| | 2 * | 3 | 0 | X |

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average)
 STEL STEL (Short Term Exposure Limit)
 Ceiling Maximum limit value

ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen
 A2 - Suspected Human Carcinogen
 A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans
Group 2A - Probably Carcinogenic to Humans
Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Revision Date

May-30-2015

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of MSDS