

Print Date
May-30-2015

Revision Date
May-30-2015

Revision Number
1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product code **5521**
Product name **Rich Brown**
Product category **5500 Series Flat Poster Screen Ink**

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended use Printing operations

Details of the supplier of the safety data sheet

UNITED STATES	UNITED KINGDOM
Nazdar Company	Nazdar Limited
8501 Hedge Lane Terrace	Barton Road
Shawnee, KS 66227	Heaton Mersey
Tel: 1-913-422-1888	Stockport, England SK4 3EG
Tel: 1-800-677-4657	Tel: +44 161 442 2111
Fax: 1-913-422-2294	
www.nazdar.com	

Emergency telephone number

USA: Chemtrec: 1-800-424-9300
Outside USA: Chemtrec: 1-703-527-3887
24 Hour Emergency Phone Number

2. HAZARDS IDENTIFICATION

Classification

Serious eye damage/eye irritation	Category 2 - (H319)
Aspiration toxicity	Category 1 - (H304)
Flammable liquids	Category 3 - (H226)

Label elements



Signal Word
Danger

Hazard Statements

H304 - May be fatal if swallowed and enters airways
H319 - Causes serious eye irritation
H226 - Flammable liquid and vapor

P331 - Do NOT induce vomiting

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Hazards not otherwise classified (HNOC)

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Component	CAS-No	Weight %	Trade Secret	Note
Stoddard solvent	8052-41-3	10 - 30	*	
Petroleum naphtha, light aromatic	64742-95-6	10 - 30	*	
Calcium Carbonate	1317-65-3	10 - 30	*	
Crystalline silica (cristobalite)	14464-46-1	5 - 10	*	
1,2,4-Trimethylbenzene (constituent)	95-63-6	5 - 10	*	1
Iron oxide	1309-37-1	5 - 10	*	
Inert Pigment	Trade Secret	1 - 5	*	
Ethylene glycol monopropyl ether	2807-30-9	1 - 5	*	
Ethyl alcohol	64-17-5	1 - 5	*	
1,3,5-Trimethylbenzene (constituent)	108-67-8	1 - 5	*	1
Cumene (constituent)	98-82-8	< 1	*	1
Quartz, crystalline silica	14808-60-7	< 0.5	*	
Ethyl benzene (constituent)	100-41-4	< 0.5	*	1

*The exact percentage (concentration) of composition has been withheld as a trade secret.

Note 1. Type of chemical: Constituent

4. FIRST AID MEASURES

Description of first aid measures

General Advice

Show this safety data sheet to the doctor in attendance.

Eye Contact

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.

Skin Contact

Wash off immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.

Inhalation

Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.

Ingestion

DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Most important symptoms and effects, both acute and delayed

None under normal use conditions.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

No information available.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures**Personal Precautions**

Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

Precautions for safe handling**Handling**

Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Ensure adequate ventilation.

Conditions for safe storage, including any incompatibilities**Storage**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep container closed when not in use. Keep out of the reach of children.

Incompatible Products

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters**Exposure limits**

Component	ACGIH TLV
Stoddard solvent 8052-41-3	TWA: 100 ppm
Crystalline silica (cristobalite) 14464-46-1	TWA: 0.025 mg/m ³ (respirable fraction)
Iron oxide 1309-37-1	TWA: 5 mg/m ³ (respirable fraction)
Ethyl alcohol 64-17-5	STEL: 1000 ppm
Cumene (constituent) 98-82-8	TWA: 50 ppm
Quartz, crystalline silica 14808-60-7	TWA: 0.025 mg/m ³ (respirable fraction)
Ethyl benzene (constituent) 100-41-4	TWA: 20 ppm

Component	OSHA PEL
Stoddard solvent	TWA: 100 ppm

8052-41-3	TWA: 525 mg/m ³ TWA: 500 ppm TWA: 2900 mg/m ³
Calcium Carbonate 1317-65-3	TWA: 15 mg/m ³ (total dust) TWA: 5 mg/m ³ (respirable fraction)
Crystalline silica (cristobalite) 14464-46-1	TWA: 0.05 mg/m ³ (respirable dust)
Iron oxide 1309-37-1	TWA: 10 mg/m ³ (fume)
Ethyl alcohol 64-17-5	TWA: 1000 ppm TWA: 1900 mg/m ³
Cumene (constituent) 98-82-8	TWA: 50 ppm TWA: 245 mg/m ³ Skin
Quartz, crystalline silica 14808-60-7	TWA: 0.1 mg/m ³ (respirable dust)
Ethyl benzene (constituent) 100-41-4	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³

Component	Ontario TWAEV
Stoddard solvent 8052-41-3	TWA: 525 mg/m ³
Crystalline silica (cristobalite) 14464-46-1	TWA: 0.05 mg/m ³ (respirable)
Iron oxide 1309-37-1	TWA: 5 mg/m ³ (respirable)
Ethylene glycol monopropyl ether 2807-30-9	TWA: 25 ppm TWA: 110 mg/m ³ Skin
Ethyl alcohol 64-17-5	STEL: 1000 ppm
Cumene (constituent) 98-82-8	TWA: 50 ppm
Quartz, crystalline silica 14808-60-7	TWA: 0.10 mg/m ³ (respirable)
Ethyl benzene (constituent) 100-41-4	TWA: 100 ppm STEL: 125 ppm

Component	Mexico OEL (TWA)
Stoddard solvent 8052-41-3	TWA/LMPE-PPT: 100 ppm TWA/LMPE-PPT: 523 mg/m ³ STEL/LMPE-CT: 200 ppm STEL/LMPE-CT: 1050 mg/m ³
Calcium Carbonate 1317-65-3	TWA/LMPE-PPT: 10 mg/m ³ STEL/LMPE-CT: 20 mg/m ³
Crystalline silica (cristobalite) 14464-46-1	TWA/LMPE-PPT: 0.05 mg/m ³ (respirable fraction)
Iron oxide 1309-37-1	TWA/LMPE-PPT: 5 mg/m ³ STEL/LMPE-CT: 10 mg/m ³ (as Fe)
Ethyl alcohol 64-17-5	TWA/LMPE-PPT: 1000 ppm TWA/LMPE-PPT: 1900 mg/m ³
Cumene (constituent) 98-82-8	TWA/LMPE-PPT: 50 ppm TWA/LMPE-PPT: 245 mg/m ³ STEL/LMPE-CT: 75 ppm STEL/LMPE-CT: 365 mg/m ³
Quartz, crystalline silica 14808-60-7	TWA/LMPE-PPT: 0.1 mg/m ³ (respirable fraction)
Ethyl benzene (constituent) 100-41-4	TWA/LMPE-PPT: 100 ppm TWA/LMPE-PPT: 435 mg/m ³ STEL/LMPE-CT: 125 ppm STEL/LMPE-CT: 545 mg/m ³

Appropriate engineering controls

Engineering Measures ————— Provide a good standard of general ventilation. Natural ventilation is from doors, windows —————

etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.

Individual protection measures, such as personal protective equipment

Eye/face Protection	Wear safety glasses with side shields (or goggles). If splashes are likely to occur. Wear suitable face shield. Ensure that eyewash stations and safety showers are close to the workstation location.
Skin Protection	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
Respiratory Protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid	Appearance	Colored Liquid
Odor	Characteristic	Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH		No data available
Melting point/freezing point		No data available
Boiling point/Boiling Range	> 149 °C / 300 °F	
Flash Point	29 °C / 85 °F	Pensky Martens Closed Cup (PMCC)
Evaporation rate		No data available
Flammability Limit in Air		
Upper flammability limit		No data available
Lower flammability limit		No data available
Vapor Pressure		No data available
Vapor Density		No data available
Specific Gravity	1.19	
Water Solubility		No data available
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition Temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available

Explosive Properties	No data available
Oxidizing Properties	No data available

Other Information

Photochemically Reactive	Yes
Weight Per Gallon (lbs/gal)	9.94

VOC by weight % (less water)	VOC by volume % (less water)	VOC lbs/gal (less water)	VOC grams/liter (less water)
42.7	61.82	4.25	508.81

10. STABILITY AND REACTIVITY

Reactivity

No information available.

Chemical stability

Stable under normal conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

Hazardous Decomposition ProductsThermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO₂). Carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	There is no data for this product.
Eye Contact	There is no data for this product.
Skin Contact	There is no data for this product.
Ingestion	There is no data for this product.

Component	Oral LD50
Petroleum naphtha, light aromatic 64742-95-6	8400 mg/kg (Rat)
1,2,4-Trimethylbenzene (constituent) 95-63-6	3400 mg/kg (Rat)
Iron oxide 1309-37-1	>10000 mg/kg (Rat)
Ethylene glycol monopropyl ether 2807-30-9	3089 mg/kg (Rat)
Ethyl alcohol 64-17-5	7060 mg/kg (Rat)
1,3,5-Trimethylbenzene (constituent) 108-67-8	5000 mg/kg (Rat)
Cumene (constituent) 98-82-8	1400 mg/kg (Rat)
Quartz, crystalline silica 14808-60-7	500 mg/kg (Rat)
Ethyl benzene (constituent) 100-41-4	3500 mg/kg (Rat)

Component	LD50 Dermal
Petroleum naphtha, light aromatic 64742-95-6	>2000 mg/kg (Rabbit)
1,2,4-Trimethylbenzene (constituent) 95-63-6	>3160 mg/kg (Rabbit)
Ethylene glycol monopropyl ether 2807-30-9	960 µL/kg (Rabbit)
Cumene (constituent) 98-82-8	>3160 mg/kg (Rabbit)
Ethyl benzene (constituent) 100-41-4	15354 mg/kg (Rabbit)

Component	Inhalation LC50
Petroleum naphtha, light aromatic 64742-95-6	3400 ppm (Rat) 4 h >5.2 mg/L (Rat) 4 h
1,2,4-Trimethylbenzene (constituent) 95-63-6	18 g/m ³ (Rat) 4 h
Ethyl alcohol	124.7 mg/L (Rat) 4 h

64-17-5	
1,3,5-Trimethylbenzene (constituent) 108-67-8	24 g/m ³ (Rat) 4 h
Cumene (constituent) 98-82-8	39000 mg/m ³ (Rat) 4 h
Ethyl benzene (constituent) 100-41-4	17.2 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms There is no data for this product.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation There is no data for this product.
Eye damage/irritation There is no data for this product.
Irritation There is no data for this product.
Corrosivity There is no data for this product.
Sensitisation There is no data for this product.
Mutagenic Effects There is no data for this product.
Reproductive Effects There is no data for this product.
STOT - single exposure There is no data for this product.
STOT - repeated exposure There is no data for this product.
Chronic Toxicity There is no data for this product.
Aspiration hazard There is no data for this product.
Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH
Ethyl benzene (constituent) 100-41-4	A3

Component	IARC
Crystalline silica (cristobalite) 14464-46-1	Group 1
Cumene (constituent) 98-82-8	Group 2B
Quartz, crystalline silica 14808-60-7	Group 1
Ethyl benzene (constituent) 100-41-4	Group 2B

Component	NTP
Quartz, crystalline silica 14808-60-7	Known

Component	OSHA
Crystalline silica (cristobalite) 14464-46-1	X
Cumene (constituent) 98-82-8	X
Quartz, crystalline silica 14808-60-7	X
Ethyl benzene (constituent) 100-41-4	X

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 21,228.00 mg/kg
ATEmix (dermal) 9,032.00 mg/kg
ATEmix (inhalation-dust/mist) 41.10 mg/l
ATEmix (inhalation-vapor) 4,343.40 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

None known

0% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Algae/aquatic plants
Cumene (constituent) 98-82-8	72h EC50 Pseudokirchneriella subcapitata: 2.6 mg/L
Ethyl benzene (constituent) 100-41-4	96h EC50 Pseudokirchneriella subcapitata: 1.7 - 7.6 mg/L [static] 72h EC50 Pseudokirchneriella subcapitata: 2.6 - 11.3 mg/L [static] 72h EC50 Pseudokirchneriella subcapitata: 4.6 mg/L 96h EC50 Pseudokirchneriella subcapitata: >438 mg/L

Component	Fish
Petroleum naphtha, light aromatic 64742-95-6	96h LC50 Oncorhynchus mykiss: 9.22 mg/L
1,2,4-Trimethylbenzene (constituent) 95-63-6	96h LC50 Pimephales promelas: 7.19 - 8.28 mg/L [flow-through]
Ethyl alcohol 64-17-5	96h LC50 Oncorhynchus mykiss: 12.0 - 16.0 mg/L [static] 96h LC50 Pimephales promelas: 13400 - 15100 mg/L [flow-through] 96h LC50 Pimephales promelas: >100 mg/L [static]
1,3,5-Trimethylbenzene (constituent) 108-67-8	96h LC50 Pimephales promelas: 3.48 mg/L
Cumene (constituent) 98-82-8	96h LC50 Pimephales promelas: 6.04 - 6.61 mg/L [flow-through] 96h LC50 Oncorhynchus mykiss: 2.7 mg/L [semi-static] 96h LC50 Oncorhynchus mykiss: 4.8 mg/L [flow-through] 96h LC50 Poecilia reticulata: 5.1 mg/L [semi-static]
Ethyl benzene (constituent) 100-41-4	96h LC50 Oncorhynchus mykiss: 11.0 - 18.0 mg/L [static] 96h LC50 Pimephales promelas: 7.55 - 11 mg/L [flow-through] 96h LC50 Pimephales promelas: 9.1 - 15.6 mg/L [static] 96h LC50 Lepomis macrochirus: 32 mg/L [static] 96h LC50 Oncorhynchus mykiss: 4.2 mg/L [semi-static] 96h LC50 Poecilia reticulata: 9.6 mg/L [static]

Component	Crustacea
1,2,4-Trimethylbenzene (constituent) 95-63-6	48h EC50 Daphnia magna: 6.14 mg/L
Ethyl alcohol 64-17-5	48h LC50 Daphnia magna: 9268 - 14221 mg/L 24h EC50 Daphnia magna: 10800 mg/L
1,3,5-Trimethylbenzene (constituent) 108-67-8	24h EC50 Daphnia magna: 50 mg/L
Cumene (constituent) 98-82-8	48h EC50 Daphnia magna: 7.9 - 14.1 mg/L [static] 48h EC50 Daphnia magna: 0.6 mg/L
Ethyl benzene (constituent) 100-41-4	48h EC50 Daphnia magna: 1.8 - 2.4 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

No information available.

Component	Partition coefficient
1,2,4-Trimethylbenzene (constituent) 95-63-6	3.63
Ethyl alcohol 64-17-5	-0.32
Cumene (constituent) 98-82-8	3.55
Ethyl benzene (constituent) 100-41-4	3.118

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste Disposal Methods

Contain and dispose of waste according to local regulations.

Contaminated Packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION

DOT

UN/ID no.	UN1210
Proper Shipping Name	Printing Ink
Hazard Class	3
Packing Group	III

ICAO / IATA / IMDG / IMO

UN/ID no.	UN1210
Proper Shipping Name	Printing Ink
Hazard Class	3
Packing Group	III

15. REGULATORY INFORMATION

International Inventories

All components are listed on the TSCA Inventory. For further information, please contact: Supplier (manufacturer/importer/downstream user/distributor).

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS-No	Weight %	SARA 313 - Threshold Values
1,2,4-Trimethylbenzene (constituent)	95-63-6	5 - 10	1.0
Ethylene glycol monopropyl ether	2807-30-9	1 - 5	1.0
Ethyl benzene (constituent)	100-41-4	< 0.5	0.1

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:.

Component	CAS-No	Weight %
Ethylene glycol monopropyl ether	2807-30-9	1 - 5

U.S. State Regulations

Component	Massachusetts Right To Know
Stoddard solvent 8052-41-3	X
Calcium Carbonate 1317-65-3	X
Crystalline silica (cristobalite) 14464-46-1	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Iron oxide 1309-37-1	X
Ethyl alcohol	X

64-17-5	
1,3,5-Trimethylbenzene (constituent) 108-67-8	X
Cumene (constituent) 98-82-8	X
Quartz, crystalline silica 14808-60-7	X
Ethyl benzene (constituent) 100-41-4	X

Component	Minnesota Right To Know
Stoddard solvent 8052-41-3	X
Calcium Carbonate 1317-65-3	X
Crystalline silica (cristobalite) 14464-46-1	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Iron oxide 1309-37-1	X
Ethyl alcohol 64-17-5	X
Cumene (constituent) 98-82-8	X
Quartz, crystalline silica 14808-60-7	X
Ethyl benzene (constituent) 100-41-4	X

Component	New Jersey Right To Know
Stoddard solvent 8052-41-3	X
Calcium Carbonate 1317-65-3	X
Crystalline silica (cristobalite) 14464-46-1	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Iron oxide 1309-37-1	X
Ethylene glycol monopropyl ether 2807-30-9	X
Ethyl alcohol 64-17-5	X
Cumene (constituent) 98-82-8	X
Quartz, crystalline silica 14808-60-7	X
Ethyl benzene (constituent) 100-41-4	X

Component	Pennsylvania Right To Know
Stoddard solvent 8052-41-3	X
Calcium Carbonate 1317-65-3	X
Crystalline silica (cristobalite) 14464-46-1	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Iron oxide 1309-37-1	X
Inert Pigment	X

Ethylene glycol monopropyl ether 2807-30-9	X
Ethyl alcohol 64-17-5	X
Cumene (constituent) 98-82-8	X
Quartz, crystalline silica 14808-60-7	X
Ethyl benzene (constituent) 100-41-4	X

California Prop. 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

Component	California Prop. 65
Cumene (constituent)	Carcinogen
Quartz, crystalline silica	Carcinogen
Ethyl benzene (constituent)	Carcinogen

This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product

Canada

Component	NPRI - National Pollutant Release Inventory
Stoddard solvent 8052-41-3	Part 5, Other Groups and Mixtures
Petroleum naphtha, light aromatic 64742-95-6	Part 5, Other Groups and Mixtures
1,2,4-Trimethylbenzene (constituent) 95-63-6	Part 1, Group A Substance Part 5, Individual Substances Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
Ethylene glycol monopropyl ether 2807-30-9	Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
Ethyl alcohol 64-17-5	Part 5, Individual Substances Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
1,3,5-Trimethylbenzene (constituent) 108-67-8	Part 5, Isomer Groups total of 1,2,3-Trimethylbenzene, CAS No. 526-73-8, and 1,3,5-Trimethylbenzene, CAS No. 108-67-8, except 1,2,4-Trimethylbenzene, CAS No. 95-63-6 Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
Cumene (constituent) 98-82-8	Part 1, Group A Substance Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
Ethyl benzene (constituent) 100-41-4	Part 1, Group A Substance Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999

16. OTHER INFORMATION

HMIS: Health 2 * Flammability 3 Reactivity 0 Personal Protection X

Key or legend to abbreviations and acronyms used in the safety data sheet**Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

TWA TWA (time-weighted average)
 STEL STEL (Short Term Exposure Limit)
 Ceiling Maximum limit value

ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Revision Date

May-30-2015

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of MSDS