

# **SAFETY DATA SHEET**

Published Date Aug-18-2021 Revision Date Aug-18-2021 Revision Number 2.6

# **1. IDENTIFICATION**

Product identifier Product code	S267	
Product name	Reflex Blue	
Product category	System 2 Series SV Vinyl Screen Ink	
Other means of identification Synonyms	None	
Recommended use of the chemica	I and restrictions on use	
Recommended use	Industrial Printing Operations	
Details of the supplier of the safety	<u>/ data sheet</u>	
UNITED STATES	UNITED KINGDOM	
Nazdar Company	Nazdar Limited	
8501 Hedge Lane Terrace	Barton Road	
Shawnee, KS 66227	Heaton Mersey	

Emergency telephone number

Tel: +001-913-422-1888

Tel: +001-800-677-4657 Fax: +001-913-422-2294 www.nazdar.com

USA: Chemtrec: +001-800-424-9300 Outside USA: Chemtrec: +001-703-527-3887 24 Hour Emergency Phone Number

# 2. HAZARDS IDENTIFICATION

Stockport, England SK4 3EG

Tel: +44 161 442 2111

#### Classification

Skin Corrosion/Irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 1 - (H318)
Flammable liquids	Category 3 - (H226)

#### Label elements



Danger

#### Hazard Statements

H315 - Causes skin irritation H318 - Causes serious eye damage H226 - Flammable liquid and vapor

#### **Precautionary Statements**

P264 - Wash face, hands and any exposed skin thoroughly after handling

P332 + P313 - If skin irritation occurs: Get medical advice/attention

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P233 - Keep container tightly closed

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P403 + P235 - Store in a well-ventilated place. Keep cool

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

#### Hazards not otherwise classified (HNOC)

No information available.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixture

Component	CAS-No	Weight %	Trade Secret	Note
Ethylene glycol monopropyl ether	2807-30-9	10 - 30	*	
Cyclohexanone	108-94-1	10 - 30	*	
Diethylene glycol ethyl ether acetate	112-15-2	1 - 5	*	
Titanium dioxide	13463-67-7	1 - 5	*	

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST-AID MEASURES

#### **Description of first aid measures**

General Advice Eye Contact	Show this safety data sheet to the doctor in attendance. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.
Skin Contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.
Inhalation	Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Most important symptoms and effects, both acute and delayed

None under normal use conditions.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.

# **5. FIRE-FIGHTING MEASURES**

#### Suitable Extinguishing Media

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

#### Unsuitable Extinguishing Media

No information available.

### Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

# 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

#### **Personal Precautions**

Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

# Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

#### Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

Handling	Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Ensure adequate ventilation.		
Conditions for safe storage, including any incompatibilities			
Storage	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep container closed when not in use. Keep out of the reach of children.		
Incompatible Products	Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.		

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

#### Exposure limits

Cyclohexanone

108-94-1

Component	ACGIH TLV	
Cyclohexanone	TWA: 20 ppm	
108-94-1	STEL: 50 ppm	
	Skin	
Titanium dioxide	TWA: 10 mg/m <sup>3</sup>	
13463-67-7		
Component	OSHA PEL	
Cyclohexanone	TWA: 50 ppm	
108-94-1	TWA: 200 mg/m <sup>3</sup>	
Titanium dioxide	TWA: 15 mg/m <sup>3</sup> total dust	
13463-67-7		
Component	OSHA PEL (vacated)	
Cyclohexanone	TWA: 25 ppm	
108-94-1	TWA: 100 mg/m <sup>3</sup>	
	Skin	
Titanium dioxide	TWA: 10 mg/m <sup>3</sup> total dust	
13463-67-7		
Component	Ontario TWAEV	
Ethylene glycol monopropyl ether		
2807-30-9	TWA: 25 ppm	
2007-30-9	TWA: 110 mg/m <sup>3</sup>	
	Skin	

TWA: 20 ppm

STEL: 50 ppm

	Skin
	TWA: 10 mg/m <sup>3</sup>
13463-67-7	

Component	Mexico OEL (TWA)
Cyclohexanone	TWA/VLE-PPT: 20 ppm
108-94-1	STEL/PPT-CT: 50 ppm
Titanium dioxide	TWA/VLE-PPT: 10 mg/m <sup>3</sup>
13463-67-7	

# Appropriate engineering controls

Engineering Measures	Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.
Individual protection measures, suc	ch as personal protective equipment
Eye/Face Protection	Wear safety glasses with side shields (or goggles). If splashes are likely to occur:. Wear suitable face shield. Ensure that eyewash stations and safety showers are close to the workstation location.
Skin Protection	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
Hand Protection	Chemical resistant protective gloves. Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding >480 minutes of permeation time): eg. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), polyvinylchloride (0.7 mm) and other Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers. Taking into account the varying conditions, the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing. Due to different glove types, the manufacturer's directions for use should be observed. Replace gloves immediately when torn or any change in appearance is noticed such as dimension, color, flexibility.
Respiratory Protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material.
General Hygiene Consideration	<b>s</b> Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and Physical State	<u>l chemical properties</u> Liquid	Color	Colored
Odor	Characteristic	Odor Threshold	No information available
<u>Property</u> pH	<u>Values</u>	<b>Remarks • Method</b> No data available	
Melting Point / Freezing Point		No data available	
Boiling Point / Boiling Range	> 149 °C / 300 °F	Develop Mantana Olara	
Flash Point Evaporation rate	46 °C / 115 °F	Pensky Martens Close No data available	a Cup (PMCC)
Flammability Limit in Air Upper flammability limit		No data available	

VOC by weight %	VOC by volume %	VOC lbs/gal	V
Weight Per Gallon (Ibs/gal)	8.86		
Photochemically Reactive	No		
Other Information			
Oxidizing Properties	No data available		
Explosive Properties	No data available		
Dynamic viscosity		No data available	
Kinematic viscosity		No data available	
Decomposition temperature		No data available	
Autoignition Temperature	Water	No data available	
Solubility in other solvents Partition coefficient: n-octanol/	water	No data available	
Water Solubility		No data available No data available	
Specific Gravity	1.06		
Vapor Density		No data available	
Vapor Pressure		No data available	
Lower flammability limit		No data available	

VOC by weight %	VOC by volume %	VOC lbs/gal	VOC grams/liter
(less water)	(less water)	(less water)	(less water)
57.64	59.49	5.11	612.4
		•	

# **10. STABILITY AND REACTIVITY**

#### **Reactivity**

No information available.

### Chemical stability

Stable under normal conditions.

#### Possibility of Hazardous Reactions

None under normal processing.

#### Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

#### Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

# Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO2). Carbon monoxide.

# **11. TOXICOLOGICAL INFORMATION**

# Information on likely routes of exposure

Inhalation	Specific test data for the substance or mixture is not available.
Eye Contact	Specific test data for the substance or mixture is not available.
Skin Contact	Specific test data for the substance or mixture is not available.
Ingestion	Specific test data for the substance or mixture is not available.

Component	Oral LD50
Ethylene glycol monopropyl ether 2807-30-9	= 3089 mg/kg (Rat)
Cyclohexanone 108-94-1	= 1544 mg/kg (Rat)
Diethylene glycol ethyl ether acetate 112-15-2	= 11 g/kg (Rat)
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)

Component	Dermal LD50
Ethylene glycol monopropyl ether	= 870 mg/kg (Rabbit)
2807-30-9	
Cyclohexanone	= 947 mg/kg (Rabbit)
108-94-1	
Diethylene glycol ethyl ether acetate	= 15100 mg/kg (Rabbit)
112-15-2	
Component	Inhalation LC50
Ethylene glycol monopropyl ether	= 1530 ppm (Rat)7 h
2807-30-9	

2807-30-9	
Cyclohexanone	> 6.2 mg/L (Rat) 4 h
108-94-1	
Titanium dioxide	= 5.09 mg/L (Rat)4 h
13463-67-7	

#### Information on toxicological effects

Symptoms

Specific test data for the substance or mixture is not available.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Specific test data for the substance or mixture is not available. Causes skin irritation (pain, redness and swelling). (based on components).		
Eye damage/irritation	Specific test data for the substance or mixture is not available. Causes serious eye damage. (based on components).		
Irritation	Specific test data for the substance or mixture is not available.		
Corrosivity	Specific test data for the substance or mixture is not available.		
Sensitization	Specific test data for the substance or mixture is not available.		
Mutagenic Effects	Specific test data for the substance or mixture is not available.		
Carcinogenic effects	Specific test data for the substance or mixture is not available.		
Reproductive Effects	Specific test data for the substance or mixture is not available.		
STOT - single exposure	Specific test data for the substance or mixture is not available.		
STOT - repeated exposure	Specific test data for the substance or mixture is not available.		
Chronic Toxicity	Specific test data for the substance or mixture is not available		
Aspiration hazard	Specific test data for the substance or mixture is not available.		
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.		
Component	ACGIH		
Cyclohexanone	АЗ		
108-94-1			

Component	IARC
Titanium dioxide	Group 2B
13463-67-7	

Component	OSHA
Titanium dioxide	X
13463-67-7	

# Numerical measures of toxicity - Product Information

**Unknown Acute Toxicity** 

0 % of the mixture consists of ingredient(s) of unknown toxicity

# The following values are calculated based on chapter 3.1 of the GHS document ATEmix (oral) 6,746.00 mg/kg

ATEmix (oral)	6,746.00 mg/kg	
ATEmix (dermal)	2,095.00 mg/kg	
ATEmix (inhalation-dust/mist)	6.60 mg/l	
ATEmix (inhalation-vapor)	48.00 mg/l	

# **12. ECOLOGICAL INFORMATION**

**Ecotoxicity** Specific test data for the substance or mixture is not available.

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Fish
Ethylene glycol monopropyl ether 2807-30-9	96h LC50 Pimephales promelas: > 5000 mg/L [static]
	96h LC50 Pimephales promelas: 481 - 578 mg/L (flow-through) 96h LC50 Pimephales promelas: = 8.9 mg/L

# Persistence and Degradability

No information available.

#### **Bioaccumulation**

Component	Partition coefficient
Cyclohexanone	0.86
108-94-1	

13. DISPOSAL CONSIDERATIONS		
Waste treatment methods		
Waste Disposal Methods	Contain and dispose of waste according to local regulations.	
Contaminated Packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.	
	14. TRANSPORT INFORMATION	
Note:	This information is not intended to convey all specific transportation requirements relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation information can be found in the specific regulations for your mode of transportation. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.	
DOTUN/ID no	In the U.S. and Canada, this material may be reclassified as a combustible liquid and is not regulated, via surface transportation, in containers less than 119 gallons or 450 liters [per 49 CFR 173.150 (f)] [per Transportation of Dangerous Goods Regulations/Clear Language Part 1.33]. UN1210	
Proper Shipping Name	Printing Ink	
Hazard Class Packing Group	3 	
ICAO / IATA / IMDG / IMO UN/ID no Proper Shipping Name Hazard Class Packing Group	UN1210 Printing Ink 3 III	

# **15. REGULATORY INFORMATION**

# **International Inventories**

All components are listed on the TSCA Inventory. For further information, please contact:. Supplier

(manufacturer/importer/downstream user/distributor).

#### U.S. Federal Regulations

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS-NO	weight %	Values
Ethylene glycol monopropyl ether	2807-30-9	10 - 30	1.0
Diethylene glycol ethyl ether acetate	112-15-2	1 - 5	1.0

# Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:.

Component	CAS-No	Weight %
Ethylene glycol monopropyl ether	2807-30-9	10 - 30
Diethylene glycol ethyl ether acetate	112-15-2	1 - 5
Xylenes (o-, m-, p- isomers)	1330-20-7	0.1 - < 1

# U.S. State Regulations

	Massachusetts Right To Know
Cyclohexanone 108-94-1	X
Titanium dioxide 13463-67-7	X

	Minnesota
	Right To Know
Cyclohexanone	X
108-94-1	
Titanium dioxide	X
13463-67-7	

	New Jersey Right To Know
Ethylene glycol monopropyl ether 2807-30-9	^
Cyclohexanone 108-94-1	X
Diethylene glycol ethyl ether acetate 112-15-2	X
Titanium dioxide 13463-67-7	X

Component	Pennsylvania Right To Know
Ethylene glycol monopropyl ether 2807-30-9	X
Cyclohexanone 108-94-1	X
Diethylene glycol ethyl ether acetate 112-15-2	X
Titanium dioxide 13463-67-7	X

# California Prop. 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

Component	Califor	nia Prop. 65		
Titanium dioxide	Carcino			
		C		

- This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

#### <u>Canada</u>

Component	NPRI - National Pollutant Release Inventory
Ethylene glycol monopropyl ether	Part 5, Other Groups and Mixtures (total of CAS 112-07-2, CAS
2807-30-9	112-15-2, CAS 112-25-4, CAS 112-34-5, CAS 5131-66-8, CAS
	107-98-2, CAS 109-59-1, CAS 111-90-0, CAS 124-17-4, CAS
	1569-01-3, CAS 1569-02-4, CAS 2807-30-9, CAS 29911-27-1,
	CAS 29911-28-2, CAS 34590-94-8, CAS 54839-24-6, CAS
	623-84-7, CAS 88917-22-0 and their isomers, listed under Other
	Glycol ethers and acetates (and their isomers)) Part 4 Substance
	(as set out in Section 65 of the List of Toxic Substances in
	Schedule 1 of the Canadian Environmental Protection Act, 1999)
Cyclohexanone	Part 4 Substance (as set out in Section 65 of the List of Toxic
108-94-1	Substances in Schedule 1 of the Canadian Environmental
	Protection Act, 1999)
Diethylene glycol ethyl ether acetate	Part 5, Other Groups and Mixtures (total of CAS 112-07-2, CAS
112-15-2	112-15-2, CAS 112-25-4, CAS 112-34-5, CAS 5131-66-8, CAS
	107-98-2, CAS 109-59-1, CAS 111-90-0, CAS 124-17-4, CAS
	1569-01-3, CAS 1569-02-4, CAS 2807-30-9, CAS 29911-27-1,
	CAS 29911-28-2, CAS 34590-94-8, CAS 54839-24-6, CAS
	623-84-7, CAS 88917-22-0 and their isomers, listed under Other
	Glycol ethers and acetates (and their isomers)) Part 4 Substance
	(as set out in Section 65 of the List of Toxic Substances in
	Schedule 1 of the Canadian Environmental Protection Act, 1999)

# **16. OTHER INFORMATION**

HMIS:	Health	Flammability	Reactivity	Personal Protection
	2 *	2	0	Х

#### Key or legend to abbreviations and acronyms used in the safety data sheet

Legend	- Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION
TŴĂ	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)

Ceiling Maximum limit value

ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen
A2 - Suspected Human Carcinogen
A3 - Animal Carcinogen
IARC: (International Agency for Research on Cancer)
Group 1 - Carcinogenic to Humans
Group 2A - Probably Carcinogenic to Humans
Group 2B - Possibly Carcinogenic to Humans
NTP: (National Toxicity Program)
Known - Known Carcinogen
Reasonably Anticipated to be a Human Carcinogen
OSHA: (Occupational Safety & Health Administration)
X - Present

# Revision Date Aug-18-2021

#### Pursuant to NOM-018-STPS-2015

This information within is considered correct but is not exhaustive and will be used for guidance only, which is based on the current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet