

SAFETY DATA SHEET

Published DateRevision DateRevision NumberMay-15-2019May-15-20192.5

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product code S2HTB

Product name Halftone Blue

Product category System 2 Series SV Vinyl Screen Ink

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use
Recommended use Printing operations

Details of the supplier of the safety data sheet

UNITED STATES
UNITED KINGDOM
Nazdar Company
Nazdar Limited
8501 Hedge Lane Terrace
Shawnee, KS 66227
Barton Road
Heaton Mersey

Tel: +001-913-422-1888 Stockport, England SK4 3EG
Tel: +001-800-677-4657 Tel: +44 161 442 2111

Fax: +001-900-677-4657 www.nazdar.com

www.nazdar.com

Emergency telephone number

USA: Chemtrec: +001-800-424-9300 Outside USA: Chemtrec: +001-703-527-3887

24 Hour Emergency Phone Number

2. HAZARDS IDENTIFICATION

Classification

Skin Corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 1 - (H318)
Flammable liquids	Category 3 - (H226)

Label elements





Signal Word Danger

Hazard Statements

H315 - Causes skin irritation

H318 - Causes serious eye damage H226 - Flammable liquid and vapor

Precautionary Statements

P264 - Wash face, hands and any exposed skin thoroughly after handling

S2HTB Halftone Blue Revision Date May-15-2019

P332 + P313 - If skin irritation occurs: Get medical advice/attention

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P233 - Keep container tightly closed

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P403 + P235 - Store in a well-ventilated place. Keep cool

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Hazards not otherwise classified (HNOC)

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Component	CAS-No	Weight %	Trade Secret	Note
Ethylene glycol monopropyl ether	2807-30-9	10 - 30	*	
Cyclohexanone	108-94-1	10 - 30	*	
Ethylene glycol monobutyl ether acetate	112-07-2	1 - 5	*	
Diethylene glycol ethyl ether acetate	112-15-2	1 - 5	*	
Additive	Trade Secret	< 1	*	
Ethyl alcohol	64-17-5	< 0.5	*	

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General Advice Show this safety data sheet to the doctor in attendance.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Get medical attention if irritation develops and

persists.

Skin Contact Wash off immediately with soap and plenty of water for at least 15 minutes. Remove

contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.

Inhalation Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or

stopped, administer artificial respiration. Get medical attention immediately.

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a

physician or poison control center immediately.

Most important symptoms and effects, both acute and delayed

None under normal use conditions.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

No information available.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full

protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and

clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people

away from and upwind of spill/leak.

Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

Precautions for safe handling

HandlingUse personal protective equipment as required. Do not eat, drink or smoke when using this

product. Ensure adequate ventilation.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

open flames, hot surfaces and sources of ignition. Keep container closed when not in use.

Keep out of the reach of children.

Incompatible Products Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits

Component	ACGIH TLV	
Cyclohexanone	TWA: 20 ppm	
108-94-1	STEL: 50 ppm	
	Skin	
Ethylene glycol monobutyl ether acetate	TWA: 20 ppm	
112-07-2		
Ethyl alcohol	STEL: 1000 ppm	
64-17-5		

Component	OSHA PEL
Cyclohexanone	TWA: 50 ppm
108-94-1	TWA: 200 mg/m ³
Ethyl alcohol	TWA: 1000 ppm
64-17-5	TWA: 1900 mg/m ³

Component	OSHA PEL (vacated)
Cyclohexanone	TWA: 25 ppm
108-94-1	TWA: 100 mg/m ³
	Skin
Ethyl alcohol	TWA: 1000 ppm
64-17-5	TWA: 1900 mg/m ³

Component	Ontario TWAEV

Ethylene glycol monopropyl ether 2807-30-9	TWA: 25 ppm TWA: 110 mg/m ³ Skin
Cyclohexanone 108-94-1	TWA: 20 ppm STEL: 50 ppm Skin
Ethylene glycol monobutyl ether acetate 112-07-2	TWA: 20 ppm
Ethyl alcohol 64-17-5	STEL: 1000 ppm

Component	Mexico OEL (TWA)
Cyclohexanone	TWA/VLE-PPT: 50 ppm
108-94-1	TWA/VLE-PPT: 200 mg/m³
	STEL/PPT-CT: 100 ppm
	STEL/PPT-CT: 400 mg/m³
Ethyl alcohol	TWA/VLE-PPT: 1000 ppm
64-17-5	TWA/VLE-PPT: 1900 mg/m ³

Appropriate engineering controls

Engineering Measures

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Wear safety glasses with side shields (or goggles). If splashes are likely to occur:. Wear

suitable face shield. Ensure that eyewash stations and safety showers are close to the

workstation location.

Skin Protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls,

as appropriate, to prevent skin contact.

Hand Protection Chemical resistant protective gloves.

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding >480 minutes of permeation time): eg. nitrile rubber (0.4 mm), chloroprene

rubber (0.5 mm), polyvinylchloride (0.7 mm) and other

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers. Taking into account the varying conditions, the practical usage of a

chemical-protective glove in practice may be much shorter than the permeation time

determined through testing.

Due to different glove types, the manufacturer's directions for use should be observed. Replace gloves immediately when torn or any change in appearance is noticed such as

dimension, color, flexibility.

Respiratory Protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of

the material.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before

eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of

equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Liquid Appearance Colored Liquid

Odor Characteristic Odor Threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No data available

Melting Point / Freezing Point

No data available

Melting Point / Freezing Point

No data available

Boiling Point / Boiling Range > 149 °C / 300 °F

Flash Point 46 °C / 115 °F Pensky Martens Closed Cup (PMCC)

Evaporation rate No data available Flammability Limit in Air

Upper flammability limit
Lower flammability limit
No data available
No data available
Vapor Pressure
No data available
Vapor Density
No data available

Vapor Density No data Specific Gravity 1.06

Water SolubilityNo data availableSolubility in other solventsNo data availablePartition coefficient: n-octanol/waterNo data availableAutoignition TemperatureNo data availableDecomposition temperatureNo data availableKinematic viscosityNo data available

Explosive Properties No data available Oxidizing Properties No data available

Other Information

Dynamic viscosity

Photochemically Reactive No Weight Per Gallon (lbs/gal) 8.81

VOC by weight %	VOC by volume %	VOC lbs/gal	VOC grams/liter
(less water)	(less water)	(less water)	(less water)
67.54	No information available	5.95	712.64

No data available

10. STABILITY AND REACTIVITY

Reactivity

No information available.

Chemical stability

Stable under normal conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO2). Carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

InhalationSpecific test data for the substance or mixture is not available.Eye ContactSpecific test data for the substance or mixture is not available.Skin ContactSpecific test data for the substance or mixture is not available.IngestionSpecific test data for the substance or mixture is not available.

Component Oral LD50

S2HTB Halftone Blue

Ethylene glycol monopropyl ether 2807-30-9	= 3089 mg/kg(Rat)
Cyclohexanone 108-94-1	= 1544 mg/kg(Rat)
Ethylene glycol monobutyl ether acetate 112-07-2	= 2400 mg/kg(Rat)
Diethylene glycol ethyl ether acetate 112-15-2	= 11 g/kg(Rat)
Ethyl alcohol 64-17-5	= 7060 mg/kg(Rat)

Component	Dermal LD50
Ethylene glycol monopropyl ether	= 870 mg/kg(Rabbit)
2807-30-9	
Cyclohexanone	= 947 mg/kg(Rabbit)
108-94-1	
Ethylene glycol monobutyl ether acetate	= 1500 mg/kg(Rabbit)
112-07-2	
Diethylene glycol ethyl ether acetate	= 15.1 mL/kg(Rabbit)
112-15-2	

Component	Inhalation LC50
1 , 0, 1,	= 1530 ppm (Rat) 7 h
2807-30-9	(2)
1 '	= 8000 ppm (Rat) 4 h
108-94-1	
Ethylene glycol monobutyl ether acetate	> 400 ppm (Rat) 4 h
112-07-2	
Ethyl alcohol	= 124.7 mg/L (Rat) 4 h
64-17-5	

Information on toxicological effects

Symptoms

Specific test data for the substance or mixture is not available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Specific test data for the substance or mixture is not available. Causes skin irritation (pain,

redness and swelling). (based on components).

Eye damage/irritation Specific test data for the substance or mixture is not available. Causes serious eye

damage. (based on components).

Specific test data for the substance or mixture is not available. Irritation Specific test data for the substance or mixture is not available. Corrosivity Sensitization Specific test data for the substance or mixture is not available. Specific test data for the substance or mixture is not available. **Mutagenic Effects** Specific test data for the substance or mixture is not available. Carcinogenic effects **Reproductive Effects** Specific test data for the substance or mixture is not available. Specific test data for the substance or mixture is not available. STOT - single exposure STOT - repeated exposure Specific test data for the substance or mixture is not available. **Chronic Toxicity** Specific test data for the substance or mixture is not available **Aspiration hazard** Specific test data for the substance or mixture is not available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

our on ogoniony	The table below indicates whether each agoney has noted any ingredient as a carolinegen.	
Component	ACGIH	
Cyclohexanone	A3	
108-94-1		
Ethylene glycol monobutyl ether acetate	A3	
112-07-2		
Ethyl alcohol	A3	
64-17-5		

Component	IARC
Ethyl alcohol	Group 1
64-17-5	· ·

S2HTB Halftone Blue

Component	OSHA
Ethyl alcohol	X
64-17-5	

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0 % of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 9,620.00 mg/kg

 ATEmix (dermal)
 2,321.00 mg/kg

 ATEmix (inhalation-dust/mist)
 7.40 mg/l

 ATEmix (inhalation-vapor)
 54.00 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Specific test data for the substance or mixture is not available.

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Algae/aquatic plants
Ethylene glycol monobutyl ether acetate	72h EC50 Desmodesmus subspicatus: > 500 mg/L
112-07-2	·

Component	Fish
Cyclohexanone	96h LC50 Pimephales promelas: 481 - 578 mg/L (flow-through)
108-94-1	96h LC50 Pimephales promelas: = 8.9 mg/L
Ethyl alcohol	96h LC50 Oncorhynchus mykiss: 12.0 - 16.0 mL/L (static)
64-17-5	96h LC50 Pimephales promelas: 13400 - 15100 mg/L
	(flow-through)
	96h LC50 Pimephales promelas: > 100 mg/L (static)

Component	Crustacea
Ethylene glycol monobutyl ether acetate	48h EC50 Daphnia magna: = 37 mg/L
112-07-2	
Ethyl alcohol	48h LC50 Daphnia magna: 9268 - 14221 mg/L
64-17-5	48h EC50 Daphnia magna: = 2 mg/L Static

Persistence and Degradability

No information available.

Bioaccumulation

No information available

Component	Partition coefficient
Cyclohexanone	0.86
108-94-1	
Ethylene glycol monobutyl ether acetate	1.51
112-07-2	
Ethyl alcohol	-0.32
64-17-5	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste Disposal Methods Contain and dispose of waste according to local regulations.

S2HTB Halftone Blue Revision Date May-15-2019

Contaminated Packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION

Note: This information is not intended to convey all specific transportation requirements relating to

this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation information can be found in the specific regulations for your mode of transportation. It is the responsibility of the transporting organization to follow all applicable laws, regulations and

rules relating to the transportation of the material.

DOT In the U.S. and Canada, this material may be reclassified as a combustible liquid and is not

regulated, via surface transportation, in containers less than 119 gallons or 450 liters [per 49 CFR 173.150 (f)] [per Transportation of Dangerous Goods Regulations/Clear Language

Part 1.33].

UN/ID no. UN1210 Proper Shipping Name Printing Ink

Hazard Class 3 Packing Group III

ICAO / IATA / IMDG / IMO

UN1210
Proper Shipping Name
UN1210
Printing Ink

Hazard Class 3
Packing Group III

15. REGULATORY INFORMATION

International Inventories

All components are listed on the TSCA Inventory. For further information, please contact.. Supplier (manufacturer/importer/downstream user/distributor).

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS-No	Weight %	SARA 313 - Threshold Values
Ethylene glycol monopropyl ether	2807-30-9	10 - 30	1.0
Ethylene glycol monobutyl ether acetate	112-07-2	1 - 5	1.0
Diethylene glycol ethyl ether acetate	112-15-2	1 - 5	1.0

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:.

Component	CAS-No	Weight %
Ethylene glycol monopropyl ether	2807-30-9	10 - 30
Ethylene glycol monobutyl ether acetate	112-07-2	1 - 5
Diethylene glycol ethyl ether acetate	112-15-2	1 - 5

U.S. State Regulations

	Massachusetts Right To Know
Cyclohexanone 108-94-1	X
Ethyl alcohol	X

64-17-5		
Component	Minnesota Right To Know	
Cyclohexanone 108-94-1	X	
Ethyl alcohol	X	
64-17-5		
Component	New Jersey Right To Know	
Ethylene glycol monopropyl ether 2807-30-9	X	
Cyclohexanone 108-94-1	X	
Ethylene glycol monobutyl ether acetate 112-07-2	x	
Diethylene glycol ethyl ether acetate 112-15-2	x	
Ethyl alcohol 64-17-5	X	
0+110		
Component	Pennsylvania Right To Know	
Ethylene glycol monopropyl ether 2807-30-9	x	
Cyclohexanone 108-94-1	X	
Ethylene glycol monobutyl ether acetate 112-07-2	X	
Diethylene glycol ethyl ether acetate 112-15-2	x	
Ethyl alcohol 64-17-5	x	
<u>California Prop. 65</u> This product contains chemical(s) known to the State of California	a to cause cancer and/or to cause hirth defects or other	
reproductive harm	a to cause carried analor to cause birth delects of other	
Component	California Prop. 65	
Ethyl alcohol	nogen	
,	Developmental	
<u>Canada</u>		
Component	NPRI - National Pollutant Release Inventory	
Ethylene glycol monopropyl ether 2807-30-9	Part 5, Other Groups and Mixtures; Part 4 Substance	
Cyclohexanone 108-94-1	Part 4 Substance	
Ethylene glycol monobutyl ether acetate 112-07-2	Part 5, Other Groups and Mixtures; Part 4 Substance	
Diethylene glycol ethyl ether acetate 112-15-2	Part 5, Other Groups and Mixtures; Part 4 Substance	
Ethyl alcohol 64-17-5	Part 5, Individual Substances; Part 4 Substance	
[OT 17 0		
16. OTHER II	NFORMATION	
HMIS: Health Flamr	nability Reactivity Personal Protection	
	2 0 X	

Key or legend to abbreviations and acronyms used in the safety data sheet

S2HTB Halftone Blue Revision Date May-15-2019

Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value

ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen
Reasonably Anticipated to be a Human Carcinogen
OSHA: (Occupational Safety & Health Administration)

X - Present

Revision Date May-15-2019

Pursuant to NOM-018-STPS-2015

This information within is considered correct but is not exhaustive and will be used for guidance only, which is based on the current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet