

Print Date  
May-31-2015

Revision Date  
May-30-2015

Revision Number  
1

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

**Product identifier**

Product code **59410**  
Product name **Yellow**  
Product category **59000 Series Enamel Plus Gloss Screen Ink**

**Other means of identification**

Synonyms None

**Recommended use of the chemical and restrictions on use**

Recommended use Printing operations

**Details of the supplier of the safety data sheet**

|  |                            |
|--|----------------------------|
| UNITED STATES                                      | UNITED KINGDOM             |
| Nazdar Company                                     | Nazdar Limited             |
| 8501 Hedge Lane Terrace                            | Barton Road                |
| Shawnee, KS 66227                                  | Heaton Mersey              |
| Tel: 1-913-422-1888                                | Stockport, England SK4 3EG |
| Tel: 1-800-677-4657                                | Tel: +44 161 442 2111      |
| Fax: 1-913-422-2294                                |                            |
| <a href="http://www.nazdar.com">www.nazdar.com</a> |                            |

**Emergency telephone number**

USA: Chemtrec: 1-800-424-9300  
Outside USA: Chemtrec: 1-703-527-3887  
24 Hour Emergency Phone Number

**2. HAZARDS IDENTIFICATION**

**Classification**

|                     |                     |
|---------------------|---------------------|
| Aspiration toxicity | Category 1 - (H304) |
| Flammable liquids   | Category 3 - (H226) |

**Label elements**



**Signal Word**  
Danger

**Hazard Statements**

H304 - May be fatal if swallowed and enters airways  
H226 - Flammable liquid and vapor  
EUH208 - May produce an allergic reaction

P331 - Do NOT induce vomiting  
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

**Hazards not otherwise classified (HNOC)**

No information available.

**3. COMPOSITION/INFORMATION ON INGREDIENTS****Mixture**

| Component                                     | CAS-No       | Weight % | Trade Secret | Note |
|---|--------------|----------|--------------|------|
| Stoddard solvent                              | 8052-41-3    | 10 - 30  | *            |      |
| Barium sulfate                                | 7727-43-7    | 10 - 30  | *            |      |
| Titanium dioxide                              | 13463-67-7   | 1 - 5    | *            |      |
| Solvent naphtha (petroleum), medium aliphatic | 64742-88-7   | 1 - 5    | *            |      |
| Naphtha (petroleum), heavy aromatic           | 64742-94-5   | 1 - 5    | *            |      |
| Xylenes (o-, m-, p- isomers)                  | 1330-20-7    | 1 - 5    | *            |      |
| Ethyl benzene (constituent)                   | 100-41-4     | < 0.5    | *            | 1    |
| Crystalline silica (cristobalite)             | 14464-46-1   | < 0.5    | *            |      |
| Naphthalene (constituent)                     | 91-20-3      | < 0.5    | *            | 1    |
| Cobalt Compounds                              | Trade Secret | < 0.5    | *            |      |

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

Note 1. Type of chemical: Constituent

**4. FIRST AID MEASURES****Description of first aid measures****General Advice**

Show this safety data sheet to the doctor in attendance.

**Eye Contact**

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.

**Skin Contact**

Wash off immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.

**Inhalation**

Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.

**Ingestion**

DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

**Most important symptoms and effects, both acute and delayed**

None under normal use conditions.

**Indication of any immediate medical attention and special treatment needed****Notes to Physician**

Treat symptomatically.

**5. FIRE-FIGHTING MEASURES****Suitable Extinguishing Media**Foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.**Unsuitable Extinguishing Media**

No information available.

**Specific Hazards Arising from the Chemical**

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal Precautions** Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

### Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

### Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Ensure adequate ventilation.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep container closed when not in use. Keep out of the reach of children.

**Incompatible Products** Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure limits

| Component                                       | ACGIH TLV  |
|---|--|
| Stoddard solvent<br>8052-41-3                   | TWA: 100 ppm                                       |
| Barium sulfate<br>7727-43-7                     | TWA: 10 mg/m <sup>3</sup>                          |
| Titanium dioxide<br>13463-67-7                  | TWA: 10 mg/m <sup>3</sup>                          |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7       | TWA: 100 ppm<br>STEL: 150 ppm                      |
| Ethyl benzene (constituent)<br>100-41-4         | TWA: 20 ppm  |
| Crystalline silica (cristobalite)<br>14464-46-1 | TWA: 0.025 mg/m <sup>3</sup> (respirable fraction) |
| Naphthalene (constituent)<br>91-20-3            | TWA: 10 ppm<br>STEL: 15 ppm<br>Skin                |

| Component                     | OSHA PEL  |
|-------------------------------|---|
| Stoddard solvent<br>8052-41-3 | TWA: 100 ppm<br>TWA: 525 mg/m <sup>3</sup><br>TWA: 500 ppm<br>TWA: 2900 mg/m <sup>3</sup> |
| Barium sulfate                | TWA: 10 mg/m <sup>3</sup> (total dust)  |

|   |  |
|---|--|
| 7727-43-7                                       | TWA: 5 mg/m <sup>3</sup> (respirable fraction)<br>TWA: 15 mg/m <sup>3</sup> (total dust)   |
| Titanium dioxide<br>13463-67-7                  | TWA: 10 mg/m <sup>3</sup> (total dust)<br>TWA: 15 mg/m <sup>3</sup> (total dust)           |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7       | TWA: 100 ppm<br>TWA: 435 mg/m <sup>3</sup><br>STEL: 150 ppm<br>STEL: 655 mg/m <sup>3</sup> |
| Ethyl benzene (constituent)<br>100-41-4         | TWA: 100 ppm<br>TWA: 435 mg/m <sup>3</sup><br>STEL: 125 ppm<br>STEL: 545 mg/m <sup>3</sup> |
| Crystalline silica (cristobalite)<br>14464-46-1 | TWA: 0.05 mg/m <sup>3</sup> (respirable dust)  |
| Naphthalene (constituent)<br>91-20-3            | TWA: 10 ppm<br>TWA: 50 mg/m <sup>3</sup><br>STEL: 15 ppm<br>STEL: 75 mg/m <sup>3</sup>     |

| Component   | Ontario TWAEV                            |
|---|--|
| Stoddard solvent<br>8052-41-3                               | TWA: 525 mg/m <sup>3</sup>               |
| Barium sulfate<br>7727-43-7                                 | TWA: 10 mg/m <sup>3</sup> (total dust)   |
| Titanium dioxide<br>13463-67-7                              | TWA: 10 mg/m <sup>3</sup> (total dust)   |
| Solvent naphtha (petroleum), medium aliphatic<br>64742-88-7 | TWA: 525 mg/m <sup>3</sup>               |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7                   | TWA: 100 ppm<br>STEL: 150 ppm            |
| Ethyl benzene (constituent)<br>100-41-4                     | TWA: 100 ppm<br>STEL: 125 ppm            |
| Crystalline silica (cristobalite)<br>14464-46-1             | TWA: 0.05 mg/m <sup>3</sup> (respirable) |
| Naphthalene (constituent)<br>91-20-3                        | TWA: 10 ppm<br>STEL: 15 ppm<br>Skin      |

| Component                                       | Mexico OEL (TWA)  |
|---|---|
| Stoddard solvent<br>8052-41-3                   | TWA/LMPE-PPT: 100 ppm<br>TWA/LMPE-PPT: 523 mg/m <sup>3</sup><br>STEL/LMPE-CT: 200 ppm<br>STEL/LMPE-CT: 1050 mg/m <sup>3</sup> |
| Titanium dioxide<br>13463-67-7                  | TWA/LMPE-PPT: 10 mg/m <sup>3</sup> (as Ti)<br>STEL/LMPE-CT: 20 mg/m <sup>3</sup> (as Ti)                                      |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7       | TWA/LMPE-PPT: 100 ppm<br>TWA/LMPE-PPT: 435 mg/m <sup>3</sup><br>STEL/LMPE-CT: 150 ppm<br>STEL/LMPE-CT: 655 mg/m <sup>3</sup>  |
| Ethyl benzene (constituent)<br>100-41-4         | TWA/LMPE-PPT: 100 ppm<br>TWA/LMPE-PPT: 435 mg/m <sup>3</sup><br>STEL/LMPE-CT: 125 ppm<br>STEL/LMPE-CT: 545 mg/m <sup>3</sup>  |
| Crystalline silica (cristobalite)<br>14464-46-1 | TWA/LMPE-PPT: 0.05 mg/m <sup>3</sup> (respirable fraction)  |
| Naphthalene (constituent)<br>91-20-3            | TWA/LMPE-PPT: 10 ppm<br>TWA/LMPE-PPT: 50 mg/m <sup>3</sup><br>STEL/LMPE-CT: 15 ppm<br>STEL/LMPE-CT: 75 mg/m <sup>3</sup>      |

### Appropriate engineering controls

#### Engineering Measures

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.

**Individual protection measures, such as personal protective equipment**

|                                       |  |
|---------------------------------------|--|
| <b>Eye/face Protection</b>            | Wear safety glasses with side shields (or goggles). If splashes are likely to occur. Wear suitable face shield. Ensure that eyewash stations and safety showers are close to the workstation location.   |
| <b>Skin Protection</b>                | Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.   |
| <b>Respiratory Protection</b>         | If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.   |
| <b>General Hygiene Considerations</b> | Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended. |

**9. PHYSICAL AND CHEMICAL PROPERTIES****Information on basic physical and chemical properties**

|                       |                |                       |                          |
|-----------------------|----------------|-----------------------|--------------------------|
| <b>Physical State</b> | Liquid         | <b>Appearance</b>     | Colored Liquid           |
| <b>Odor</b>           | Characteristic | <b>Odor Threshold</b> | No information available |

| <u>Property</u>                        | <u>Values</u>     | <u>Remarks • Method</u> |
|--|-------------------|-------------------------|
| pH                                     |                   | No data available       |
| Melting point/freezing point           |                   | No data available       |
| Boiling point/Boiling Range            | > 149 °C / 300 °F |                         |
| Flash Point                            | 46 °C / 115 °F    | Setaflash closed cup    |
| Evaporation rate                       |                   | No data available       |
| Flammability Limit in Air              |                   |                         |
| Upper flammability limit               |                   | No data available       |
| Lower flammability limit               |                   | No data available       |
| Vapor Pressure                         |                   | No data available       |
| Vapor Density                          |                   | No data available       |
| Specific Gravity                       | 1.2               |                         |
| Water Solubility                       |                   | No data available       |
| Solubility in other solvents           |                   | No data available       |
| Partition coefficient: n-octanol/water |                   | No data available       |
| Autoignition Temperature               |                   | No data available       |
| Decomposition temperature              |                   | No data available       |
| Kinematic viscosity                    |                   | No data available       |
| Dynamic viscosity                      |                   | No data available       |

|                             |                   |
|-----------------------------|-------------------|
| <b>Explosive Properties</b> | No data available |
| <b>Oxidizing Properties</b> | No data available |

**Other Information**

|                                    |    |
|------------------------------------|----|
| <b>Photochemically Reactive</b>    | No |
| <b>Weight Per Gallon (lbs/gal)</b> | 10 |

| VOC by weight %<br>(less water) | VOC by volume %<br>(less water) | VOC lbs/gal<br>(less water) | VOC grams/liter<br>(less water) |
|---------------------------------|---------------------------------|-----------------------------|---------------------------------|
| 30.2                            | No information available        | 3.02                        | 361.68                          |

**10. STABILITY AND REACTIVITY****Reactivity**

No information available.

**Chemical stability**

Stable under normal conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Keep away from open flames, hot surfaces and sources of ignition.

**Incompatible materials**

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

**Hazardous Decomposition Products**

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO<sub>2</sub>). Carbon monoxide.

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure**

|                     |                                    |
|---------------------|------------------------------------|
| <b>Inhalation</b>   | There is no data for this product. |
| <b>Eye Contact</b>  | There is no data for this product. |
| <b>Skin Contact</b> | There is no data for this product. |
| <b>Ingestion</b>    | There is no data for this product. |

| Component   | Oral LD50            |
|---|----------------------|
| Titanium dioxide<br>13463-67-7                              | >10000 mg/kg ( Rat ) |
| Solvent naphtha (petroleum), medium aliphatic<br>64742-88-7 | >5000 mg/kg ( Rat )  |
| Naphtha (petroleum), heavy aromatic<br>64742-94-5           | >5000 mg/kg ( Rat )  |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7                   | 4300 mg/kg ( Rat )   |
| Ethyl benzene (constituent)<br>100-41-4                     | 3500 mg/kg ( Rat )   |
| Naphthalene (constituent)<br>91-20-3                        | 490 mg/kg ( Rat )    |

| Component   | LD50 Dermal                                |
|---|--|
| Solvent naphtha (petroleum), medium aliphatic<br>64742-88-7 | 3000 mg/kg ( Rabbit )                      |
| Naphtha (petroleum), heavy aromatic<br>64742-94-5           | >2000 mg/kg ( Rabbit )                     |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7                   | >1700 mg/kg ( Rabbit )                     |
| Ethyl benzene (constituent)<br>100-41-4                     | 15354 mg/kg ( Rabbit )                     |
| Naphthalene (constituent)<br>91-20-3                        | >2500 mg/kg ( Rat )<br>>20 g/kg ( Rabbit ) |

| Component   | Inhalation LC50                                |
|---|--|
| Solvent naphtha (petroleum), medium aliphatic<br>64742-88-7 | >5.28 mg/L ( Rat ) 4 h                         |
| Naphtha (petroleum), heavy aromatic<br>64742-94-5           | >590 mg/m <sup>3</sup> ( Rat ) 4 h             |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7                   | 5000 ppm ( Rat ) 4 h<br>47635 mg/L ( Rat ) 4 h |
| Ethyl benzene (constituent)<br>100-41-4                     | 17.2 mg/L ( Rat ) 4 h                          |
| Naphthalene (constituent)<br>91-20-3                        | >340 mg/m <sup>3</sup> ( Rat ) 1 h             |

**Information on toxicological effects**

**Symptoms** There is no data for this product.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

|                                  |  |
|----------------------------------|--|
| <b>Skin corrosion/irritation</b> | There is no data for this product.   |
| <b>Eye damage/irritation</b>     | There is no data for this product.   |
| <b>Irritation</b>                | There is no data for this product.   |
| <b>Corrosivity</b>               | There is no data for this product.   |
| <b>Sensitisation</b>             | There is no data for this product.   |
| <b>Mutagenic Effects</b>         | There is no data for this product.   |
| <b>Reproductive Effects</b>      | There is no data for this product.   |
| <b>STOT - single exposure</b>    | There is no data for this product.   |
| <b>STOT - repeated exposure</b>  | There is no data for this product.   |
| <b>Chronic Toxicity</b>          | There is no data for this product.   |
| <b>Aspiration hazard</b>         | There is no data for this product.   |
| <b>Carcinogenicity</b>           | The table below indicates whether each agency has listed any ingredient as a carcinogen. |

| Component                               | ACGIH |
|---|-------|
| Ethyl benzene (constituent)<br>100-41-4 | A3    |

| Component                                       | IARC     |
|---|----------|
| Titanium dioxide<br>13463-67-7                  | Group 2B |
| Ethyl benzene (constituent)<br>100-41-4         | Group 2B |
| Crystalline silica (cristobalite)<br>14464-46-1 | Group 1  |
| Naphthalene (constituent)<br>91-20-3            | Group 2B |
| Cobalt Compounds                                | Group 2B |

| Component                            | NTP                    |
|--------------------------------------|------------------------|
| Naphthalene (constituent)<br>91-20-3 | Reasonably Anticipated |

| Component                                       | OSHA |
|---|------|
| Titanium dioxide<br>13463-67-7                  | X    |
| Ethyl benzene (constituent)<br>100-41-4         | X    |
| Crystalline silica (cristobalite)<br>14464-46-1 | X    |
| Naphthalene (constituent)<br>91-20-3            | X    |
| Cobalt Compounds                                | X    |

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document

|                                      |                 |
|--------------------------------------|-----------------|
| <b>ATEmix (oral)</b>                 | 58,748.00 mg/kg |
| <b>ATEmix (dermal)</b>               | 36,768.00 mg/kg |
| <b>ATEmix (inhalation-dust/mist)</b> | 72.20 mg/l      |
| <b>ATEmix (inhalation-vapor)</b>     | 917.00 mg/l     |

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

None known

0% of the mixture consists of components(s) of unknown hazards to the aquatic environment

| Component                                     | Algae/aquatic plants                               |
|---|--|
| Solvent naphtha (petroleum), medium aliphatic | 96h EC50 Pseudokirchneriella subcapitata: 450 mg/L |

|   |  |
|---|--|
| 64742-88-7                              |  |
| Ethyl benzene (constituent)<br>100-41-4 | 96h EC50 Pseudokirchneriella subcapitata: 1.7 - 7.6 mg/L [static]<br>72h EC50 Pseudokirchneriella subcapitata: 2.6 - 11.3 mg/L [static]<br>72h EC50 Pseudokirchneriella subcapitata: 4.6 mg/L<br>96h EC50 Pseudokirchneriella subcapitata: >438 mg/L |
| Naphthalene (constituent)<br>91-20-3    | 72h EC50 Skeletonema costatum: 0.4 mg/L  |

| Component   | Fish  |
|---|---|
| Solvent naphtha (petroleum), medium aliphatic<br>64742-88-7 | 96h LC50 Pimephales promelas: 800 mg/L [static]   |
| Ethyl benzene (constituent)<br>100-41-4                     | 96h LC50 Oncorhynchus mykiss: 11.0 - 18.0 mg/L [static]<br>96h LC50 Pimephales promelas: 7.55 - 11 mg/L [flow-through]<br>96h LC50 Pimephales promelas: 9.1 - 15.6 mg/L [static]<br>96h LC50 Lepomis macrochirus: 32 mg/L [static]<br>96h LC50 Oncorhynchus mykiss: 4.2 mg/L [semi-static]<br>96h LC50 Poecilia reticulata: 9.6 mg/L [static] |
| Naphthalene (constituent)<br>91-20-3                        | 96h LC50 Oncorhynchus mykiss: 0.91 - 2.82 mg/L [static]<br>96h LC50 Pimephales promelas: 5.74 - 6.44 mg/L [flow-through]<br>96h LC50 Oncorhynchus mykiss: 1.6 mg/L [flow-through]<br>96h LC50 Pimephales promelas: 1.99 mg/L [static]<br>96h LC50 Lepomis macrochirus: 31.0265 mg/L [static]  |

| Component   | Crustacea   |
|---|---|
| Solvent naphtha (petroleum), medium aliphatic<br>64742-88-7 | 48h EC50 Daphnia magna: >100 mg/L   |
| Ethyl benzene (constituent)<br>100-41-4                     | 48h EC50 Daphnia magna: 1.8 - 2.4 mg/L  |
| Naphthalene (constituent)<br>91-20-3                        | 48h EC50 Daphnia magna: 1.09 - 3.4 mg/L [static]<br>48h EC50 Daphnia magna: 1.96 mg/L [Flow through]<br>48h LC50 Daphnia magna: 2.16 mg/L |

**Persistence and Degradability**

No information available.

**Bioaccumulation**

No information available.

| Component   | Partition coefficient |
|---|-----------------------|
| Naphtha (petroleum), heavy aromatic<br>64742-94-5 | 4.5                   |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7         | 2.96                  |
| Ethyl benzene (constituent)<br>100-41-4           | 3.118                 |
| Naphthalene (constituent)<br>91-20-3              | 3.3                   |

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods****Waste Disposal Methods**

Contain and dispose of waste according to local regulations.

**Contaminated Packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

**14. TRANSPORT INFORMATION****DOT**

In the U.S. and Canada, this material may be reclassified as a combustible liquid and is not



regulated, via surface transportation, in containers less than 119 gallons or 450 liters [per 49 CFR 173.150 (f)] [per Transportation of Dangerous Goods Regulations/Clear Language Part 1.33].

**UN/ID no.** UN1210  
**Proper Shipping Name** Printing Ink  
**Hazard Class** 3  
**Packing Group** III

**ICAO / IATA / IMDG / IMO**

**UN/ID no.** UN1210  
**Proper Shipping Name** Printing Ink  
**Hazard Class** 3  
**Packing Group** III

**15. REGULATORY INFORMATION****International Inventories**

All components are listed on the TSCA Inventory. For further information, please contact: Supplier (manufacturer/importer/downstream user/distributor).

**U.S. Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

| Component                    | CAS-No    | Weight % | SARA 313 - Threshold Values |
|------------------------------|-----------|----------|-----------------------------|
| Xylenes (o-, m-, p- isomers) | 1330-20-7 | 1 - 5    | 1.0                         |
| Ethyl benzene (constituent)  | 100-41-4  | < 0.5    | 0.1                         |
| Naphthalene (constituent)    | 91-20-3   | < 0.5    | 0.1                         |

**Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)**

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:

| Component                    | CAS-No    | Weight % |
|------------------------------|-----------|----------|
| Xylenes (o-, m-, p- isomers) | 1330-20-7 | 1 - 5    |

**U.S. State Regulations**

| Component                                       | Massachusetts Right To Know |
|---|-----------------------------|
| Stoddard solvent<br>8052-41-3                   | X                           |
| Barium sulfate<br>7727-43-7                     | X                           |
| Titanium dioxide<br>13463-67-7                  | X                           |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7       | X                           |
| Ethyl benzene (constituent)<br>100-41-4         | X                           |
| Crystalline silica (cristobalite)<br>14464-46-1 | X                           |
| Naphthalene (constituent)<br>91-20-3            | X                           |

| Component                      | Minnesota Right To Know |
|--------------------------------|-------------------------|
| Stoddard solvent<br>8052-41-3  | X                       |
| Barium sulfate<br>7727-43-7    | X                       |
| Titanium dioxide<br>13463-67-7 | X                       |

|   |   |
|---|---|
| Xylenes (o-, m-, p- isomers)<br>1330-20-7       | X |
| Ethyl benzene (constituent)<br>100-41-4         | X |
| Crystalline silica (cristobalite)<br>14464-46-1 | X |
| Naphthalene (constituent)<br>91-20-3            | X |

| Component   | New Jersey<br>Right To Know |
|---|-----------------------------|
| Stoddard solvent<br>8052-41-3                               | X                           |
| Barium sulfate<br>7727-43-7                                 | X                           |
| Titanium dioxide<br>13463-67-7                              | X                           |
| Solvent naphtha (petroleum), medium aliphatic<br>64742-88-7 | X                           |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7                   | X                           |
| Ethyl benzene (constituent)<br>100-41-4                     | X                           |
| Crystalline silica (cristobalite)<br>14464-46-1             | X                           |
| Naphthalene (constituent)<br>91-20-3                        | X                           |
| Cobalt Compounds  | X                           |

| Component                                       | Pennsylvania<br>Right To Know |
|---|-------------------------------|
| Stoddard solvent<br>8052-41-3                   | X                             |
| Barium sulfate<br>7727-43-7                     | X                             |
| Titanium dioxide<br>13463-67-7                  | X                             |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7       | X                             |
| Ethyl benzene (constituent)<br>100-41-4         | X                             |
| Crystalline silica (cristobalite)<br>14464-46-1 | X                             |
| Naphthalene (constituent)<br>91-20-3            | X                             |
| Cobalt Compounds                                | X                             |

**California Prop. 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

| Component                   | California Prop. 65 |
|-----------------------------|---------------------|
| Titanium dioxide            | Carcinogen          |
| Ethyl benzene (constituent) | Carcinogen          |
| Naphthalene (constituent)   | Carcinogen          |

*This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product*

**Canada**

| Component   | NPRI - National Pollutant Release Inventory  |
|---|--|
| Stoddard solvent<br>8052-41-3                               | Part 5, Other Groups and Mixtures  |
| Solvent naphtha (petroleum), medium aliphatic<br>64742-88-7 | Part 5, Other Groups and Mixtures  |
| Naphtha (petroleum), heavy aromatic<br>64742-94-5           | Part 5, Other Groups and Mixtures Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the |

|   |   |
|---|---|
|   | Canadian Environmental Protection Act, 1999   |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7 | Part 1, Group A Substance total of all isomers of Xylene, including m-Xylene, CAS No. 108-38-3, o-Xylene, CAS No. 95-47-6, and p-Xylene, CAS No. 106-42-3<br>Part 5, Isomer Groups total of all isomers of Xylene, including m-Xylene, CAS No. 108-38-3, o-Xylene, CAS No. 95-47-6, and p-Xylene, CAS No. 106-42-3 Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999 |
| Ethyl benzene (constituent)<br>100-41-4   | Part 1, Group A Substance Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999  |
| Naphthalene (constituent)<br>91-20-3      | Part 1, Group A Substance Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999  |
| Cobalt Compounds                          | Part 1, Group A Substance total of the pure element and the equivalent weight of the element contained in any compound, alloy or mixture  |

## 16. OTHER INFORMATION

|              |               |                     |                   |                            |
|--------------|---------------|---------------------|-------------------|----------------------------|
| <b>HMIS:</b> | <b>Health</b> | <b>Flammability</b> | <b>Reactivity</b> | <b>Personal Protection</b> |
|              | 1 *           | 2                   | 0                 | X                          |

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### **Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

|         |                                  |
|---------|----------------------------------|
| TWA     | TWA (time-weighted average)      |
| STEL    | STEL (Short Term Exposure Limit) |
| Ceiling | Maximum limit value              |

#### **ACGIH: (American Conference of Governmental Industrial Hygienists)**

- A1 - Known Human Carcinogen
- A2 - Suspected Human Carcinogen
- A3 - Animal Carcinogen

#### **IARC: (International Agency for Research on Cancer)**

- Group 1 - Carcinogenic to Humans
- Group 2A - Probably Carcinogenic to Humans
- Group 2B - Possibly Carcinogenic to Humans

#### **NTP: (National Toxicity Program)**

- Known - Known Carcinogen
- Reasonably Anticipated to be a Human Carcinogen

#### **OSHA: (Occupational Safety & Health Administration)**

- X - Present

**Revision Date** May-30-2015

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of MSDS**