

Published Date
May-15-2019

Revision Date
May-15-2019

Revision Number
2.5

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product code 51358
Product name Tinting White
Product category 5100 Series SV Screen Ink

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended use Printing operations

Details of the supplier of the safety data sheet

| | |
|-------------------------|----------------------------|
| UNITED STATES | UNITED KINGDOM |
| Nazdar Company | Nazdar Limited |
| 8501 Hedge Lane Terrace | Barton Road |
| Shawnee, KS 66227 | Heaton Mersey |
| Tel: +001-913-422-1888 | Stockport, England SK4 3EG |
| Tel: +001-800-677-4657 | Tel: +44 161 442 2111 |
| Fax: +001-913-422-2294 | |
| www.nazdar.com | |

Emergency telephone number

USA: Chemtrec: +001-800-424-9300
Outside USA: Chemtrec: +001-703-527-3887
24 Hour Emergency Phone Number

2. HAZARDS IDENTIFICATION

Classification

| | |
|-----------------------------------|----------------------|
| Skin Corrosion/irritation | Category 2 - (H315) |
| Serious eye damage/eye irritation | Category 1 - (H318) |
| Skin sensitization | Category 1 - (H317) |
| Carcinogenicity | Category 1B - (H350) |
| Flammable liquids | Category 3 - (H226) |

Label elements



Signal Word
Danger

Hazard Statements

H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H350 - May cause cancer

H226 - Flammable liquid and vapor

Precautionary Statements

P264 - Wash face, hands and any exposed skin thoroughly after handling

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention

P202 - Do not handle until all safety precautions have been read and understood

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P233 - Keep container tightly closed

P403 + P235 - Store in a well-ventilated place. Keep cool

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Hazards not otherwise classified (HNOC)

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

| Component | CAS-No | Weight % | Trade Secret | Note |
|-------------------------------------|--------------|----------|--------------|------|
| Titanium dioxide | 13463-67-7 | 30 - 60 | * | |
| Resin | Trade Secret | 10 - 30 | * | |
| Resin | Trade Secret | 10 - 30 | * | |
| 1-Butanol | 71-36-3 | 5 - 10 | * | |
| Dipropylene glycol monomethyl ether | 34590-94-8 | 5 - 10 | * | |
| Ethylene glycol monopropyl ether | 2807-30-9 | 5 - 10 | * | |
| 2-Butoxyethanol | 111-76-2 | 5 - 10 | * | |
| Phosphoric acid polyester | TRADE SECRET | 1 - 5 | * | |
| Formaldehyde | 50-00-0 | < 0.5 | * | |

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General Advice

Show this safety data sheet to the doctor in attendance.

Eye Contact

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.

Skin Contact

Wash off immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.

Inhalation

Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.

Ingestion

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Most important symptoms and effects, both acute and delayed

None under normal use conditions.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Foam. Carbon dioxide (CO₂). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

No information available.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions

Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling

Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Ensure adequate ventilation.

Conditions for safe storage, including any incompatibilities

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep container closed when not in use. Keep out of the reach of children.

Incompatible Products

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits

| Component | ACGIH TLV |
|---|---------------------------------------|
| Titanium dioxide 13463-67-7 | TWA: 10 mg/m ³ |
| 1-Butanol 71-36-3 | TWA: 20 ppm |
| Dipropylene glycol monomethyl ether 34590-94-8 | TWA: 100 ppm STEL: 150 ppm Skin |
| 2-Butoxyethanol 111-76-2 | TWA: 20 ppm |
| Formaldehyde 50-00-0 | TWA: 0.1 ppm STEL: 0.3 ppm |

| Component | OSHA PEL |
|---|--|
| Titanium dioxide 13463-67-7 | TWA: 15 mg/m ³ total dust |
| 1-Butanol 71-36-3 | TWA: 100 ppm TWA: 300 mg/m ³ |
| Dipropylene glycol monomethyl ether 34590-94-8 | TWA: 100 ppm TWA: 600 mg/m ³ Skin |
| 2-Butoxyethanol 111-76-2 | TWA: 50 ppm TWA: 240 mg/m ³ Skin |
| Formaldehyde 50-00-0 | TWA: 0.75 ppm STEL: 2 ppm |

| Component | OSHA PEL (vacated) |
|---|--|
| Titanium dioxide 13463-67-7 | TWA: 10 mg/m ³ total dust |
| 1-Butanol 71-36-3 | Ceiling: 50 ppm Ceiling: 150 mg/m ³ Skin |
| Dipropylene glycol monomethyl ether 34590-94-8 | TWA: 100 ppm TWA: 600 mg/m ³ STEL: 150 ppm STEL: 900 mg/m ³ Skin |
| 2-Butoxyethanol 111-76-2 | TWA: 25 ppm TWA: 120 mg/m ³ Skin |
| Formaldehyde 50-00-0 | Ceiling: 5 ppm TWA: 3 ppm STEL: 10 ppm |

| Component | Ontario TWAEV |
|---|---|
| Titanium dioxide 13463-67-7 | TWA: 10 mg/m ³ |
| 1-Butanol 71-36-3 | TWA: 20 ppm |
| Dipropylene glycol monomethyl ether 34590-94-8 | TWA: 100 ppm STEL: 150 ppm Skin |
| Ethylene glycol monopropyl ether 2807-30-9 | TWA: 25 ppm TWA: 110 mg/m ³ Skin |
| 2-Butoxyethanol 111-76-2 | TWA: 20 ppm |
| Formaldehyde 50-00-0 | STEL: 1 ppm Ceiling: 1.5 ppm |

| Component | Mexico OEL (TWA) |
|---|---|
| Titanium dioxide 13463-67-7 | TWA/VLE-PPT: 10 mg/m ³ STEL/PPT-CT: 20 mg/m ³ |
| 1-Butanol 71-36-3 | Ceiling: 50 ppm Ceiling: 150 mg/m ³ |
| Dipropylene glycol monomethyl ether 34590-94-8 | TWA/VLE-PPT: 100 ppm TWA/VLE-PPT: 60 mg/m ³ STEL/PPT-CT: 150 ppm STEL/PPT-CT: 900 mg/m ³ |
| 2-Butoxyethanol 111-76-2 | TWA/VLE-PPT: 26 ppm TWA/VLE-PPT: 120 mg/m ³ STEL/PPT-CT: 75 ppm STEL/PPT-CT: 360 mg/m ³ |
| Formaldehyde 50-00-0 | Ceiling: 2 ppm Ceiling: 3 mg/m ³ |

Appropriate engineering controls

Engineering Measures

Provide a good standard of general ventilation. Natural ventilation is from doors, windows

etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.

Individual protection measures, such as personal protective equipment

| | |
|---------------------------------------|--|
| Eye/Face Protection | Wear safety glasses with side shields (or goggles). If splashes are likely to occur. Wear suitable face shield. Ensure that eyewash stations and safety showers are close to the workstation location. |
| Skin Protection | Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. |
| Hand Protection | Chemical resistant protective gloves. Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding >480 minutes of permeation time): eg. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), polyvinylchloride (0.7 mm) and other Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers. Taking into account the varying conditions, the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing. Due to different glove types, the manufacturer's directions for use should be observed. Replace gloves immediately when torn or any change in appearance is noticed such as dimension, color, flexibility. |
| Respiratory Protection | If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material. |
| General Hygiene Considerations | Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended. |

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | | | |
|---|--------------------------|----------------------------------|--------------------------|
| Physical State | Liquid | Appearance | Colored |
| Odor | No information available | Odor Threshold | No information available |
| <u>Property</u> | <u>Values</u> | <u>Remarks • Method</u> | |
| pH | | No data available | |
| Melting Point / Freezing Point | | No data available | |
| Boiling Point / Boiling Range | > 149 °C / 300 °F | | |
| Flash Point | 39 °C / 102 °F | Pensky Martens Closed Cup (PMCC) | |
| Evaporation rate | | No data available | |
| Flammability Limit in Air | | | |
| Upper flammability limit | | No data available | |
| Lower flammability limit | | No data available | |
| Vapor Pressure | | No data available | |
| Vapor Density | | No data available | |
| Specific Gravity | 1.41 | | |
| Water Solubility | | No data available | |
| Solubility in other solvents | | No data available | |
| Partition coefficient: n-octanol/water | | No data available | |
| Autoignition Temperature | | No data available | |
| Decomposition temperature | | No data available | |
| Kinematic viscosity | | No data available | |
| Dynamic viscosity | | No data available | |
| Explosive Properties | No data available | | |

Oxidizing Properties No data available

Other Information

Photochemically Reactive No
Weight Per Gallon (lbs/gal) 11.73

| VOC by weight % (less water) | VOC by volume % (less water) | VOC lbs/gal (less water) | VOC grams/liter (less water) |
|---------------------------------|---------------------------------|-----------------------------|---------------------------------|
| 29.3 | No information available | 3.44 | 412.22 |

10. STABILITY AND REACTIVITY

Reactivity

No information available.

Chemical stability

Stable under normal conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO₂). Carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

| | |
|---------------------|---|
| Inhalation | Specific test data for the substance or mixture is not available. |
| Eye Contact | Specific test data for the substance or mixture is not available. |
| Skin Contact | Specific test data for the substance or mixture is not available. |
| Ingestion | Specific test data for the substance or mixture is not available. |

| Component | Oral LD50 |
|---|-----------------------|
| Titanium dioxide 13463-67-7 | > 10000 mg/kg (Rat) |
| 1-Butanol 71-36-3 | = 700 mg/kg (Rat) |
| Dipropylene glycol monomethyl ether 34590-94-8 | = 5.35 g/kg (Rat) |
| Ethylene glycol monopropyl ether 2807-30-9 | = 3089 mg/kg (Rat) |
| 2-Butoxyethanol 111-76-2 | = 470 mg/kg (Rat) |
| Formaldehyde 50-00-0 | = 100 mg/kg (Rat) |

| Component | Dermal LD50 |
|---|-------------------------|
| 1-Butanol 71-36-3 | = 3402 mg/kg (Rabbit) |
| Dipropylene glycol monomethyl ether 34590-94-8 | = 9500 mg/kg (Rabbit) |
| Ethylene glycol monopropyl ether 2807-30-9 | = 870 mg/kg (Rabbit) |
| 2-Butoxyethanol 111-76-2 | = 435 mg/kg (Rabbit) |
| Formaldehyde | = 270 mg/kg (Rabbit) |

| | |
|---|--|
| 50-00-0 | |
| Component | Inhalation LC50 |
| 1-Butanol 71-36-3 | > 8000 ppm (Rat) 4 h |
| Ethylene glycol monopropyl ether 2807-30-9 | = 1530 ppm (Rat) 7 h |
| 2-Butoxyethanol 111-76-2 | = 450 ppm (Rat) 4 h = 486 ppm (Rat) 4 h |
| Formaldehyde 50-00-0 | = 0.578 mg/L (Rat) 4 h |

Information on toxicological effects

Symptoms Specific test data for the substance or mixture is not available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Specific test data for the substance or mixture is not available. Causes skin irritation (pain, redness and swelling). (based on components).

Eye damage/irritation Specific test data for the substance or mixture is not available. Causes serious eye damage. (based on components).

Irritation Specific test data for the substance or mixture is not available.

Corrosivity Specific test data for the substance or mixture is not available.

Sensitization Specific test data for the substance or mixture is not available. May cause an allergic skin reaction. (based on components).

Mutagenic Effects Specific test data for the substance or mixture is not available.

Carcinogenic effects Specific test data for the substance or mixture is not available. May cause cancer. (based on components).

Reproductive Effects Specific test data for the substance or mixture is not available.

STOT - single exposure Specific test data for the substance or mixture is not available.

STOT - repeated exposure Specific test data for the substance or mixture is not available.

Chronic Toxicity Specific test data for the substance or mixture is not available.

Aspiration hazard Specific test data for the substance or mixture is not available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Component | ACGIH |
|-----------------------------|-------|
| 2-Butoxyethanol 111-76-2 | A3 |
| Formaldehyde 50-00-0 | A1 |

| Component | IARC |
|--------------------------------|----------|
| Titanium dioxide 13463-67-7 | Group 2B |
| Formaldehyde 50-00-0 | Group 1 |

| Component | NTP |
|-------------------------|-------|
| Formaldehyde 50-00-0 | Known |

| Component | OSHA |
|--------------------------------|------|
| Titanium dioxide 13463-67-7 | X |
| Formaldehyde 50-00-0 | X |

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 1.94 % of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 3,295.00 mg/kg

ATEmix (dermal) 9,894.00 mg/kg

ATEmix (inhalation-dust/mist) 26.50 mg/l
 ATEmix (inhalation-vapor) 190.00 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Specific test data for the substance or mixture is not available.

1.94 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

| Component | Algae/aquatic plants |
|----------------------|--|
| 1-Butanol 71-36-3 | 96h EC50 Desmodesmus subspicatus: > 500 mg/L 72h EC50 Desmodesmus subspicatus: > 500 mg/L |

| Component | Fish |
|---|--|
| 1-Butanol 71-36-3 | 96h LC50 Pimephales promelas: 1730 - 1910 mg/L (static) 96h LC50 Pimephales promelas: = 1740 mg/L (flow-through) 96h LC50 Lepomis macrochirus: 100000 - 500000 µg/L (static) 96h LC50 Pimephales promelas: = 1910000 µg/L (static) |
| Dipropylene glycol monomethyl ether 34590-94-8 | 96h LC50 Pimephales promelas: > 10000 mg/L (static) |
| 2-Butoxyethanol 111-76-2 | 96h LC50 Lepomis macrochirus: = 2950 mg/L 96h LC50 Lepomis macrochirus: = 1490 mg/L (static) |
| Formaldehyde 50-00-0 | 96h LC50 Oncorhynchus mykiss: 0.032 - 0.226 mL/L (flow-through) 96h LC50 Lepomis macrochirus: = 1510 µg/L (static) 96h LC50 Brachydanio rerio: = 41 mg/L (static) 96h LC50 Pimephales promelas: 22.6 - 25.7 mg/L (flow-through) 96h LC50 Pimephales promelas: 23.2 - 29.7 mg/L (static) 96h LC50 Oncorhynchus mykiss: 100 - 136 mg/L (static) |

| Component | Crustacea |
|---|--|
| 1-Butanol 71-36-3 | 48h EC50 Daphnia magna: 1897 - 2072 mg/L Static 48h EC50 Daphnia magna: = 1983 mg/L |
| Dipropylene glycol monomethyl ether 34590-94-8 | 48h LC50 Daphnia magna: = 1919 mg/L |
| 2-Butoxyethanol 111-76-2 | 48h EC50 Daphnia magna: > 1000 mg/L |
| Formaldehyde 50-00-0 | 48h LC50 Daphnia magna: = 2 mg/L 48h EC50 Daphnia magna: 11.3 - 18 mg/L Static |

Persistence and Degradability

No information available.

Bioaccumulation

No information available

| Component | Partition coefficient |
|---|-----------------------|
| 1-Butanol 71-36-3 | 0.785 |
| Dipropylene glycol monomethyl ether 34590-94-8 | -0.064 |
| 2-Butoxyethanol 111-76-2 | 0.81 |
| Formaldehyde 50-00-0 | 0.35 |

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

| | |
|-------------------------------|--|
| Waste Disposal Methods | Contain and dispose of waste according to local regulations. |
| Contaminated Packaging | Empty containers should be taken to an approved waste handling site for recycling or disposal. |

14. TRANSPORT INFORMATION

Note: This information is not intended to convey all specific transportation requirements relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation information can be found in the specific regulations for your mode of transportation. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

DOT In the U.S. and Canada, this material may be reclassified as a combustible liquid and is not regulated, via surface transportation, in containers less than 119 gallons or 450 liters [per 49 CFR 173.150 (f)] [per Transportation of Dangerous Goods Regulations/Clear Language Part 1.33].

| | |
|-----------------------------|--------------|
| UN/ID no. | UN1210 |
| Proper Shipping Name | Printing Ink |
| Hazard Class | 3 |
| Packing Group | III |

ICAO / IATA / IMDG / IMO

| | |
|-----------------------------|--------------|
| UN/ID no. | UN1210 |
| Proper Shipping Name | Printing Ink |
| Hazard Class | 3 |
| Packing Group | III |

15. REGULATORY INFORMATION

International Inventories

All components are listed on the TSCA Inventory. For further information, please contact: Supplier (manufacturer/importer/downstream user/distributor).

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

| Component | CAS-No | Weight % | SARA 313 - Threshold Values |
|----------------------------------|-----------|----------|-----------------------------|
| 1-Butanol | 71-36-3 | 5 - 10 | 1.0 |
| Ethylene glycol monopropyl ether | 2807-30-9 | 5 - 10 | 1.0 |
| 2-Butoxyethanol | 111-76-2 | 5 - 10 | 1.0 |
| Formaldehyde | 50-00-0 | < 0.5 | 0.1 |

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:

| Component | CAS-No | Weight % |
|----------------------------------|-----------|----------|
| Ethylene glycol monopropyl ether | 2807-30-9 | 5 - 10 |
| Formaldehyde | 50-00-0 | < 0.5 |

U.S. State Regulations

| Component | Massachusetts Right To Know |
|------------------|-----------------------------|
| Titanium dioxide | X |

| | |
|---|---|
| 13463-67-7 | |
| 1-Butanol 71-36-3 | X |
| Dipropylene glycol monomethyl ether 34590-94-8 | X |
| 2-Butoxyethanol 111-76-2 | X |
| Formaldehyde 50-00-0 | X |

| Component | Minnesota Right To Know |
|---|----------------------------|
| Titanium dioxide 13463-67-7 | X |
| 1-Butanol 71-36-3 | X |
| Dipropylene glycol monomethyl ether 34590-94-8 | X |
| 2-Butoxyethanol 111-76-2 | X |
| Formaldehyde 50-00-0 | X |

| Component | New Jersey Right To Know |
|---|-----------------------------|
| Titanium dioxide 13463-67-7 | X |
| 1-Butanol 71-36-3 | X |
| Dipropylene glycol monomethyl ether 34590-94-8 | X |
| Ethylene glycol monopropyl ether 2807-30-9 | X |
| 2-Butoxyethanol 111-76-2 | X |
| Formaldehyde 50-00-0 | X |

| Component | Pennsylvania Right To Know |
|---|-------------------------------|
| Titanium dioxide 13463-67-7 | X |
| 1-Butanol 71-36-3 | X |
| Dipropylene glycol monomethyl ether 34590-94-8 | X |
| Ethylene glycol monopropyl ether 2807-30-9 | X |
| 2-Butoxyethanol 111-76-2 | X |
| Formaldehyde 50-00-0 | X |

California Prop. 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

| Component | California Prop. 65 |
|------------------|---------------------|
| Titanium dioxide | Carcinogen |
| Formaldehyde | Carcinogen |

- This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

Canada

| Component | NPRI - National Pollutant Release Inventory |
|-------------------------------------|---|
| 1-Butanol 71-36-3 | Part 1, Group A Substance; Part 4 Substance |
| Dipropylene glycol monomethyl ether | Part 5, Other Groups and Mixtures; Part 4 Substance |

| | |
|---|---|
| 34590-94-8 | |
| Ethylene glycol monopropyl ether 2807-30-9 | Part 5, Other Groups and Mixtures; Part 4 Substance |
| 2-Butoxyethanol 111-76-2 | Part 5, Individual Substances; Part 4 Substance |
| Formaldehyde 50-00-0 | Part 5, Individual Substances; Part 4 Substance |

16. OTHER INFORMATION

| | | | | |
|--------------|---------------|---------------------|-------------------|----------------------------|
| HMIS: | Health | Flammability | Reactivity | Personal Protection |
| | 2 * | 2 | 0 | X |

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

| | |
|---------|----------------------------------|
| TWA | TWA (time-weighted average) |
| STEL | STEL (Short Term Exposure Limit) |
| Ceiling | Maximum limit value |

ACGIH: (American Conference of Governmental Industrial Hygienists)

- A1 - Known Human Carcinogen
- A2 - Suspected Human Carcinogen
- A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

- Group 1 - Carcinogenic to Humans
- Group 2A - Probably Carcinogenic to Humans
- Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

- Known - Known Carcinogen
- Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

- X - Present

Revision Date May-15-2019

Pursuant to NOM-018-STPS-2015

This information within is considered correct but is not exhaustive and will be used for guidance only, which is based on the current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet