

SAFETY DATA SHEET

Published Date Jan-25-2023 Revision Date Jan-25-2023 Revision Number 2.6

1. IDENTIFICATION

<u>Product identifier</u> Product code Product name Product category	GVLF124 Orange GV Series SV Vinyl Screen Ink
Other means of identification Synonyms	None
Recommended use of the chemica	al and restrictions on use
Recommended use	Industrial Printing Operations
Details of the supplier of the safet	y data sheet
UNITED STATES	UNITED KINGDOM
Nazdar Company	Nazdar Limited
8501 Hedge Lane Terrace	Barton Road
Shawnee, KS 66227	Heaton Mersey
Tel: +001-913-422-1888	Stockport, England SK4 3EG

Emergency telephone number

Tel: +001-800-677-4657 Fax: +001-913-422-2294 www.nazdar.com

USA: Chemtrec: +001-800-424-9300 Outside USA: Chemtrec: +001-703-527-3887 24 Hour Emergency Phone Number

2. HAZARDS IDENTIFICATION

Tel: +44 161 442 2111

Classification

Serious eye damage/eye irritation	Category 2 - (H319)
Carcinogenicity	Category 2 - (H351)
Specific target organ toxicity (single exposure)	Category 3 - (H335)
Aspiration hazard	Category 1 - (H304)
Chronic aquatic toxicity	Category 3 - (H412)

Label elements



Danger

Hazard statements

H304 - May be fatal if swallowed and enters airways

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

H351 - Suspected of causing cancer

H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements

P201 - Obtain special instructions before use
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor

P331 - Do NOT induce vomiting

Hazards not otherwise classified (HNOC)

Harmful to aquatic life.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical name	CAS No	Weight-%	Trade secret	Note
Isophorone	78-59-1	30 - 60	*	
Solvent naphtha, petroleum, heavy aromatic	64742-94-5	10 - 30	*	
Ethyl 3-ethoxypropionate	763-69-9	5 - 10	*	
Solvent naphtha, petroleum, light aromatic	64742-95-6	1 - 5	*	
1,2,4-Trimethylbenzene (constituent)	95-63-6	0.1 - < 1	*	1
Naphthalene (constituent)	91-20-3	0.1 - < 1	*	1
1,3,5-Trimethylbenzene (constituent)	108-67-8	0.1 - < 1	*	1
Cumene (constituent)	98-82-8	0.1 - < 1	*	1

*The exact percentage (concentration) of composition has been withheld as a trade secret.

Note

1. Hazardous Constituent contained in Complex Substance(s) required for disclosure

4. FIRST-AID MEASURES

Description of first aid measures

General Advice Eye Contact	Show this safety data sheet to the doctor in attendance. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.
Skin Contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.
Inhalation	If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately. Remove person to fresh air and keep comfortable for breathing.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Most important symptoms and effects, both acute and delayed None under normal use conditions.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water spray. Carbon dioxide (CO2). Foam. Dry chemical. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

No information available.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Sealed containers may rupture when heated. Cool containers / tanks with water spray.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions

Evacuate personnel to safe areas. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Avoid contact with eyes, skin and clothing. Ventilate the area. Avoid breathing dust or vapor.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained. Keep out of drains, sewers, ditches and waterways.

Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling	Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Use personal protective equipment as required.	
Conditions for safe storage, including any incompatibilities		
Storage	Keep away from open flames, hot surfaces and sources of ignition. Keep out of the reach of children. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep container closed when not in use.	
Incompatible Products	Strong oxidizing agents. Strong acids. Strong bases. Reducing agent.	
8. EXPOSURE CONTROLS/PERSONAL PROTECTION		

Control parameters

Exposure limits

Chemical name	ACGIH TLV	
Isophorone	Ceiling: 5 ppm	
78-59-1		
1,2,4-Trimethylbenzene (constituent)	TWA: 10 ppm	
95-63-6		
Naphthalene (constituent)	TWA: 10 ppm	
91-20-3	Skin	
1,3,5-Trimethylbenzene (constituent)	TWA: 10 ppm	
108-67-8		
Cumene (constituent)	TWA: 5 ppm	
98-82-8		

Chemical name	OSHA PEL
Isophorone	TWA: 25 ppm
78-59-1	TWA: 140 mg/m ³
Naphthalene (constituent)	TWA: 10 ppm

91-20-3	TWA: 50 mg/m ³
Cumene (constituent)	TWA: 50 ppm
98-82-8	TWA: 245 mg/m ³
	Skin

Chemical name	OSHA PEL (vacated)	
Isophorone	TWA: 4 ppm	
78-59-1	TWA: 23 mg/m ³	
Naphthalene (constituent)	TWA: 10 ppm	
91-20-3	TWA: 50 mg/m ³	
	STEL: 15 ppm	
	STEL: 75 mg/m ³	
Cumene (constituent)	TWA: 50 ppm	
98-82-8	TWA: 245 mg/m ³	
	Skin	

Chemical name	Ontario TWAEV
Isophorone	Ceiling: 5 ppm
78-59-1	
Ethyl 3-ethoxypropionate	TWA: 50 ppm
763-69-9	TWA: 300 mg/m ³
Naphthalene (constituent)	TWA: 10 ppm
91-20-3	Skin
Cumene (constituent)	TWA: 50 ppm
98-82-8	

Chemical name	Mexico OEL (TWA)
Isophorone	Ceiling: 5 ppm
78-59-1	
Naphthalene (constituent)	TWA/VLE-PPT: 10 ppm
91-20-3	STEL/PPT-CT: 15 ppm
Cumene (constituent)	TWA/VLE-PPT: 50 ppm
98-82-8	

Appropriate engineering controls

Engineering Measures In case of insufficient ventilation, wear suitable respiratory equipment. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values.

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Wear safety glasses with side shields (or goggles). Ensure that eyewash stations and safety showers are close to the workstation location. If splashes are likely to occur:. Wear suitable face shield.
Skin Protection	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
Hand Protection	Chemical resistant protective gloves. Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding >480 minutes of permeation time): eg. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), polyvinylchloride (0.7 mm) and other Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers. Taking into account the varying conditions, the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing. Due to different glove types, the manufacturer's directions for use should be observed. Replace gloves immediately when torn or any change in appearance is noticed such as dimension, color, flexibility.
Respiratory Protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. Selection of air-purifying or positive-pressure

supplied-air will depend on the specific operation and the potential airborne concentration of the material.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and o Physical state Odor	c hemical properties Liquid Characteristic	Appearance Odor Threshold	Colored No information available
<u>Property</u> pH	<u>Values</u>	Remarks • Method No data available	
рп Melting Point / Freezing Point Boiling Point / Boiling Range	No information available > 149 °C / 300 °F	No data available	
Flash Point	66 °C / 150 °F	Setaflash closed cup	
Evaporation rate Flammability Limit in Air		No data available	
Upper flammability limit		No data available	
Lower flammability limit		No data available	
Vapor Pressure		No data available	
Vapor Density	4.05	No data available	
Specific Gravity	1.05	No data available	
Water Solubility Solubility in other solvents		No data available	
Partition coefficient: n-octanol/wate	r	No data available	
Autoignition Temperature	No information available	No data available	
Hyphen		No data available	
Kinematic viscosity		No data available	
Dynamic viscosity		No data available	
Explosive Properties	No data available		
Oxidizing Properties	No data available		
Other information			
Photochemically Reactive Weight Per Gallon (Ibs/gal)	Yes 8.75		
VOC by weight %	VOC by volume %	VOC lbs/gal	VOC grams/liter
(less water)	(less water)	(less water)	(less water)
63.05	65.58	5.52	661.86

10. STABILITY AND REACTIVITY

Reactivity

No information available.

Chemical stability

Stable under normal conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases. Reducing agent.

<u>Hazardous decomposition products</u> Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide. Carbon dioxide (CO2).

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	Specific test data for the substance or mixture is not available.
Eye Contact	Specific test data for the substance or mixture is not available.
Skin Contact	Specific test data for the substance or mixture is not available.
Ingestion	Specific test data for the substance or mixture is not available.

Chemical name	Oral LD50
Isophorone 78-59-1	= 1870 mg/kg (Rat)
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	> 5000 mg/kg (Rat)
Ethyl 3-ethoxypropionate 763-69-9	= 5 g/kg (Rat)
Solvent naphtha, petroleum, light aromatic 64742-95-6	= 8400 mg/kg (Rat)
1,2,4-Trimethylbenzene (constituent) 95-63-6	= 3280 mg/kg (Rat)
Naphthalene (constituent) 91-20-3	= 1110 mg/kg (Rat)
Cumene (constituent) 98-82-8	= 1400 mg/kg (Rat)

Chemical name	Dermal LD50	
Isophorone 78-59-1	= 1700 mg/kg (Rat)	
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	> 2000 mg/kg (Rabbit)	
Ethyl 3-ethoxypropionate 763-69-9	> 9500 mg/kg (Rabbit)	
Solvent naphtha, petroleum, light aromatic 64742-95-6	> 2000 mg/kg (Rabbit)	
1,2,4-Trimethylbenzene (constituent) 95-63-6	> 3160 mg/kg (Rabbit)	
Naphthalene (constituent) 91-20-3	= 1120 mg/kg (Rabbit)	
Cumene (constituent) 98-82-8	= 12300 μL/kg (Rabbit)	

Chemical name	Inhalation LC50	
Isophorone	= 7 mg/L (Rat)4 h	
78-59-1		
Solvent naphtha, petroleum, heavy aromatic	> 590 mg/m³ (Rat)4 h	
64742-94-5		
Ethyl 3-ethoxypropionate	> 5.96 mg/L (Rat)6 h	
763-69-9		
Solvent naphtha, petroleum, light aromatic	= 3400 ppm (Rat)4 h	
64742-95-6		
1,2,4-Trimethylbenzene (constituent)	= 18 g/m³ (Rat)4 h	
95-63-6		
Naphthalene (constituent)	> 0.4 mg/L (Rat)4 h	
91-20-3		
1,3,5-Trimethylbenzene (constituent)	= 24 g/m³ (Rat)4 h	
108-67-8		
Cumene (constituent)	> 3577 ppm (Rat)6 h	
98-82-8		

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	Specific test data for the substance or mixture is not available.
Delayed and immediate effects	as well as chronic effects from short and long-term exposure
Skin corrosion/irritation	Specific test data for the substance or mixture is not available.
Eye damage/irritation	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components).
Irritation	Specific test data for the substance or mixture is not available.
Corrosivity	Specific test data for the substance or mixture is not available.
Sensitization	Specific test data for the substance or mixture is not available.
Mutagenic Effects	Specific test data for the substance or mixture is not available.
Carcinogenic effects	Specific test data for the substance or mixture is not available. Suspected of causing cancer. (based on components).
Reproductive Effects	Specific test data for the substance or mixture is not available.
STOT - single exposure	Specific test data for the substance or mixture is not available. May cause respiratory irritation. (based on components).
STOT - repeated exposure	Specific test data for the substance or mixture is not available.
Chronic Toxicity	Specific test data for the substance or mixture is not available
Aspiration hazard	Specific test data for the substance or mixture is not available. May be fatal if swallowed and enters airways. (based on components).
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen

Carcinogenicity	The table below indicates wheth	The table below indicates whether each agency has listed any ingredient as a carcinogen.	
Chemical name		ACGIH	
Isophorone		A3	
78-59-1			
Naphthalene (constituent)		A3	
91-20-3			
Cumene (constituent)		A3	
98-82-8			

Chemical name	IARC
	Group 2B
91-20-3	
Cumene (constituent)	Group 2B
98-82-8	

Chemical name	NTP
Naphthalene (constituent) 91-20-3	Reasonably Anticipated
Cumene (constituent) 98-82-8	Reasonably Anticipated

Chemical name	OSHA
Isophorone	X
78-59-1	
Naphthalene (constituent)	X
91-20-3	
Cumene (constituent)	X
98-82-8	

Numerical measures of toxicity - Product Information

Unknown acute toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document 4,482.20 mg/kg ATEmix (oral) ATEmix (dermal) 4,074.70 mg/kg mg/l

12. ECOLOGICAL INFORMATION

<u>Ecotoxicity</u> Specific test data for the substance or mixture is not available. Harmful to aquatic life with long lasting effects. (based on components).

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants
Isophorone	72h EC50 Desmodesmus subspicatus: = 475.4 mg/L
78-59-1	96h EC50 Pseudokirchneriella subcapitata: 51.1 - 342 mg/L
Cumene (constituent)	72h EC50 Pseudokirchneriella subcapitata: = 2.6 mg/L
98-82-8	

Chemical name	Fish
Isophorone	96h LC50 Pimephales promelas: 132 - 159 mg/L (flow-through)
78-59-1	96h LC50 Lepomis macrochirus: 180 - 250 mg/L (static)
	96h LC50 Pimephales promelas: 213 - 271 mg/L (static)
Solvent naphtha, petroleum, heavy aromatic	96h LC50 Pimephales promelas: = 19 mg/L (static)
64742-94-5	96h LC50 Oncorhynchus mykiss: = 2.34 mg/L
	96h LC50 Lepomis macrochirus: = 1740 mg/L (static)
	96h LC50 Pimephales promelas: = 45 mg/L (flow-through)
	96h LC50 Pimephales promelas: = 41 mg/L
Ethyl 3-ethoxypropionate 763-69-9	96h LC50 Pimephales promelas: = 62 mg/L (static)
Solvent naphtha, petroleum, light aromatic 64742-95-6	96h LC50 Oncorhynchus mykiss: = 9.22 mg/L
1,2,4-Trimethylbenzene (constituent) 95-63-6	96h LC50 Pimephales promelas: 7.19 - 8.28 mg/L (flow-through)
Naphthalene (constituent)	96h LC50 Oncorhynchus mykiss: = 1.6 mg/L (flow-through)
91-20-3	96h LC50 Oncorhynchus mykiss: 0.91 - 2.82 mg/L (static)
	96h LC50 Pimephales promelas: = 1.99 mg/L (static)
	96h LC50 Lepomis macrochirus: = 31.0265 mg/L (static)
	96h LC50 Pimephales promelas: 5.74 - 6.44 mg/L (flow-through)
1,3,5-Trimethylbenzene (constituent) 108-67-8	96h LC50 Pimephales promelas: = 3.48 mg/L
Cumene (constituent)	96h LC50 Pimephales promelas: 6.04 - 6.61 mg/L (flow-through)
98-82-8	96h LC50 Oncorhynchus mykiss: = 4.8 mg/L (flow-through)
	96h LC50 Oncorhynchus mykiss: = 2.7 mg/L (semi-static)
	96h LC50 Poecilia reticulata: = 5.1 mg/L (semi-static)

Chemical name	Crustacea
Isophorone	48h EC50 Daphnia magna: = 117 mg/L
78-59-1	
Solvent naphtha, petroleum, heavy aromatic	48h EC50 Daphnia magna: = 0.95 mg/L
64742-94-5	
Ethyl 3-ethoxypropionate	48h EC50 Daphnia magna: = 970 mg/L
763-69-9	
Solvent naphtha, petroleum, light aromatic	48h EC50 Daphnia magna: = 6.14 mg/L
64742-95-6	
1,2,4-Trimethylbenzene (constituent)	48h EC50 Daphnia magna: = 6.14 mg/L
95-63-6	
Naphthalene (constituent)	48h EC50 Daphnia magna: 1.09 - 3.4 mg/L Static
91-20-3	48h EC50 Daphnia magna: = 1.96 mg/L Flow through
	48h LC50 Daphnia magna: = 2.16 mg/L
Cumene (constituent)	48h EC50 Daphnia magna: 7.9 - 14.1 mg/L Static
98-82-8	48h EC50 Daphnia magna: = 0.6 mg/L

Persistence and Degradability No information available.

Bioaccumulation

Chemical name	Partition coefficient
Isophorone 78-59-1	1.66
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	2.9 - 6.1
Ethyl 3-ethoxypropionate 763-69-9	1.35
1,2,4-Trimethylbenzene (constituent)	3.63

95-63-6	
Naphthalene (constituent) 91-20-3	3.6
Cumene (constituent) 98-82-8	3.7

13. DISPOSAL CONSIDERATIONS

Waste treatment methods			
Waste Disposal Methods	Contain and dispose of waste according to local regulations.		
Contaminated Packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.		
14. TRANSPORT INFORMATION			
Note:	This information is not intended to convey all specific transportation requirements relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation information can be found in the specific regulations for your mode of transportation. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.		
DOT	Not regulated		
ICAO / IATA / IMDG / IMO	Not Regulated		

15. REGULATORY INFORMATION

International Inventories

For further information, please contact:. All components are listed on the TSCA Inventory. Supplier (manufacturer/importer/downstream user/distributor).

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Naphthalene (constituent)	91-20-3	0.1 - < 1	0.1
Cumene (constituent)	98-82-8	0.1 - < 1	0.1

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:.

Chemical name	CAS No	Weight-%
Isophorone	78-59-1	30 - 60
Naphthalene (constituent)	91-20-3	0.1 - < 1
Cumene (constituent)	98-82-8	0.1 - < 1

US State Regulations

Chemical name	Massachusetts
Isophorone 78-59-1	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X

Naphthalene (constituent) 91-20-3	x
1,3,5-Trimethylbenzene (constituent) 108-67-8	X
Cumene (constituent) 98-82-8	X

Chemical name	Minnesota Right To Know
Isophorone	X
78-59-1	
1,2,4-Trimethylbenzene (constituent)	X
95-63-6	
Naphthalene (constituent)	X
91-20-3	
Cumene (constituent)	X
98-82-8	

Chemical name	New Jersey
Isophorone 78-59-1	x
1,2,4-Trimethylbenzene (constituent) 95-63-6	x
Naphthalene (constituent) 91-20-3	x
Cumene (constituent) 98-82-8	x

Chemical name	Pennsylvania
Isophorone	X
78-59-1	
1,2,4-Trimethylbenzene (constituent)	X
95-63-6	
Naphthalene (constituent)	X
91-20-3	
Cumene (constituent)	X
98-82-8	

<u>California Proposition 65</u> This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

Chemical name	California Proposition 65
Naphthalene (constituent)	Carcinogen
Cumene (constituent)	Carcinogen

Canada

Chemical name	NPRI - National Pollutant Release Inventory
Isophorone 78-59-1	Part 4 Substance (as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999)
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	Part 5, Other Groups and Mixtures Part 4 Substance (as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999)
Ethyl 3-ethoxypropionate 763-69-9	Part 4 Substance (as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999)
Solvent naphtha, petroleum, light aromatic 64742-95-6	Part 5, Other Groups and Mixtures
1,2,4-Trimethylbenzene (constituent) 95-63-6	Part 1, Group A Substance; Part 5, Individual Substances Part 4 Substance (as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999)
Naphthalene (constituent) 91-20-3	Part 1, Group A Substance Part 4 Substance (as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999)

HMIS

108-67-8	Part 5, Isomer Groups (total of 1,2,3-Trimethylbenzene, CAS 526-73-8, and 1,3,5-Trimethylbenzene, CAS 108-67-8, excluding 1,2,4-Trimethylbenzene, CAS 95-63-6, listed under Trimethylbenzene (all isomers)) Part 4 Substance (as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999)
Cumene (constituent) 98-82-8	Part 1, Group A Substance Part 4 Substance (as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999)

16. OTHER INFORMATION

Health hazards	Flammability	Reactivity	Personal Protection
2 *	2	0	Х

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value

ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen A2 - Suspected Human Carcinogen A3 - Animal Carcinogen IARC: (International Agency for Research on Cancer) Group 1 - Carcinogenic to Humans Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans Group 3 - Not Classifiable as to Carcinogenicity in Humans NTP: (National Toxicity Program) Known - Known Carcinogen Reasonably Anticipated to be a Human Carcinogen OSHA: (Occupational Safety & Health Administration) X - Present

Revision Date Jan-25-2023

Pursuant to NOM-018-STPS-2015

This information within is considered correct but is not exhaustive and will be used for guidance only, which is based on the current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet