

SAFETY DATA SHEET

Published DateRevision DateRevision NumberJan-16-2023Jan-16-20232.7

1. IDENTIFICATION

Product identifier

Product code 8420

Product name Brilliant Orange

Product category 8400 Series SV Screen Ink

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use
Recommended use Industrial Printing Operations

Details of the supplier of the safety data sheet

UNITED STATES
UNITED KINGDOM
Nazdar Company
Nazdar Limited
8501 Hedge Lane Terrace
Shawnee, KS 66227
Barton Road
Heaton Mersey

Tel: +001-913-422-1888 Stockport, England SK4 3EG Tel: +001-800-677-4657 Tel: +44 161 442 2111

Fax: +001-913-422-2294 www.nazdar.com

Emergency telephone number

USA: Chemtrec: +001-800-424-9300

Outside USA: Chemtrec: +001-703-527-3887

24 Hour Emergency Phone Number

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 1 - (H318)
Carcinogenicity	Category 2 - (H351)
Aspiration hazard	Category 1 - (H304)
Chronic aquatic toxicity	Category 3 - (H412)
Flammable liquids	Category 3 - (H226)

Label elements



Danger

Hazard statements

H226 - Flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H318 - Causes serious eye damage

H351 - Suspected of causing cancer

H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor

P331 - Do NOT induce vomiting

P403 + P235 - Store in a well-ventilated place. Keep cool

Hazards not otherwise classified (HNOC)

Harmful to aquatic life.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical name	CAS No	Weight-%	Trade secret	Note
Solvent naphtha, petroleum, heavy aromatic	64742-94-5	10 - 30	*	
Cyclohexanone	108-94-1	10 - 30	*	
Butyrolactone	96-48-0	5 - 10	*	
Solvent naphtha, petroleum, light aromatic	64742-95-6	1 - 5	*	
Kaolin	1332-58-7	1 - 5	*	
1,2,4-Trimethylbenzene (constituent)	95-63-6	1 - 5	*	1
Naphthalene (constituent)	91-20-3	1 - 5	*	1
1,3,5-Trimethylbenzene (constituent)	108-67-8	0.1 - < 1	*	1
Dibutyltin dilaurate	77-58-7	0.1 - < 1	*	

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

Note

Inhalation

4. FIRST-AID MEASURES

Description of first aid measures

General Advice Show this safety data sheet to the doctor in attendance.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Get medical attention if irritation develops and

persists.

Skin Contact Wash off immediately with soap and plenty of water for at least 15 minutes. Remove

contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.

If breathing is irregular or stopped, administer artificial respiration. Get medical attention

immediately. Remove person to fresh air and keep comfortable for breathing.

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a

physician or poison control center immediately.

Most important symptoms and effects, both acute and delayed

None under normal use conditions.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

^{1.} Hazardous Constituent contained in Complex Substance(s) required for disclosure

Suitable Extinguishing Media

Water spray. Carbon dioxide (CO2). Foam. Dry chemical. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

No information available.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Sealed containers may rupture when heated. Cool containers / tanks with water spray.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Evacuate personnel to safe areas. Remove all sources of ignition. Keep people away from

and upwind of spill/leak. Avoid contact with eyes, skin and clothing. Ventilate the area. Avoid

breathing dust or vapor.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained. Keep out of drains, sewers, ditches and waterways.

Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Use

personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

Storage Keep away from open flames, hot surfaces and sources of ignition. Keep out of the reach of

children. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep

container closed when not in use.

Incompatible Products Strong oxidizing agents. Strong acids. Strong bases. Reducing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits

Chemical name	ACGIH TLV
Cyclohexanone	TWA: 20 ppm
108-94-1	STEL: 50 ppm
	Skin
Kaolin	TWA: 2 mg/m³ particulate matter containing no asbestos and <1%
1332-58-7	crystalline silica, respirable particulate matter
1,2,4-Trimethylbenzene (constituent)	TWA: 10 ppm
95-63-6	
Naphthalene (constituent)	TWA: 10 ppm
91-20-3	Skin

1,3,5-Trimethylbenzene (constituent) 108-67-8	TWA: 10 ppm
Chemical name	OSHA PEL
Cyclobovonone	TMA: 50 nnm

Chemical name	OSHA PEL
Cyclohexanone	TWA: 50 ppm
108-94-1	TWA: 200 mg/m ³
Kaolin	TWA: 15 mg/m³ total dust
1332-58-7	TWA: 5 mg/m³ respirable fraction
Naphthalene (constituent)	TWA: 10 ppm
91-20-3	TWA: 50 mg/m ³

Chemical name	OSHA PEL (vacated)
Cyclohexanone	TWA: 25 ppm
108-94-1	TWA: 100 mg/m ³
	Skin
Kaolin	TWA: 10 mg/m³ total dust
1332-58-7	TWA: 5 mg/m³ respirable fraction
Naphthalene (constituent)	TWA: 10 ppm
91-20-3	TWA: 50 mg/m ³
	STEL: 15 ppm
	STEL: 75 mg/m ³

Chemical name	Ontario TWAEV
Cyclohexanone	TWA: 20 ppm
108-94-1	STEL: 50 ppm
	Skin
Kaolin	TWA: 2 mg/m³ respirable particulate matter
1332-58-7	
Naphthalene (constituent)	TWA: 10 ppm
91-20-3	Skin

Chemical name	Mexico OEL (TWA)
Cyclohexanone	TWA/VLE-PPT: 20 ppm
108-94-1	STEL/PPT-CT: 50 ppm
Kaolin	TWA/VLE-PPT: 2 mg/m³ respirable fraction
1332-58-7	
Naphthalene (constituent)	TWA/VLE-PPT: 10 ppm
91-20-3	STEL/PPT-CT: 15 ppm

Appropriate engineering controls

Engineering Measures

In case of insufficient ventilation, wear suitable respiratory equipment. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Wear safety glasses with side shields (or goggles). Ensure that eyewash stations and safety

showers are close to the workstation location. If splashes are likely to occur:. Wear suitable

face shield.

Skin Protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as

appropriate, to prevent skin contact.

Hand Protection Chemical resistant protective gloves.

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding >480 minutes of permeation time): eg. nitrile rubber (0.4 mm), chloroprene

rubber (0.5 mm), polyvinylchloride (0.7 mm) and other

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers. Taking into account the varying conditions, the practical usage of a

chemical-protective glove in practice may be much shorter than the permeation time

determined through testing.

Due to different glove types, the manufacturer's directions for use should be observed. Replace gloves immediately when torn or any change in appearance is noticed such as

dimension, color, flexibility.

Respiratory Protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of

the material.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before eating, drinking or

smoking. Wash contaminated clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid Appearance Colored

Odor Characteristic Odor Threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

PH No data available

Melting Point / Freezing PointNo information availableNo data availableBoiling Point / Boiling Range> 149 °C / 300 °F

Flash Point 44 °C / 111 °F Tag closed cup

Evaporation rate No data available Flammability Limit in Air

Upper flammability limit
Lower flammability limit
No data available
No data available

Lower flammability limitNo data availableVapor PressureNo data availableVapor DensityNo data available

Specific Gravity 1.07

Water SolubilityNo data availableSolubility in other solventsNo data availablePartition coefficient: n-octanol/waterNo data available

Autoignition TemperatureNo information availableNo data availableHyphenNo data available

Kinematic viscosity
No data available
Dynamic viscosity
No data available

Explosive PropertiesNo data available **Oxidizing Properties**No data available

Other information

Photochemically Reactive Yes Weight Per Gallon (lbs/gal) 8.93

VOC by weight %	VOC by volume %	VOC lbs/gal	VOC grams/liter
(less water)	(less water)	(less water)	(less water)
61.15	64.11	5.46	654.65

10. STABILITY AND REACTIVITY

Reactivity

No information available.

Chemical stability

Stable under normal conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases. Reducing agent.

Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide. Carbon dioxide (CO2).

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

InhalationSpecific test data for the substance or mixture is not available.Eye ContactSpecific test data for the substance or mixture is not available.Skin ContactSpecific test data for the substance or mixture is not available.IngestionSpecific test data for the substance or mixture is not available.

Chemical name	Oral LD50	
Solvent naphtha, petroleum, heavy aromatic	> 5000 mg/kg (Rat)	
64742-94-5		
Cyclohexanone	= 1544 mg/kg (Rat)	
108-94-1		
Butyrolactone	= 1540 mg/kg (Rat)	
96-48-0		
Solvent naphtha, petroleum, light aromatic	= 8400 mg/kg (Rat)	
64742-95-6		
Kaolin	> 5000 mg/kg (Rat)	
1332-58-7		
1,2,4-Trimethylbenzene (constituent)	= 3280 mg/kg (Rat)	
95-63-6		
Naphthalene (constituent)	= 1110 mg/kg (Rat)	
91-20-3		
Dibutyltin dilaurate	= 45 mg/kg (Rat)	
77-58-7		

Chemical name	Dermal LD50
Solvent naphtha, petroleum, heavy aromatic	> 2000 mg/kg (Rabbit)
64742-94-5	
Cyclohexanone	= 947 mg/kg(Rabbit)
108-94-1	
Butyrolactone	> 5640 mg/kg(Rabbit)
96-48-0	
Solvent naphtha, petroleum, light aromatic	> 2000 mg/kg (Rabbit)
64742-95-6	
Kaolin	> 5000 mg/kg (Rat)
1332-58-7	
1,2,4-Trimethylbenzene (constituent)	> 3160 mg/kg (Rabbit)
95-63-6	
Naphthalene (constituent)	= 1120 mg/kg (Rabbit)
91-20-3	
Dibutyltin dilaurate	> 2000 mg/kg (Rat)
77-58-7	

Chemical name	Inhalation LC50	
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	> 590 mg/m³ (Rat) 4 h	
Cyclohexanone 108-94-1	> 6.2 mg/L (Rat)4 h	
Butyrolactone 96-48-0	> 5100 mg/m³ (Rat) 4 h	
Solvent naphtha, petroleum, light aromatic 64742-95-6	= 3400 ppm (Rat) 4 h	
1,2,4-Trimethylbenzene (constituent) 95-63-6	= 18 g/m³ (Rat) 4 h	

Naphthalene (constituent)	> 0.4 mg/L (Rat)4 h
91-20-3	
1,3,5-Trimethylbenzene (constituent)	= 24 g/m³ (Rat) 4 h
108-67-8	

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Specific test data for the substance or mixture is not available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Specific test data for the substance or mixture is not available. Causes skin irritation (pain,

redness and swelling). (based on components).

Eye damage/irritation Specific test data for the substance or mixture is not available. Causes serious eye damage.

(based on components).

IrritationSpecific test data for the substance or mixture is not available.CorrosivitySpecific test data for the substance or mixture is not available.SensitizationSpecific test data for the substance or mixture is not available.Mutagenic EffectsSpecific test data for the substance or mixture is not available.

Carcinogenic effects Specific test data for the substance or mixture is not available. Suspected of causing

cancer. (based on components).

Reproductive Effects
STOT - single exposure
STOT - repeated exposure
Chronic Toxicity
Specific test data for the substance or mixture is not available.
Specific test data for the substance or mixture is not available.
Specific test data for the substance or mixture is not available.
Specific test data for the substance or mixture is not available.

Aspiration hazard Specific test data for the substance or mixture is not available. May be fatal if swallowed and

enters airways. (based on components).

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH
Cyclohexanone	A3
108-94-1	
Naphthalene (constituent)	A3
91-20-3	

Chemical name	IARC
Naphthalene (constituent)	Group 2B
91-20-3	·

Chemical name	NTP
Naphthalene (constituent)	Reasonably Anticipated
91-20-3	

Chemical name	OSHA
Naphthalene (constituent)	X
91-20-3	

Numerical measures of toxicity - Product Information

Unknown acute toxicity 0 % of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 5,329.20 mg/kg
ATEmix (dermal) 6,007.60 mg/kg
ATEmix (inhalation-dust/mist) 7.41 mg/l
ATEmix (inhalation-vapor) 54.40 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Specific test data for the substance or mixture is not available. Harmful to aquatic life with long lasting effects. (based on components).

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants
Butyrolactone	96h EC50 Desmodesmus subspicatus: = 79 mg/L
96-48-0	72h EC50 Desmodesmus subspicatus: = 360 mg/L

Chemical name	Fish	
Solvent naphtha, petroleum, heavy aromatic	96h LC50 Pimephales promelas: = 19 mg/L (static)	
64742-94-5	96h LC50 Oncorhynchus mykiss: = 2.34 mg/L	
	96h LC50 Lepomis macrochirus: = 1740 mg/L (static)	
	96h LC50 Pimephales promelas: = 45 mg/L (flow-through)	
	96h LC50 Pimephales promelas: = 41 mg/L	
Cyclohexanone	96h LC50 Pimephales promelas: 481 - 578 mg/L (flow-through)	
108-94-1	96h LC50 Pimephales promelas: = 8.9 mg/L	
Butyrolactone	96h LC50 Lepomis macrochirus: = 56 mg/L (static)	
96-48-0		
Solvent naphtha, petroleum, light aromatic	96h LC50 Oncorhynchus mykiss: = 9.22 mg/L	
64742-95-6		
1,2,4-Trimethylbenzene (constituent)	96h LC50 Pimephales promelas: 7.19 - 8.28 mg/L (flow-through)	
95-63-6		
Naphthalene (constituent)	96h LC50 Oncorhynchus mykiss: = 1.6 mg/L (flow-through)	
91-20-3	96h LC50 Oncorhynchus mykiss: 0.91 - 2.82 mg/L (static)	
	96h LC50 Pimephales promelas: = 1.99 mg/L (static)	
	96h LC50 Lepomis macrochirus: = 31.0265 mg/L (static)	
	96h LC50 Pimephales promelas: 5.74 - 6.44 mg/L (flow-through)	
1,3,5-Trimethylbenzene (constituent)	96h LC50 Pimephales promelas: = 3.48 mg/L	
108-67-8		

Chemical name	Crustacea
Solvent naphtha, petroleum, heavy aromatic	48h EC50 Daphnia magna: = 0.95 mg/L
64742-94-5	
Butyrolactone	48h EC50 Daphnia magna Straus: > 500 mg/L
96-48-0	
Solvent naphtha, petroleum, light aromatic	48h EC50 Daphnia magna: = 6.14 mg/L
64742-95-6	
1,2,4-Trimethylbenzene (constituent)	48h EC50 Daphnia magna: = 6.14 mg/L
95-63-6	
Naphthalene (constituent)	48h EC50 Daphnia magna: 1.09 - 3.4 mg/L Static
91-20-3	48h EC50 Daphnia magna: = 1.96 mg/L Flow through
	48h LC50 Daphnia magna: = 2.16 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

Chemical name	Partition coefficient
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	2.9 - 6.1
Cyclohexanone 108-94-1	0.86
Butyrolactone 96-48-0	-0.566
1,2,4-Trimethylbenzene (constituent) 95-63-6	3.63
Naphthalene (constituent) 91-20-3	3.6

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste Disposal Methods Contain and dispose of waste according to local regulations.

Contaminated Packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION

Note: This information is not intended to convey all specific transportation requirements relating to

this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation information can be found in the specific regulations for your mode of transportation. It is the responsibility of the transporting organization to follow all applicable laws, regulations and

rules relating to the transportation of the material.

DOT In the U.S. and Canada, this material may be reclassified as a combustible liquid and is not

regulated, via surface transportation, in containers less than 119 gallons or 450 liters [per 49 CFR 173.150 (f)] [per Transportation of Dangerous Goods Regulations/Clear Language Part

1.33].

UN/ID no UN1210
Proper Shipping Name Printing Ink

Transport hazard class(es) 3
Packing Group III

ICAO / IATA / IMDG / IMO

UN/ID no UN1210 Proper Shipping Name Printing Ink

Transport hazard class(es) 3
Packing Group | ||

15. REGULATORY INFORMATION

International Inventories

For further information, please contact:. All components are listed on the TSCA Inventory. Supplier (manufacturer/importer/downstream user/distributor).

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
1,2,4-Trimethylbenzene (constituent)	95-63-6	1 - 5	1.0
Naphthalene (constituent)	91-20-3	1 - 5	0.1

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:.

Chemical name	CAS No	Weight-%
Naphthalene (constituent)	91-20-3	1 - 5

US State Regulations

Chemical name	Massachusetts
Cyclohexanone 108-94-1	X
Kaolin 1332-58-7	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Naphthalene (constituent)	X

91-20-3	
1,3,5-Trimethylbenzene (constituent)	X
108-67-8	

	Minnesota Right To Know
Cyclohexanone 108-94-1	X
Kaolin 1332-58-7	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Naphthalene (constituent) 91-20-3	X
Dibutyltin dilaurate 77-58-7	X

Chemical name	New Jersey
Cyclohexanone	X
108-94-1	
Kaolin	X
1332-58-7	
1,2,4-Trimethylbenzene (constituent)	X
95-63-6	
Naphthalene (constituent)	X
91-20-3	

Chemical name	Pennsylvania
Cyclohexanone	X
108-94-1	
Kaolin	X
1332-58-7	
1,2,4-Trimethylbenzene (constituent)	X
95-63-6	
Naphthalene (constituent)	X
91-20-3	

<u>California Proposition 65</u>
This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

Chemical name	California Proposition 65
Naphthalene (constituent)	Carcinogen

Canada

Chemical name	NPRI - National Pollutant Release Inventory
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	Part 5, Other Groups and Mixtures Part 4 Substance (as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999)
Cyclohexanone 108-94-1	Part 4 Substance (as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999)
Butyrolactone 96-48-0	Part 4 Substance (as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999)
Solvent naphtha, petroleum, light aromatic 64742-95-6	Part 5, Other Groups and Mixtures
1,2,4-Trimethylbenzene (constituent) 95-63-6	Part 1, Group A Substance; Part 5, Individual Substances Part 4 Substance (as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999)
Naphthalene (constituent) 91-20-3	Part 1, Group A Substance Part 4 Substance (as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999)
1,3,5-Trimethylbenzene (constituent) 108-67-8	Part 5, Isomer Groups (total of 1,2,3-Trimethylbenzene, CAS 526-73-8, and 1,3,5-Trimethylbenzene, CAS 108-67-8, excluding

1,2,4-Trimethylbenzene, CAS 95-63-6, listed under
Trimethylbenzene (all isomers)) Part 4 Substance (as set out in
Section 65 of the List of Toxic Substances in Schedule 1 of the
Canadian Environmental Protection Act, 1999)

16. OTHER INFORMATION

HMISHealth hazardsFlammabilityReactivityPersonal Protection3 *20X

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value

ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated to be a Human Carcinogen OSHA: (Occupational Safety & Health Administration)

X - Present

Revision Date Jan-16-2023

Pursuant to NOM-018-STPS-2015

This information within is considered correct but is not exhaustive and will be used for guidance only, which is based on the current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet