

Print Date  
Jun-01-2015

Revision Date  
May-31-2015

Revision Number  
1

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

**Product identifier**

Product code **VF184**  
Product name **Screen Wash**  
Product category **Ink Product**

**Other means of identification**

Synonyms None

**Recommended use of the chemical and restrictions on use**

Recommended use Printing operations

**Details of the supplier of the safety data sheet**

UNITED STATES	UNITED KINGDOM
Nazdar Company	Nazdar Limited
8501 Hedge Lane Terrace	Barton Road
Shawnee, KS 66227	Heaton Mersey
Tel: 1-913-422-1888	Stockport, England SK4 3EG
Tel: 1-800-677-4657	Tel: +44 161 442 2111
Fax: 1-913-422-2294	
<a href="http://www.nazdar.com">www.nazdar.com</a>	

**Emergency telephone number**

USA: Chemtrec: 1-800-424-9300  
Outside USA: Chemtrec: 1-703-527-3887  
24 Hour Emergency Phone Number

**2. HAZARDS IDENTIFICATION**

**Classification**

Acute toxicity - Dermal	Category 4 - (H312)
Acute toxicity - Inhalation (Vapors)	Category 4 - (H332)
Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin Corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Flammable liquids	Category 2 - (H225)

**Label elements**



Signal Word  
Danger

**Hazard Statements**

H312 - Harmful in contact with skin  
 H315 - Causes skin irritation  
 H319 - Causes serious eye irritation  
 H332 - Harmful if inhaled  
 H336 - May cause drowsiness or dizziness  
 H225 - Highly flammable liquid and vapor

**Precautionary Statements**

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

**Hazards not otherwise classified (HNOC)**

May be harmful if swallowed.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Mixture**

Component	CAS-No	Weight %	Trade Secret	Note
Xylenes (o-, m-, p- isomers)	1330-20-7	30 - 60	*	
Acetone	67-64-1	30 - 60	*	
Ethyl benzene (constituent)	100-41-4	10 - 30	*	1

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

Note 1. Type of chemical: Constituent

### 4. FIRST AID MEASURES

**Description of first aid measures****General Advice**

Show this safety data sheet to the doctor in attendance.

**Eye Contact**

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.

**Skin Contact**

Wash off immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.

**Inhalation**

Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.

**Ingestion**

DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

**Most important symptoms and effects, both acute and delayed**

None under normal use conditions.

**Indication of any immediate medical attention and special treatment needed****Notes to Physician**

Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media**

Foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable Extinguishing Media**

No information available.

**Specific Hazards Arising from the Chemical**

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures****Personal Precautions**

Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

**Environmental precautions**

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

**Methods and material for containment and cleaning up**

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

## 7. HANDLING AND STORAGE

**Precautions for safe handling****Handling**

Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Ensure adequate ventilation.

**Conditions for safe storage, including any incompatibilities****Storage**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep container closed when not in use. Keep out of the reach of children.

**Incompatible Products**

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters****Exposure limits**

Component	ACGIH TLV
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 100 ppm STEL: 150 ppm
Acetone 67-64-1	TWA: 500 ppm STEL: 750 ppm
Ethyl benzene (constituent) 100-41-4	TWA: 20 ppm

Component	OSHA PEL
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 150 ppm STEL: 655 mg/m <sup>3</sup>
Acetone 67-64-1	TWA: 750 ppm TWA: 1800 mg/m <sup>3</sup> STEL: 2400 mg/m <sup>3</sup> STEL: 1000 ppm TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup>
Ethyl benzene (constituent) 100-41-4	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm

	STEL: 545 mg/m <sup>3</sup>
<b>Component</b>	<b>Ontario TWAEV</b>
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 100 ppm STEL: 150 ppm
Acetone 67-64-1	TWA: 500 ppm STEL: 750 ppm
Ethyl benzene (constituent) 100-41-4	TWA: 100 ppm STEL: 125 ppm
<b>Component</b>	<b>Mexico OEL (TWA)</b>
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA/LMPE-PPT: 100 ppm TWA/LMPE-PPT: 435 mg/m <sup>3</sup> STEL/LMPE-CT: 150 ppm STEL/LMPE-CT: 655 mg/m <sup>3</sup>
Acetone 67-64-1	TWA/LMPE-PPT: 1000 ppm TWA/LMPE-PPT: 2400 mg/m <sup>3</sup> STEL/LMPE-CT: 1260 ppm STEL/LMPE-CT: 3000 mg/m <sup>3</sup>
Ethyl benzene (constituent) 100-41-4	TWA/LMPE-PPT: 100 ppm TWA/LMPE-PPT: 435 mg/m <sup>3</sup> STEL/LMPE-CT: 125 ppm STEL/LMPE-CT: 545 mg/m <sup>3</sup>

**Appropriate engineering controls****Engineering Measures**

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.

**Individual protection measures, such as personal protective equipment****Eye/face Protection**

Wear safety glasses with side shields (or goggles). If splashes are likely to occur. Wear suitable face shield. Ensure that eyewash stations and safety showers are close to the workstation location.

**Skin Protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory Protection**

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.

**General Hygiene Considerations**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

<b>Physical State</b>	Liquid	<b>Appearance</b>	Water-white
<b>Odor</b>	Characteristic	<b>Odor Threshold</b>	No information available
<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>	
<b>pH</b>		No data available	
<b>Melting point/freezing point</b>		No data available	
<b>Boiling point/Boiling Range</b>	> 149 °C / 300 °F		
<b>Flash Point</b>	-20 °C / -4 °F	Closed cup (Minimum)	
<b>Evaporation rate</b>		No data available	
<b>Flammability Limit in Air</b>			
<b>Upper flammability limit</b>		No data available	

Lower flammability limit	No data available
Vapor Pressure	No data available
Vapor Density	No data available
Specific Gravity	0.83
Water Solubility	No data available
Solubility in other solvents	No data available
Partition coefficient: n-octanol/water	No data available
Autoignition Temperature	No data available
Decomposition temperature	No data available
Kinematic viscosity	No data available
Dynamic viscosity	No data available
Explosive Properties	No data available
Oxidizing Properties	No data available

**Other Information**

Photochemically Reactive	Yes
Weight Per Gallon (lbs/gal)	6.9

VOC by weight % (less water)	VOC by volume % (less water)	VOC lbs/gal (less water)	VOC grams/liter (less water)
100	100	6.92	829.09

**10. STABILITY AND REACTIVITY****Reactivity**

No information available.

**Chemical stability**

Stable under normal conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Keep away from open flames, hot surfaces and sources of ignition.

**Incompatible materials**

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

**Hazardous Decomposition Products**

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO<sub>2</sub>). Carbon monoxide.

**11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

<b>Inhalation</b>	There is no data for this product.
<b>Eye Contact</b>	There is no data for this product.
<b>Skin Contact</b>	There is no data for this product.
<b>Ingestion</b>	There is no data for this product.

Component	Oral LD50
Xylenes (o-, m-, p- isomers) 1330-20-7	4300 mg/kg ( Rat )
Acetone 67-64-1	5800 mg/kg ( Rat )
Ethyl benzene (constituent) 100-41-4	3500 mg/kg ( Rat )

Component	LD50 Dermal
Xylenes (o-, m-, p- isomers)	>1700 mg/kg ( Rabbit )

1330-20-7	
Ethyl benzene (constituent) 100-41-4	15354 mg/kg ( Rabbit )

Component	Inhalation LC50
Xylenes (o-, m-, p- isomers) 1330-20-7	5000 ppm ( Rat ) 4 h 47635 mg/L ( Rat ) 4 h
Ethyl benzene (constituent) 100-41-4	17.2 mg/L ( Rat ) 4 h

### Information on toxicological effects

**Symptoms** There is no data for this product.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** There is no data for this product.  
**Eye damage/irritation** There is no data for this product.  
**Irritation** There is no data for this product.  
**Corrosivity** There is no data for this product.  
**Sensitisation** May cause sensitization of susceptible persons.  
**Mutagenic Effects** There is no data for this product.  
**Reproductive Effects** There is no data for this product.  
**STOT - single exposure** There is no data for this product.  
**STOT - repeated exposure** There is no data for this product.  
**Chronic Toxicity** There is no data for this product.  
**Aspiration hazard** There is no data for this product.  
**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH
Ethyl benzene (constituent) 100-41-4	A3

Component	IARC
Ethyl benzene (constituent) 100-41-4	Group 2B

Component	OSHA
Ethyl benzene (constituent) 100-41-4	X

### Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (oral)** 4,905.00 mg/kg  
**ATEmix (dermal)** 3,252.00 mg/kg  
**ATEmix (inhalation-dust/mist)** 2.90 mg/l  
**ATEmix (inhalation-vapor)** 21.00 mg/l

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

None known

0% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Algae/aquatic plants
Ethyl benzene (constituent) 100-41-4	96h EC50 Pseudokirchneriella subcapitata: 1.7 - 7.6 mg/L [static] 72h EC50 Pseudokirchneriella subcapitata: 2.6 - 11.3 mg/L [static] 72h EC50 Pseudokirchneriella subcapitata: 4.6 mg/L 96h EC50 Pseudokirchneriella subcapitata: >438 mg/L

Component	Fish
Acetone 67-64-1	96h LC50 Oncorhynchus mykiss: 4.74 - 6.33 mg/L 96h LC50 Pimephales promelas: 6210 - 8120 mg/L [static] 96h LC50 Lepomis macrochirus: 8300 mg/L
Ethyl benzene (constituent) 100-41-4	96h LC50 Oncorhynchus mykiss: 11.0 - 18.0 mg/L [static] 96h LC50 Pimephales promelas: 7.55 - 11 mg/L [flow-through] 96h LC50 Pimephales promelas: 9.1 - 15.6 mg/L [static] 96h LC50 Lepomis macrochirus: 32 mg/L [static] 96h LC50 Oncorhynchus mykiss: 4.2 mg/L [semi-static] 96h LC50 Poecilia reticulata: 9.6 mg/L [static]

Component	Crustacea
Acetone 67-64-1	48h EC50 Daphnia magna: 10294 - 17704 mg/L [static] 48h EC50 Daphnia magna: 12600 - 12700 mg/L
Ethyl benzene (constituent) 100-41-4	48h EC50 Daphnia magna: 1.8 - 2.4 mg/L

**Persistence and Degradability**

No information available.

**Bioaccumulation**

No information available.

Component	Partition coefficient
Xylenes (o-, m-, p- isomers) 1330-20-7	2.96
Acetone 67-64-1	-0.24
Ethyl benzene (constituent) 100-41-4	3.118

**Other adverse effects**

No information available

### 13. DISPOSAL CONSIDERATIONS

**Waste treatment methods****Waste Disposal Methods**

Contain and dispose of waste according to local regulations.

**Contaminated Packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. TRANSPORT INFORMATION

**DOT**

UN/ID no.	UN1210
Proper Shipping Name	Printing Ink Related Material
Hazard Class	3
Packing Group	II

**ICAO / IATA / IMDG / IMO**

UN/ID no.	UN1210
Proper Shipping Name	Printing Ink Related Material
Hazard Class	3
Packing Group	II

### 15. REGULATORY INFORMATION

**International Inventories**

All components are listed on the TSCA Inventory. For further information, please contact: Supplier

(manufacturer/importer/downstream user/distributor).

**U.S. Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS-No	Weight %	SARA 313 - Threshold Values
Xylenes (o-, m-, p- isomers)	1330-20-7	30 - 60	1.0
Ethyl benzene (constituent)	100-41-4	10 - 30	0.1

**Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)**

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:

Component	CAS-No	Weight %
Xylenes (o-, m-, p- isomers)	1330-20-7	30 - 60
Ethyl benzene (constituent)	100-41-4	10 - 30

**U.S. State Regulations**

Component	Massachusetts Right To Know
Xylenes (o-, m-, p- isomers) 1330-20-7	X
Acetone 67-64-1	X
Ethyl benzene (constituent) 100-41-4	X

Component	Minnesota Right To Know
Xylenes (o-, m-, p- isomers) 1330-20-7	X
Acetone 67-64-1	X
Ethyl benzene (constituent) 100-41-4	X

Component	New Jersey Right To Know
Xylenes (o-, m-, p- isomers) 1330-20-7	X
Acetone 67-64-1	X
Ethyl benzene (constituent) 100-41-4	X

Component	Pennsylvania Right To Know
Xylenes (o-, m-, p- isomers) 1330-20-7	X
Acetone 67-64-1	X
Ethyl benzene (constituent) 100-41-4	X

**California Prop. 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

Component	California Prop. 65
Ethyl benzene (constituent)	Carcinogen
Toluene	Developmental Female Reproductive



**Canada**

Component	NPRI - National Pollutant Release Inventory
Xylenes (o-, m-, p- isomers) 1330-20-7	Part 1, Group A Substance total of all isomers of Xylene, including m-Xylene, CAS No. 108-38-3, o-Xylene, CAS No. 95-47-6, and p-Xylene, CAS No. 106-42-3 Part 5, Isomer Groups total of all isomers of Xylene, including m-Xylene, CAS No. 108-38-3, o-Xylene, CAS No. 95-47-6, and p-Xylene, CAS No. 106-42-3 Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
Acetone 67-64-1	Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
Ethyl benzene (constituent) 100-41-4	Part 1, Group A Substance Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999

**16. OTHER INFORMATION**

HMIS:	Health	Flammability	Reactivity	Personal Protection
	2 *	3	0	X

**Key or legend to abbreviations and acronyms used in the safety data sheet****Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value

**ACGIH: (American Conference of Governmental Industrial Hygienists)**

- A1 - Known Human Carcinogen
- A2 - Suspected Human Carcinogen
- A3 - Animal Carcinogen

**IARC: (International Agency for Research on Cancer)**

- Group 1 - Carcinogenic to Humans
- Group 2A - Probably Carcinogenic to Humans
- Group 2B - Possibly Carcinogenic to Humans

**NTP: (National Toxicity Program)**

- Known - Known Carcinogen
- Reasonably Anticipated to be a Human Carcinogen

**OSHA: (Occupational Safety & Health Administration)**

- X - Present

**Revision Date** May-31-2015

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of MSDS**