

# MATERIAL SAFETY DATA SHEET

(According to ANSI Z400.1-2004)

PRODUCT NAME: LX660 DIRECT EMULSION

Previous Issue: November 23, 2009 Date Prepared: November 2, 2012

### 1. IDENTIFICATION OF PRODUCT AND COMPANY

Product Name: LX660 DIRECT EMULSION ULANO® CORPORATION

110 Third Avenue Brooklyn, NY 11217

Phone: 718-237-4700 Fax: 718-802-1119

Emergency contact: 1-800-424-9300 (CHEMTREC)

MSDS prepared by: Fred Widman

Recommended use: Manufacture of stencils for screenprinting

# 2. HAZARD IDENTIFICATION OF THE PREPARATION

This preparation is not classified as hazardous according to 29CFR 1910-1200.

Appearance / Odor: viscous liquid / mild odor

Potential Health Effects: See Section 11 for more information

Potential Health Effects Eyes

This product may be irritating to the eyes.

Potential Health Effects: Skin

Repeated exposure may irritation to skin

Potential Health Effects: Ingestion

Ingestion of this product may be irritating to the digestive system.

Potential Health Effects: Inhalation

No known effect

Xi Irritant

36 Irritating to eyes

Target Organs: not known

This product does not contain any carcinogens or potential carcinogens as listed

by OSHA, IARC or NTP.

Potential Environmental Effects: See Section 12 for more information.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture of the below mentioned materials Hazardous components:

Date Prepared: November 2, 2012

EINECS-No Name Hazard %content CAS-No. R-phrases

Trade Secret Acrylates 36 Xi 5.0-25.0%

#### Additional information:

For full text of risk phrases see Section 16.

### 4. FIRST AID MEASURES

#### Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

# Ingestion:

Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention. Place in stable side position and seek medical advice. If breathing is irregular or has stopped, apply artificial respiration.

### **Skin Contact:**

Immediately flush skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention if irritation develops. Wash clothing before reuse.

# **Eye Contact:**

Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

# 5. FIRE-FIGHTING MEASURES

Flammable: no Means of extinction: treat surrounding fire

Unsuitable extinguishing media: Hard water stream

Flash point: n.a

Explosion data impact: n.a

Upper flammable limit: n.a

Lower flammable limit: n.a

Explosion data static: n.a

Hazardous combustion products: typical carbon oxygen compounds. Fire fighters should wear SCBA for fighting fires in enclosed areas.

Autoignition temp: n.a

### 6. ACCIDENTAL RELEASE MEASURES

Do not empty large quantities directly into drains. Collect with liquid absorbing material and proceed according to local waste disposal regulations.

### 7. HANDLING AND STORAGE

Keep container tightly closed and in a cool and well ventilated place. Ensure adequate ventilation. Avoid contact with skin and eyes.

#### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Occupational exposure limit:

CAS # Name OSHA TWA ACGIH TWA

No exposure limits established for ingredients

Date Prepared: November 2, 2012

### **Engineering controls**

General- not required

Local exhaust- recommended

Other- none

#### **Personal Protection**

Gloves- recommended Respirator- not required

Eye- protective goggles recommended Protective footwear- not required Protective clothing- not required

Other- none

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Form: viscous liquid

Color: red
Odor: mild
Flash point: n.a
Ignition temperature: n.a

Density: ~1.1 g/cm<sup>3</sup>

Viscosity: ~13,000 cps @ 20°C

Explosion limits: n.a

Boiling point: ~212°F (100° C)

Vapour density: >1(air=1)
Vapour pressure: 25hPa @ 25°C
Freezing point: not known
pH: 4.2-5.8

Coefficient of water/ oil distribution: not known Volatile Organic Compounds: less than 0.1%

#### 10. STABILITY AND REACTIVITY

Stable under recommended storage and handling conditions (see Section 7).

Store as a non-hazardous liquid

INCOMPATABILITY: Strong oxidizers

# 11. TOXICOLOGICAL INFORMATION

# Effects of acute exposure:

COMPONENT	CAS#	LD <sub>50</sub>	LC <sub>50</sub>
Acrylates	Trade Secret	>5,000 mg/kg, oral rat	Not established

# **General information:**

Effects of acute exposure:

Repeated or prolonged contact causes local irritation of skin and

mucous membranes, particularly the eyes.

Irritancy of product-possible

Skin sensitization- none reported

Respiratory sensitization- none known

**Date Prepared: November 2, 2012** 

Carcinogenicity- no

IARC- no ACGIH - no

Reproductive toxicity - none known

Teratogenicity - none known Embryotoxicity - none known Mutagenicity - none known

Name of synergistic products/effects- none known

#### 12. ECOLOGICAL INFORMATION

Do not empty into drains or release into open water.

Do not store at public waste disposal sites.

#### 13. WASTE DISPOSAL INFORMATION

Dispose of as a non-hazardous aqueous waste

Empty container: scrap metal recycling or re-conditioning

Soiled container: (treatment like product itself)

#### 14. TRANSPORT INFORMATION

ADR/RID/DOT: Class: Not regulated

UN: n.a

Packaging group: n.a

IMDG: Class: not regulated

EMS: n.a UN: n.a

Marine pollutant: No Packaging group: n.a

### **15. REGULATORY INFORMATION**

Global Inventories (components):

TSCA: United States - included DSL: Canada - included ENCS: Japan - included EINECS: Europe - included

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65)

This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins under California Proposition 65 at levels which would be subject to the proposition.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of information required by the CPR, and it is not classified as a hazardous material.

#### Labeling

Χi

Date Prepared: November 2, 2012

R-phrases:

36 Irritating to eyes

S-phrases:

In case of contact with eyes, rinse immediately with plenty of water

and seek medical attention

Special labeling:

n.a

National Regulation for Germany:

Water pollution class: 1

#### **16. OTHER INFORMATION**

### HMIS: Health 1, Flammability 0, Reactivity 0

Text of risk phrases mentioned in Section 2:

Xi Irritant

36 Irritating to eyes

For further information please refer to our technical information sheet. Data in this MSDS correspond with our current level of knowledge, but do not represent any assurance of product properties. The user personally is responsible for compliance with all legal requirements.

#### **DISCLAIMER OF RESPONSIBILITY:**

This document is generated for the purpose of distributing health, safety and environmental data. It is not a specification sheet nor should any displayed data be construed as a specification. The information on this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the substance itself. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with handling, storage, use or disposal of this product.



# MATERIAL SAFETY DATA SHEET

(According to ANSI Z400.1-2004)

PRODUCT NAME: DIAZO - C / SENSITIZING POWDER

Previous Issue: June 28, 2011 Date Prepared: Jan 3, 2012

### 1. IDENTIFICATION OF PRODUCT AND COMPANY

Product Name: DIAZO - C / SENSITIZING POWDER

Company: ULANO® CORPORATION

110 Third Avenue

Brooklyn, NY 11217

Phone: 718-237-4700 Fax: 718-802-1119

Emergency contact: 1-800-424-9300 (CHEMTREC)

MSDS prepared by: P.Drago

Recommended use: Sensitizing powder for stencil emulsions.

# 2. HAZARD IDENTIFICATION OF THE PREPARATION

This preparation is not classified as hazardous according to 29CFR 1910-1200.

This product may be a flammable solid

Appearance: Powder
Odor: no odor

Potential Health Effects: See Section 11 for more information

Potential Health Effects Eyes: This product may be irritating to the eyes.

Potential Health Effects: Skin: Repeated exposure may irritation to skin

Potential Health Effects: Ingestion Ingestion of this product may be irritating to

the digestive system.

Xn Hazardous

Harmful if swallowed Irritating to eyes

May Be Flammable. Self Reactive Substance

Target Organs: not known

This product does not contain any carcinogens or potential carcinogens as listed by

OSHA, IARC or NTP.

Potential Environmental Effects: See Section 12 for more information.

Date Prepared: Jan 3, 2012

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture of the below mentioned materials Hazardous components:

EINECS-No	CAS-No.	Name	R-phrases	Hazard	% content
Not found	41432-19-3	Benzenediazonium, 4-(phenylamino)-, sulfate polymer with formaldehyde	11, 36, 22	F, Xn	100%

#### Additional information:

For full text of risk phrases see Section 16.

### 4. FIRST AID MEASURES

**Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

**Ingestion:** Expected to be a low ingestion hazard. May cause irritation to throat and mouth. Rinse mouth thoroughly with water. Do not induce vomiting. Seek medical attention if irritation develops.

**Skin Contact:** Immediately flush skin with plenty of water for at least 15 minutes. Get medical attention if irritation develops. Wash clothing before reuse.

**Eye Contact:** Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

### 5. FIRE-FIGHTING MEASURES

Flammable: no

Means of extinction: treat surrounding fire Unsuitable extinguishing media: Hard water stream

Flash point: n.a
Upper flammable limit: n.a
Lower flammable limit: n.a
Explosion data impact: n.a
Explosion data static: n.a

Hazardous combustion products: During fire, toxic fumes will be liberated.

Dust may cause an explosion.

Autoignition temp: n.a

Decomposition temperature: 180°C

This material is an organic powder. Care must be taken to avoid dust produced fire or explosion.

Fire fighters should wear SCBA for fighting fires in enclosed areas.

Date Prepared: Jan 3, 2012

#### 6. ACCIDENTAL RELEASE MEASURES

Do not empty large quantities directly into drains. Sweep up and collect in a sealable fiber or plastic container and proceed according to local waste disposal regulations. Avoid dust creation.

### 7. HANDLING AND STORAGE

Keep container tightly closed and in a cool and well ventilated place. Ensure adequate ventilation. Avoid contact with skin and eyes.

# 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Occupational exposure limit:

CAS # Name OSHA TWA ACGIH TWA

No exposure limits established for ingredients

**Engineering controls** 

General- not required Local exhaust- recommended

Other- none

**Personal Protection** 

Gloves- recommended

Respirator- NIOSH approved powder respirator if dust is created.

Eve- protective goggles recommended

Protective footwear- not required not required

Other- none

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Form: powder Color: yellow Odor: odorless Flash point: n.a Ignition temperature: n.a Density: n.a Viscosity: n.a Explosion limits: n.a Boiling point: n.a Vapor density: n.a Vapor pressure: n.a

Melting Point: Decomposes at 356°F (180°C)

pH: n.a

Coefficient of water/ oil distribution: soluble in water Volatile Organic Compounds: less than 0.1%

Date Prepared: Jan 3, 2012

### 10. STABILITY AND REACTIVITY

Stable under recommended storage and handling conditions (See Section 7).

Avoid exposure to heat and light Store as a possible flammable solid INCOMPATABILITY: Strong oxidizers

# 11. TOXICOLOGICAL INFORMATION

### Effects of acute exposure:

COMPONENT	CAS#	LD <sub>50</sub>	LC <sub>50</sub>
DIAZO POWDER	41432-19-3	1643 mg/kg, oral rat	Not established

#### General information:

Effects of acute exposure: Repeated or prolonged contact causes local irritation of

skin and mucous membranes, particularly the eyes.

Irritancy of productSkin sensitizationRespiratory sensitizationpossible
none reported
none known

Carcinogenicity- no IARC- no ACGIH - no

Reproductive toxicity - none known
Teratogenicity - none known
Embryotoxicity - none known
Mutagenicity - none known

Name of synergistic products/effects- none known

### 12. ECOLOGICAL INFORMATION

Do not empty large quantities into drains or release into open water.

Do not store at public waste disposal sites.

# 13. WASTE DISPOSAL INFORMATION

Dispose of as a possible flammable solid.

Empty container: scrap recycling or re-conditioning. Soiled container: (treatment like product itself)

Date Prepared: Jan 3, 2012

#### 14. TRANSPORT INFORMATION

ADR/RID/DOT: Class: 4.1 (Self Reactive Solid, Type D)

UN: 3226

Packaging group: n.a

IATA Class: 4.1 (Self Reactive Solid, Type D)

Label: 4.1

UN 3226

Passenger Aircraft: 429 Cargo Aircraft: 430

IMDG: Class: 4.1 (Self Reactive Solid, Type D)

EMS: F-J, S-G

UN: 3226

Marine pollutant: No Packaging group: n.a

### 15. REGULATORY INFORMATION

Global Inventories (components):

INGREDIANT	CAS No.	SARA 302 RQ	SARA 302 TPQ	SARA 313 LIST	RCRA RQ	CRCLA 261.33	TSCA 8(d)
Benzenediazonium, 4- (phenylamino) sulfate (1:1), polymer with formaldehyde	(41432-17-3)	No	No	No	No	No	No

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65)

This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins under California Proposition 65 at levels which would be subject to the proposition.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of information required by the CPR, and it is not classified as a hazardous material.

# Labeling

Xn

# R-phrases:

Harmful if swallowed 36 Irritating to eyes

# S-phrases:

16 Keep away from sources of ignition-No smoking

In case of contact with eyes, rinse with plenty of water and seek medical advice

Take precautionary measures against static discharges

### Special labeling:

National Regulation for Germany:

Water pollution class: 1

Date Prepared: Jan 3, 2012

#### **16. OTHER INFORMATION**

HMIS: Health 1, Flammability 2, Reactivity 0

Text of risk phrases mentioned in Section 2:

Xn

22 Harmful if swallowed

36 Irritating to eyes

For further information please refer to our technical information sheet. Data in this MSDS correspond with our current level of knowledge, but do not represent any assurance of product properties. The user personally is responsible for compliance with all legal requirements.

#### **DISCLAIMER OF RESPONSIBILITY:**

This document is generated for the purpose of distributing health, safety and environmental data. It is not a specification sheet nor should any displayed data be construed as a specification. The information on this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the substance itself. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with handling, storage, use or disposal of this product.