

# SAFETY DATA SHEET CPS SCREEN WASH UV

## **1. IDENTIFICATION**

Product Name	CPS SCREEN WASH UV	
Identified uses	Industrial use: Ink cleaner for printing inks.	
Uses advised against	The product should not be used for any purpose, other than that described above.	
Supplier	MacDermid Autotype Inc. 1675 Winnetka Circle Rolling Meadows IL 60008 USA T: 001 847 818 8262 F: 001 847 818 8280 e: technical@cps.eu	
Manufacturer	CPS - Chemical Products and Services, Grove Road, Wantage, Oxfordshire, OX12 7BZ UNITED KINGDOM T: +44 (0) 1235 773240 F: +44 (0) 1235 771196 e: technical@cps.eu	
Emergency Telephone	800-424-9300 (Chemtrec, 24 hours)	

# 2. HAZARD(S) IDENTIFICATION

## **EMERGENCY OVERVIEW**

This Product is Hazardous under the OSHA Hazard Communication Standard. This product is hazardous under the Workplace Hazardous Materials Information System (WHMIS) GHS Pictogram



	Signal Word Hazard Statements	Warning	
•	Precautionary Statements	H319	Causes serious eye irritation.
-		P280	Wear eye protection.
		P501	Dispose of contents/container in accordance with local regulations.
	GHS Classification		
-		Physical and Chemical Hazards	Not classified.
		Human health	Eye Irrit. 2 - H319
		Environment	Not classified.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

## ETHOXYLATED C13 ALCOHOLS

GHS Classification

Acute Tox. 4 - H302; Eye Dam. 1 - H318

### ETHOXYLATED C9-C11 ALCOHOLS

CAS No.:

EC No.:

GHS Classification Acute Tox. 4 - H302; Eye Dam. 1 - H318

## 4. FIRST-AID MEASURES

## **Description of first aid measures**

#### Inhalation

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

#### Ingestion

Immediately rinse mouth and drink plenty of water (200-300 ml). Give milk instead of water if readily available. Do not induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit doesn't enter the lungs. Get medical attention.

# Skin Contact

Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing. **Eye Contact** 

Promptly wash eyes with plenty of water while lifting the eye lids. Make sure to remove any contact lenses from the eyes before rinsing. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

## Most important symptoms and effects, both acute and delayed

#### Inhalation

High concentrations of vapors may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

### Ingestion

May cause stomach pain or vomiting.

### Skin Contact

Prolonged skin contact may cause redness and irritation.

### Eye Contact

Irritating and may cause redness and pain.

## Indication of any immediate medical attention and special treatment needed

#### Notes To The Physician

No specific first aid measures noted.

## **5. FIRE-FIGHTING MEASURES**

Auto Ignition Temperature (°C) 310 °C (590°F) Flammability Limit - Lower(%) 0.8 % Flammability Limit - Upper(%) 14.0 % Flash point (°C) 100 °C (212°F) Sh CC (Setaflash closed cup). **Extinguishing Media** Extinguish with foam, carbon dioxide, dry powder or water fog. Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire. Hazardous combustion products Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2). **Protective Equipment For Fire-Fighters** Self contained breathing apparatus and full protective clothing must be worn in case of fire.

## 6. ACCIDENTAL RELEASE MEASURES

1-5%

1-5%

# CPS SCREEN WASH UV

### **Personal Precautions**

Avoid inhalation of vapors and aerosol spray. Avoid contact with skin and eyes. Wear protective clothing as described in Section 8 of this material safety data sheet. In case of spills, beware of slippery floors and surfaces.

### **Environmental Precautions**

Avoid discharge into water courses or onto the ground.

### Spill Clean Up Methods

Stop leak if possible without risk. Absorb spillage with oil-absorbing material.

## 7. HANDLING AND STORAGE

### Handling

Avoid contact with skin and eyes. Do not eat, drink or smoke when using the product. Promptly remove any clothing that becomes wet. Wash promptly if skin becomes wet. Use appropriate skin cream to prevent drying of skin.

### Storage

Store in tightly closed original container in a dry and cool place. Store away from: Oxidizing material.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

COMPONENT	STD	TWA (8-hrs)		STEL (15 min)		Notes
(2-METHOXYMETHYLETHOXY)PROPANOL	PEL	100	-	-	-	
(2-METHOXYMETHYLETHOXY)PROPANOL		100	-	150	-	
COMPONENT IDLH					IDLH	
(2-METHOXYMETHYLETHOXY)PROPANOL				600		

#### **Engineering Measures**

Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of vapors.

### **Respiratory Equipment**

If ventilation is insufficient, suitable respiratory protection must be provided. Use respiratory equipment with gas filter, type A2.

#### Hand Protection

Wear protective gloves. Butyl rubber gloves are recommended. Neoprene gloves are recommended. Nitrile gloves are recommended. Be aware that the liquid may penetrate the gloves. Frequent change is advisable.

### Eye Protection

Wear approved, tight fitting safety glasses where splashing is probable.

#### **Other Protection**

Wear suitable protective clothing as protection against splashing or contamination.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid	
Color	Yellowish	
Odor	Solvent.	
Solubility	Forms an emulsion with water.	
Initial boiling point and boiling range	190 - 240 °C (374-464°F)	
Relative density	1.08 g/ml @ 20 °C (68°F)	
Vapor density (air=1)	> 1	
Vapor pressure	0.027 kPa @ 20 °C (68°F)	
Evaporation rate	< 1 (BuAc = 100)	
pH-Value, Diluted Solution		
Not available.		
Viscosity		
Not available.		
Flash point	100 °C (212°F) Sh CC (Setaflash closed cup).	
Auto Ignition Temperature (°C)	310 °C (590°F)	
Flammability Limit - Lower(%)	0.8 %	
Flammability Limit - Upper(%)	14.0 %	
Volatile Organic Compound (VOC)	ASTM D2369: 1040 g/litre	

# **10. STABILITY AND REACTIVITY**

### Reactivity

There are no known reactivity hazards associated with this product.

### Stability

Stable under normal temperature conditions and recommended use.

### Materials To Avoid

Strong acids. Strong alkalis. Strong oxidizing substances.

## **11. TOXICOLOGICAL INFORMATION**

### Toxicological information

No information available.

## **12. ECOLOGICAL INFORMATION**

#### Degradability

The product is expected to be biodegradable.

### Bioaccumulative potential

The product does not contain any substances expected to be bio-accumulating.

#### Mobility:

The product is miscible with water. May spread in water systems.

## **13. DISPOSAL CONSIDERATIONS**

#### **Disposal Methods**

Dispose of contents/container in accordance with local regulations. Contact specialist disposal companies. Recover and reclaim or recycle, if practical. Liquid components can be disposed of by incineration. Small quantities in an industrial wastewater stream are easily treated in biological treatment systems.

### Waste Class

Not classified as hazardous waste under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261

## **14. TRANSPORT INFORMATION**

General

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, DOT).

**Transport Labels** 

No transport warning sign required.

Environmentally Hazardous Substance/Marine Pollutant

No.

## **15. REGULATORY INFORMATION**

## **US Federal Regulations**

### **Federal Regulations Comments**

SECTION 313: This product does not contain toxic chemical subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR Part 372. TSCA: The ingredients of this product are on the TSCA Inventory.

## **US State Regulations**

#### State Regulations Comments

State and local regulations may apply.

## 16. OTHER INFORMATION

## **CPS SCREEN WASH UV**

### HAZARDOUS MATERIAL INFORMATION SYSTEM (HMIS)

HEALTH	1
FLAMMABILITY	1
PHYSICAL	0
PERSONAL PROTECTIO	N В

### NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)



### **Revision Comments**

NOTE: Lines within the margin indicate significant changes from the previous revision.		
Revision Date	05/08/2015	
Revision	5	

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.