

SAFETY DATA SHEET

Published DateRevision DateRevision NumberAug-29-2018Aug-28-20182

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product code ADE677
Product name Catalyst

Product category ADE Series SV Epoxy Screen Ink

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use
Recommended use Printing operations

Details of the supplier of the safety data sheet

UNITED STATES
UNITED KINGDOM
Nazdar Company
Nazdar Limited
8501 Hedge Lane Terrace
Shawnee, KS 66227
Burton Road
Heaton Mersey

Tel: +001-913-422-1888 Stockport, England SK4 3EG
Tel: +001-800-677-4657 Tel: +44 161 442 2111

Fax: +001-913-422-2294 www.nazdar.com

Emergency telephone number

USA: Chemtrec: +001-800-424-9300 Outside USA: Chemtrec: +001-703-527-3887

24 Hour Emergency Phone Number

2. HAZARDS IDENTIFICATION

Classification

Acute toxicity - Oral	Category 4 - (H302)
Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin Corrosion/irritation	Category 1 - (H314)
Serious eye damage/eye irritation	Category 1 - (H318)
Skin sensitization	Category 1 - (H317)
Specific target organ toxicity (single exposure)	Category 3
Acute aquatic toxicity	Category 1 - (H400)
Flammable liquids	Category 3 - (H226)

Label elements







Hazard Statements

ADE677 Catalyst Revision Date Aug-28-2018

H302 - Harmful if swallowed

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H332 - Harmful if inhaled

H400 - Very toxic to aquatic life

H226 - Flammable liquid and vapor

Precautionary Statements

P264 - Wash face, hands and any exposed skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing

P363 - Wash contaminated clothing before reuse

P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P273 - Avoid release to the environment

P235 - Keep cool

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Hazards not otherwise classified (HNOC)

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Component	CAS-No	Weight %	Trade Secret	Note
Resin	Trade Secret	30 - 60	*	
Propylene glycol monomethyl ether	107-98-2	10 - 30	*	
Methyl isobutyl ketone	108-10-1	10 - 30	*	
Xylenes (o-, m-, p- isomers)	1330-20-7	10 - 30	*	
Curing Agent	Trade Secret	1 - 5	*	
Diethylenetriamine	111-40-0	1 - 5	*	
Ethyl benzene (constituent)	100-41-4	1 - 5	*	1

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

Note 1. Type of chemical: Constituent

4. FIRST AID MEASURES

Description of first aid measures

General Advice Show this safety data sheet to the doctor in attendance.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Get medical attention if irritation develops and

persists.

Skin Contact Wash off immediately with soap and plenty of water for at least 15 minutes. Remove

contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.

Inhalation Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or

stopped, administer artificial respiration. Get medical attention immediately.

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a

physician or poison control center immediately.

Most important symptoms and effects, both acute and delayed

None under normal use conditions.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

No information available.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and

clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people

away from and upwind of spill/leak.

Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

Precautions for safe handling

HandlingUse personal protective equipment as required. Do not eat, drink or smoke when using this

product. Ensure adequate ventilation.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

open flames, hot surfaces and sources of ignition. Keep container closed when not in use.

Keep out of the reach of children.

Incompatible Products Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits

Component	ACGIH TLV
Propylene glycol monomethyl ether	TWA: 50 ppm
107-98-2	STEL: 100 ppm
Methyl isobutyl ketone	TWA: 20 ppm
108-10-1	STEL: 75 ppm

	TWA: 100 ppm STEL: 150 ppm
	TWA: 1 ppm Skin
Ethyl benzene (constituent) 100-41-4	TWA: 20 ppm

Component	OSHA PEL
Methyl isobutyl ketone	TWA: 100 ppm
108-10-1	TWA: 410 mg/m ³
Xylenes (o-, m-, p- isomers)	TWA: 100 ppm
1330-20-7	TWA: 435 mg/m ³
Ethyl benzene (constituent)	TWA: 100 ppm
100-41-4	TWA: 435 mg/m ³

Component	OSHA PEL (vacated)
Propylene glycol monomethyl ether	TWA: 100 ppm
107-98-2	TWA: 360 mg/m ³
	STEL: 150 ppm
	STEL: 540 mg/m ³
Methyl isobutyl ketone	TWA: 50 ppm
108-10-1	TWA: 205 mg/m ³
	STEL: 75 ppm
	STEL: 300 mg/m ³
Xylenes (o-, m-, p- isomers)	TWA: 100 ppm
1330-20-7	TWA: 435 mg/m ³
	STEL: 150 ppm
	STEL: 655 mg/m ³
Diethylenetriamine	TWA: 1 ppm
111-40-0	TWA: 4 mg/m ³
Ethyl benzene (constituent)	TWA: 100 ppm
100-41-4	TWA: 435 mg/m ³
	STEL: 125 ppm
	STEL: 545 mg/m ³

Component	Ontario TWAEV
Propylene glycol monomethyl ether	TWA: 50 ppm
107-98-2	STEL: 100 ppm
Methyl isobutyl ketone	TWA: 20 ppm
108-10-1	STEL: 75 ppm
Xylenes (o-, m-, p- isomers)	TWA: 100 ppm
1330-20-7	STEL: 150 ppm
Diethylenetriamine	TWA: 1 ppm
111-40-0	Skin
Ethyl benzene (constituent)	TWA: 20 ppm
100-41-4	

Component	Mexico OEL (TWA)
Methyl isobutyl ketone	TWA/VLE-PPT: 50 ppm
108-10-1	TWA/VLE-PPT: 205 mg/m ³
	STEL/PPT-CT: 75 ppm
	STEL/PPT-CT: 307 mg/m ³
Xylenes (o-, m-, p- isomers)	TWA/VLE-PPT: 100 ppm
1330-20-7	TWA/VLE-PPT: 435 mg/m ³
	STEL/PPT-CT: 150 ppm
	STEL/PPT-CT: 655 mg/m ³
Diethylenetriamine	TWA/VLE-PPT: 1 ppm
111-40-0	TWA/VLE-PPT: 4.2 mg/m ³
Ethyl benzene (constituent)	TWA/VLE-PPT: 100 ppm
100-41-4	TWA/VLE-PPT: 435 mg/m ³
	STEL/PPT-CT: 125 ppm
	STEL/PPT-CT: 545 mg/m ³

Appropriate engineering controls

Engineering Measures

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are

advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Wear safety glasses with side shields (or goggles). If splashes are likely to occur:. Wear

suitable face shield. Ensure that eyewash stations and safety showers are close to the

workstation location.

Skin Protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls,

as appropriate, to prevent skin contact.

Respiratory Protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Respiratory protection must be provided in

accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before

eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of

equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Water-white **Physical State** Liquid **Appearance**

Characteristic No information available Odor **Odor Threshold**

Property <u>Values</u> Remarks • Method pН

No data available **Melting Point / Freezing Point** No data available

Boiling Point / Boiling Range > 149 °C / 300 °F

Flash Point 27 °C / 80 °F Setaflash closed cup **Evaporation rate** No data available

Flammability Limit in Air

Upper flammability limit No data available

1.0% Lower flammability limit

Vapor Pressure No data available Vapor Density No data available

Specific Gravity 1.01

Water Solubility No data available Solubility in other solvents No data available No data available Partition coefficient: n-octanol/water **Autoignition Temperature** No data available **Decomposition temperature** No data available

Kinematic viscosity No data available **Dynamic viscosity** No data available

No data available **Explosive Properties Oxidizing Properties** No data available

Other Information

Photochemically Reactive Yes Weight Per Gallon (lbs/gal) 8.4

VOC by weight %	VOC by volume %	VOC lbs/gal	VOC grams/liter
(less water)	(less water)	(less water)	(less water)
53.2	53.09	4.47	536.15

10. STABILITY AND REACTIVITY

Reactivity

Revision Date Aug-28-2018

ADE677 Catalyst

No information available.

Chemical stability

Stable under normal conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO2). Carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Specific test data for the substance or mixture is not available. Harmful if inhaled. (based on

components).

Eye Contact Specific test data for the substance or mixture is not available. **Skin Contact** Specific test data for the substance or mixture is not available.

Ingestion Specific test data for the substance or mixture is not available. Harmful if swallowed. (based

on components).

Component	Oral LD50
Resin	= 540 mg/kg(Rat)
Propylene glycol monomethyl ether 107-98-2	= 5000 mg/kg(Rat)
Methyl isobutyl ketone 108-10-1	= 2080 mg/kg(Rat)
Xylenes (o-, m-, p- isomers) 1330-20-7	= 3500 mg/kg(Rat)
Curing Agent	= 1200 mg/kg(Rat)
Diethylenetriamine 111-40-0	= 1080 mg/kg(Rat)
Ethyl benzene (constituent) 100-41-4	= 3500 mg/kg(Rat)

Component	Dermal LD50
Propylene glycol monomethyl ether 107-98-2	= 13 g/kg(Rabbit)
Methyl isobutyl ketone 108-10-1	= 3000 mg/kg(Rabbit)
Xylenes (o-, m-, p- isomers) 1330-20-7	> 4350 mg/kg (Rabbit)
Curing Agent	= 1280 mg/kg(Rat)
Diethylenetriamine 111-40-0	= 672 mg/kg(Rabbit)
Ethyl benzene (constituent) 100-41-4	= 15400 mg/kg(Rabbit)

Component	Inhalation LC50
Propylene glycol monomethyl ether	> 7559 ppm (Rat) 6 h
107-98-2	
Methyl isobutyl ketone	= 8.2 mg/L (Rat) 4 h
108-10-1	
Xylenes (o-, m-, p- isomers)	= 29.08 mg/L (Rat) 4 h
1330-20-7	

ADE677 Catalyst

Diethylenetriamine 111-40-0	= 70 mg/L (Rat) 4 h
Ethyl benzene (constituent) 100-41-4	= 17.4 mg/L (Rat)4 h

Information on toxicological effects

Symptoms Specific test data for the substance or mixture is not available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Specific test data for the substance or mixture is not available. Causes severe burns.

(based on components).

Eye damage/irritation Specific test data for the substance or mixture is not available. Causes severe eye damage.

(based on components).

IrritationSpecific test data for the substance or mixture is not available.CorrosivitySpecific test data for the substance or mixture is not available.

Sensitization Specific test data for the substance or mixture is not available. May cause an allergic skin

reaction. (based on components).

Mutagenic EffectsSpecific test data for the substance or mixture is not available.Carcinogenic effectsSpecific test data for the substance or mixture is not available.Reproductive EffectsSpecific test data for the substance or mixture is not available.STOT - single exposureSpecific test data for the substance or mixture is not available.STOT - repeated exposureSpecific test data for the substance or mixture is not available.Chronic ToxicitySpecific test data for the substance or mixture is not available.Aspiration hazardSpecific test data for the substance or mixture is not available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

the table a control of the control o		
Component	ACGIH	
Methyl isobutyl ketone	A3	
108-10-1		
Ethyl benzene (constituent)	A3	
100-41-4		

Component	IARC
Methyl isobutyl ketone	Group 2B
108-10-1	
Ethyl benzene (constituent)	Group 2B
100-41-4	

Component	OSHA
Methyl isobutyl ketone	X
108-10-1	
Ethyl benzene (constituent)	X
100-41-4	

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0 % of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 1,181.00 mg/kg

 ATEmix (dermal)
 6,579.00 mg/kg mg/l

ATEmix (inhalation-dust/mist) 4.60 mg/l ATEmix (inhalation-vapor) 34.00 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Specific test data for the substance or mixture is not available. Very toxic to aquatic life. (based on components).

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Algae/aquatic plants
Methyl isobutyl ketone	96h EC50 Pseudokirchneriella subcapitata: = 400 mg/L
108-10-1	
Diethylenetriamine	96h EC50 Desmodesmus subspicatus: = 592 mg/L
111-40-0	72h EC50 Pseudokirchneriella subcapitata: = 1164 mg/L
	96h EC50 Pseudokirchneriella subcapitata: = 345.6 mg/L
Ethyl benzene (constituent)	96h EC50 Pseudokirchneriella subcapitata: > 438 mg/L
100-41-4	96h EC50 Pseudokirchneriella subcapitata: 1.7 - 7.6 mg/L static
	72h EC50 Pseudokirchneriella subcapitata: = 4.6 mg/L
	72h EC50 Pseudokirchneriella subcapitata: 2.6 - 11.3 mg/L static

Component	Fish
Propylene glycol monomethyl ether 107-98-2	96h LC50 Pimephales promelas: = 20.8 g/L (static)
Methyl isobutyl ketone 108-10-1	96h LC50 Pimephales promelas: 496 - 514 mg/L (flow-through)
Xylenes (o-, m-, p- isomers) 1330-20-7	96h LC50 Oncorhynchus mykiss: 2.661 - 4.093 mg/L (static) 96h LC50 Lepomis macrochirus: 7.711 - 9.591 mg/L (static) 96h LC50 Lepomis macrochirus: 13.1 - 16.5 mg/L (flow-through) 96h LC50 Poecilia reticulata: 30.26 - 40.75 mg/L (static) 96h LC50 Oncorhynchus mykiss: 13.5 - 17.3 mg/L 96h LC50 Lepomis macrochirus: = 19 mg/L 96h LC50 Cyprinus carpio: = 780 mg/L (semi-static) 96h LC50 Cyprinus carpio: > 780 mg/L 96h LC50 Pimephales promelas: = 13.4 mg/L (flow-through) 96h LC50 Pimephales promelas: 23.53 - 29.97 mg/L (static)
Diethylenetriamine 111-40-0	96h LC50 Poecilia reticulata: = 248 mg/L (static) 96h LC50 Poecilia reticulata: = 1014 mg/L (semi-static)
Ethyl benzene (constituent) 100-41-4	96h LC50 Pimephales promelas: 7.55 - 11 mg/L (flow-through) 96h LC50 Poecilia reticulata: = 9.6 mg/L (static) 96h LC50 Oncorhynchus mykiss: 11.0 - 18.0 mg/L (static) 96h LC50 Pimephales promelas: 9.1 - 15.6 mg/L (static) 96h LC50 Oncorhynchus mykiss: = 4.2 mg/L (semi-static) 96h LC50 Lepomis macrochirus: = 32 mg/L (static)

Component	Crustacea
Propylene glycol monomethyl ether	48h EC50 Daphnia magna: = 23300 mg/L
107-98-2	
Methyl isobutyl ketone	48h EC50 Daphnia magna: = 170 mg/L
108-10-1	
Xylenes (o-, m-, p- isomers)	48h EC50 water flea: = 3.82 mg/L
1330-20-7	48h LC50 Gammarus lacustris: = 0.6 mg/L
Diethylenetriamine	48h EC50 Daphnia magna: = 16 mg/L
111-40-0	
Ethyl benzene (constituent)	48h EC50 Daphnia magna: 1.8 - 2.4 mg/L
100-41-4	

<u>Persistence and Degradability</u> No information available.

Bioaccumulation

No information available

Component	Partition coefficient	
Propylene glycol monomethyl ether	-0.437	
107-98-2		
Methyl isobutyl ketone	1.19	
108-10-1		
Xylenes (o-, m-, p- isomers)	2.77 - 3.15	
1330-20-7		
Diethylenetriamine	-1.3	
111-40-0		
Ethyl benzene (constituent)	3.2	•
100-41-4		

Other adverse effects

ADE677 Catalyst Revision Date Aug-28-2018

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste Disposal Methods Contain and dispose of waste according to local regulations.

Contaminated Packaging Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. TRANSPORT INFORMATION

Note: This information is not intended to convey all specific transportation requirements relating to

this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation information can be found in the specific regulations for your mode of transportation. It is the responsibility of the transporting organization to follow all applicable laws, regulations and

rules relating to the transportation of the material.

DOT

UN/ID no. UN2734

Proper Shipping Name Polyamines, Liquid, Corrosive, Flammable, N.O.S. (Diethylenetriamine, Methyl Isobutyl

Ketone)

Hazard Class 8
Subsidiary Hazard Class 3
Packing Group ||

ICAO / IATA / IMDG / IMO

UN/ID no. UN2734

Proper Shipping Name Polyamines, Liquid, Corrosive, Flammable, N.O.S. (Diethylenetriamine, Methyl Isobutyl

Ketone)

Hazard Class 8
Subsidiary Hazard Class 3
Packing Group ||

15. REGULATORY INFORMATION

International Inventories

All components are listed on the TSCA Inventory. For further information, please contact:. Supplier (manufacturer/importer/downstream user/distributor).

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS-No	Weight %	SARA 313 - Threshold Values
Methyl isobutyl ketone	108-10-1	10 - 30	1.0
Xylenes (o-, m-, p- isomers)	1330-20-7	10 - 30	1.0
Ethyl benzene (constituent)	100-41-4	1 - 5	0.1

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:.

Component	CAS-No	Weight %
Methyl isobutyl ketone	108-10-1	10 - 30

Revision Date Aug-28-2018

ADE677 Catalyst

Xylenes (o-, m-, p- isomers)	1330-20-7	10 - 30
Ethyl benzene (constituent)	100-41-4	1 - 5

U.S. State Regulations

Component	Massachusetts Right To Know
Propylene glycol monomethyl ether 107-98-2	X
Methyl isobutyl ketone 108-10-1	X
Xylenes (o-, m-, p- isomers) 1330-20-7	X
Diethylenetriamine 111-40-0	X
Ethyl benzene (constituent) 100-41-4	X

Component	Minnesota Right To Know
Propylene glycol monomethyl ether 107-98-2	X
Methyl isobutyl ketone 108-10-1	X
Xylenes (o-, m-, p- isomers) 1330-20-7	X
Diethylenetriamine 111-40-0	X
Ethyl benzene (constituent) 100-41-4	X

	New Jersey Right To Know
Propylene glycol monomethyl ether 107-98-2	X
Methyl isobutyl ketone 108-10-1	X
Xylenes (o-, m-, p- isomers) 1330-20-7	X
Diethylenetriamine 111-40-0	X
Ethyl benzene (constituent) 100-41-4	X

Component	Pennsylvania Right To Know
Propylene glycol monomethyl ether 107-98-2	x
Methyl isobutyl ketone 108-10-1	x
Xylenes (o-, m-, p- isomers) 1330-20-7	x
Diethylenetriamine 111-40-0	x
Ethyl benzene (constituent) 100-41-4	x

<u>California Prop. 65</u>
This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

To productive right				
Component	California Prop. 65			
Methyl isobutyl ketone	Carcinogen			
	Developmental			
Ethyl benzene (constituent)	Carcinogen			

Canada

Component	NPRI - National Pollutant Release Inventory
Propylene glycol monomethyl ether 107-98-2	Part 5, Other Groups and Mixtures; Part 4 Substance
Methyl isobutyl ketone 108-10-1	Part 5, Individual Substances; Part 4 Substance
Xylenes (o-, m-, p- isomers) 1330-20-7	Part 5, Isomer Groups; Part 4 Substance
Ethyl benzene (constituent) 100-41-4	Part 1, Group A Substance; Part 4 Substance

Pursuant to NOM-018-STPS-2015

This information within is considered correct but is not exhaustive and will be used for guidance only, which is based on the current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.

16. OTHER INFORMATION						
HMIS:	Health 3 *	Flammability 3	Reactivity 0	Personal Protection		

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value

ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen
A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program) Known - Known Carcinogen

Reasonably Anticipated to be a Human Carcinogen
OSHA: (Occupational Safety & Health Administration)

X - Present

Revision Date Aug-28-2018

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet