



P.O. Box 368, Union, NJ 07083-0368, 908-687-7810, 800-327-2443, www.paigeelectric.com

SIGNWIRE

spec

**98P183M 1000 ft.
98P183L 500 ft.
98P183B 200 ft.**



**PLENUM +
LED SIGN WIRE
SUNLIGHT RESISTANT CL3P**



Application: Plenum LED Sign Wire, 2 conductor
18 AWG stranded tinned copper
75°C (UL) CL3P FT-6
Made in USA



1.0 CONSTRUCTION

1.1 Conductor:

- 1.1.1 Material: Tinned Copper
- 1.1.2 Size: 18 AWG
- 1.1.3 Stranding: 16 Strands

1.2 Lay Length:

- 1.2.1 This is an integral construction cable

1.3 Jacket:

- 1.3.1 Material:
Paige Compound #12056
- 1.3.2 Wall Thickness: .020"
- 1.3.3 O.D.: .187" x .086"
- 1.3.4 Marking: "PAIGE WEATHER RESISTANT RIPSTRIP™ LED PLENUM + P/N (*SEE BELOW) CONDUIT NOT REQUIRED E191597 18AWG 2C 75°C (UL) CL3P SUNLIGHT RESISTANT FT-6 "ROHS COMPLIANT" MADE IN USA WWW.PAIGEELECTRIC.COM" (sequential footage markers)
*98P183M – 1,000 ft. reel
98P183L – 500 ft. box
98P183B – 200 ft. bagged
- 1.3.5 Color: Light Blue + Light Blue/Red

1.4 Temperature / Voltage:

- 1.4.1 75°C / 300V

1.5 Packaging:

- 1.5.1 P/N 98P183M – 1000 ft. reel
- 1.5.2 P/N 98P183L – 500 ft. box
- 1.5.3 P/N 98P183B – 200 ft. bagged

1.6 Standard:

- 1.6.1 NEC/UL compliant for all applications other than "Wet" (direct exposure to the elements)

