

PALLET GEL

product of **PMI** TAPE

Important Instructions

Step 1: Clean the Pallets

PalletGel sticks best directly to clean and dry pallets.



Scan for Installation
Video

Step 2: Apply PalletGel

Apply the back edge of PalletGel directly to your pallet. While holding the opposite end of PalletGel up and off of the pallet, use a squeegee card or something rigid to squeegee PalletGel onto the pallet. Take your time here to avoid air bubbles. PalletGel will be on your pallets for a while.

Step 3: Tape the Edges ***Important**

Remove the top release liner from PalletGel and use masking tape to tape down all four sides of PalletGel to the pallets. This will help shirts slide and off of the pallets easily. It will also ensure PalletGel doesn't lift over time.

PalletGel Features

Durable 1mm thick Gel adhesive on the garment side

Lasts for several months

Lint can be easily cleaned off with water and a scrub pad

PalletGel changes color from green to yellow when your pallets are heated to 120F

Warm/Preheated pallets:

- Allow ink to flow through mesh smoothly
- Help prevent ink from sticking to the bottom of your screens
- Ensure consistency so your first print will be like your last
- Speed up flash time

PalletGel is applied directly to the pallets - No need for paper pallet tape

Film release liners on both sides that don't wrinkle for a smooth application

Made in the USA