



Recommendations	
<b>Product Overview</b>	
Product Code	PLUEF666
Industry	Inks
Application	Screen Printing
Category	Stock Colors
Chemistry	Plastisol
Substrate(s)	Cotton
Best Used By	12 months
Certification(s)	ISO9001
<b>Curing:</b>	
Fusion Temperature	320 °F
<b>Screen:</b>	
Mesh	86 to 305
Emulsion Type	Direct
Cleanup	Bio-degradable screen wash
<b>Storage:</b>	
Storage Temperature	65°F - 95°F (18°C - 35°C)

*Last Change: Oct 2017*

## PLUEF666 EF PHOSPHOR GREEN

For light and medium colored shirts, Hot-split and cold-peel transfers and 100% Cotton fabrics only. Ultrasoft inks will fully cure when the entire thickness of the ink deposit reaches 300°F (149°C).

### **Disclaimer:**

Not all Union products are available in every country. Please check with your local representative for availability. The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.