



SAFETY DATA SHEET

SECTION 1 — IDENTIFICATION

Product identifier: SUPERKLEEN 200
Product Number: 8201, 8205, 8255
Product uses: For industrial use only in removing cured screen print ink from textiles.*
Manufacturer's name and address: Refer to supplier
Supplier name and address:

ALBATROSS USA INC./EXPERT WORLDWIDE

36-41 36th Street
Long Island City, New York
United States
11106
718-392-6272

5439 San Fernando Road West
Los Angeles, California
United States
90039
818-543-5850

Emergency Telephone #: Spill, leak, fire, exposure or accident – Call CHEMTREC – Day or Night
1-800-424-9300 or 1-703-527-3887 (USA & Canada)
01-800-681-9531 (Mexico)

This Safety Data Sheet conforms to the requirements of ANSI Z400.5, and to the format requirements of the Global Harmonizing System. This SDS complies with 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD).

IMPORTANT: Read this SDS before handling and disposing of this product. Pass this information on to employees, customers, and users of this product.

*This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5) or processed (as defined in TSCA section 3(13) for consumer paint or coating removal.

SECTION 2 — HAZARDS IDENTIFICATION

DANGER !!



2.1 HAZARD STATEMENTS: (CAT = Hazard Category)

(H300s) HEALTH: Skin Corrosion/Irritation (CAT:2)

H315 CAUSES SKIN IRRITATION

(H300s) HEALTH: Serious Eye Damage/ Eye Irritation (CAT:2)

H320 CAUSES EYE IRRITATION

(H300s) HEALTH: Acute Toxicity, Inhalation (CAT:4)

H332 HARMFUL IF INHALED

(H300s) HEALTH: Target Organ Toxicity, Single Exposure; Respiratory Tract Irritation (CAT:3)

H335 MAY CAUSE RESPIRATORY IRRITATION

(H300s) HEALTH: Target Organ Toxicity, Single Exposure; Narcotic Effects (CAT:3)

H336 MAY CAUSE DROWSINESS OR DIZZINESS

(H300s) HEALTH: Target Organ Toxicity, Single Exposure (CAT:2)

H371 MAY CAUSE DAMAGE TO ORGANS (See section 11 for Target Organ Information)

(H400s) ENVIRONMENT: Hazard to Aquatic Environment, Acute (CAT:2)

H401 TOXIC TO AQUATIC LIFE

2.2 PRECAUTIONARY STATEMENTS:

EXPOSURE PREVENTION: STRICT HYGIENE! PREVENT DISPERSION OF MISTS OR DUST!

P100s = General, P200s = Prevention, P300s = Response, P400s = Storage, P500s = Disposal

P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.
P233	Keep container tightly closed.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P264	Wash with soap & water thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+352	IF ON SKIN: Wash with plenty of water.
P304+340	IF INHALED: Remove victim to fresh air & keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present & easy to do – Continue rinsing.
P308+311	IF exposed or concerned: Call a POISON CENTER/doctor/physician
P332+313	If skin irritation occurs: Get medical advice/attention.
P337+313	If eye irritation persists, get medical advice/attention.
P361	Take off immediately all contaminated clothing.
P363	Wash contaminated clothing before reuse.
P405	Store Locked up.
P500	Dispose of contents/container following local/regional/federal regulations.

SEE SECTIONS 8,11 & 12 FOR TOXICOLOGICAL INFORMATION

SECTION 3 — COMPOSITION/INFORMATION ON INGREDIENTS

MATERIAL	CAS#	EINECS#	WT %
METHYLENE CHLORIDE	75-09-2	200-838-9	80 - 90
PERCHLOROETHYLENE	127-18-4	200-825-9	0 - 10
ETHANOL	64-17-5	200-578-6	0 - 5
N-PROPYL ACETATE	109-60-4	-	0 - 5
ISOPROPANOL	67-63-0	200-661-7	0 - 5

The specific chemical component identities and/or the exact component percentages of this material may be withheld as trade secrets. This information is made available to health professionals, employees and designated representatives in accordance with the applicable provisions of 20 CFR 1910.1200 (I) (1).

TRACE COMPONENTS: Trace ingredients (if any) are present in < 1% concentration (< 0.1% for potential carcinogens, reproductive toxins, respiratory tract mutagens and sensitizers). None of the trace ingredients contribute

significant additional hazards at the concentrations that may be present in this product. All pertinent hazard information has been provided in this document per the requirements of the Federal Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalents, and Canadian Hazardous Materials Identification System Standard (CPR 4).

SECTION 4 — FIRST AID MEASURES

4.1 MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE & CHRONIC:

See Section 11 for Symptoms/Effects (acute & chronic).

4.2 GENERAL ADVICE:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists, refer to Section 8 for specific personal protective equipment.

4.3 EYE CONTACT:

If this product enters the eyes, check for and remove any contact lenses. Open eyes while under gently running water. Use sufficient force to open eyelids. "Roll" eyes to expose more surface. Minimum flushing is for 15 minutes. Seek immediate medical attention.

4.4 SKIN CONTACT:

If the product contaminates the skin, immediately begin decontamination with running water. Minimum flushing is for 15 minutes. Remove contaminated clothing, taking care not to contaminate eyes. If skin becomes irritated and irritation persists, medical attention may be necessary. Wash contaminated clothing before reuse, discard contaminated shoes.

4.5 INHALATION:

After high vapour exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, trained personnel should immediately begin artificial respiration. If the heart has stopped, trained personnel should immediately begin cardiopulmonary resuscitation (CPR). Seek immediate medical attention.

4.6 SWALLOWING:

If swallowed, CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION. If professional advice is not available, give two glasses of water to drink. DO NOT INDUCE VOMITING. Never induce vomiting or give liquids to someone who is unconscious, having convulsions, or unable to swallow. Seek immediate medical attention.

4.7 RESCUERS:

Victims of chemical exposure must be taken for medical attention. Rescuers should be taken for medical attention, if necessary. Take a copy of label and SDS to physician or health profession with victim.

4.8 NOTES TO PHYSICIAN:

There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. Any material aspirated during vomiting may cause lung injury. Therefore, emesis should not be induced mechanically or pharmacologically. If it is considered necessary to evacuate the stomach contents, this should be done by means least likely to cause aspiration (such as: Gastric lavage after endotracheal intubation)

SECTION 5 — FIRE FIGHTING MEASURES

5.1 FIRE & EXPLOSION PREVENTIVE MEASURES:

NO open flames, NO sparks, NO smoking. NO contact with oxidants. Above flash point, use a closed system, ventilation, explosion-proof electrical equipment, lighting. Do NOT use compressed air for filling, discharging, or handling.

5.2 SUITABLE (& UNSUITABLE) EXTINGUISHING MEDIA:

Use dry powder, alcohol-resistant foam, water in large amounts, carbon dioxide.

5.3 SPECIAL PROTECTIVE EQUIPMENT & PRECAUTIONS FOR FIRE FIGHTERS:

Water spray may be ineffective on fire but can protect fire-fighters & cool closed containers. Use fog nozzles if water is used. Do not enter confined fire-space without full bunker gear. (Helmet with face shield, bunker coats, gloves & rubber boots).

5.4 SPECIFIC HAZARDS OF CHEMICAL & HAZARDOUS COMBUSTION PRODUCTS:

COMBUSTIBLE!

Isolate from oxidizers, heat, & open flame. Closed containers may explode if exposed to extreme heat. Applying to hot surfaces requires special precautions. Empty container very hazardous! Continue all label precautions!

SECTION 6 — ACCIDENTAL RELEASE MEASURES

6.1 SPILL AND LEAK RESPONSE AND ENVIRONMENTAL PRECAUTIONS:

Uncontrolled releases should be responded to by trained personnel using pre-planned procedures. No action shall be taken involving personal risk without suitable training. Keep unnecessary and unprotected personnel from entering spill area. Do not touch or walk through material. Avoid breathing vapour or mist. Provide adequate ventilation. Proper protective equipment should be used. In case of a spill, clear the affected area, protect people, and respond with trained personnel. ELIMINATE all ignition sources (no smoking, flares, sparks, or flames in immediate area).

6.2 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, EMERGENCY PROCEDURES:

The proper personal protective equipment for incidental releases (such as: 1 liter of the product released in a well-ventilated area), use impermeable gloves, they should be Level B: **triple-gloves (rubber gloves and nitrile gloves over latex gloves), chemical resistant suit and boots, hard-hat, and Self-Contained Breathing Apparatus** specific for the material handled, goggles, face shield, and appropriate body protection. In the event of a large release, use impermeable gloves, specific for the material handled, chemically resistant suit and boots, and hard hat and Self-Contained Breathing Apparatus or respirator.

Personal protective equipment are required wherever engineering controls are not adequate or conditions for potential exposure exist. Select NIOSH/MSHA approved based on actual or potential airborne concentrations in accordance with latest OSHA and/or ANSI recommendations.

6.3 ENVIRONMENTAL PRECAUTIONS:

Stop spill at source. Construct temporary dikes of dirt, sand, or any appropriate readily available material to prevent spreading of the material. Close or cap valves and/or block or plug hole in leaking container and transfer to another container. Keep from entering storm sewers and ditches which lead to waterways, and if necessary, call the local fire or police department for immediate emergency assistance.

6.4 METHODS AND MATERIAL FOR CONTAINMENT & CLEAN-UP.

Absorb spilled liquid with polypads or other suitable absorbent materials. If necessary, neutralize using suitable buffering material, (acid with soda ash or base with phosphoric acid), and test area with litmus paper to confirm neutralization. Clean up with non-combustible absorbent (such as: sand, soil, and so on). Shovel up and place all spill residue in suitable containers, dispose of at an appropriate waste disposal facility according to current applicable laws and regulations and product characteristics at time of disposal (see Section 13 – Disposal Considerations).

6.5 NOTIFICATION PROCEDURES:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. US regulations require reporting release of this material to the environment which exceed the applicable reportable quantity or oil spills which could reach any waterway including intermittent dry creeks. The National Response Center can be reached at (800) 424-8802.

SECTION 7 — HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING:

Electrostatic charge may accumulate and create a hazardous conditions when apumping and handling this material. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures. For more information, refer to OSHA Standard 20 CR 1910.106, “Flammable and Combustible Liquids”, National Fire Protection Association (NFPA 77, “Recommended Practice on Static electricity”, and/or the American Petroleum Institute (API) Recommended Practice 2003, “Protection Against Ignitions Arising Out of Static, Lightning, and Stray currents”. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/sec until fill pipe submerged to twice its diameter, then ≤ 7 m/sec). Avoid splash filling. Do NOT use compressed air for filling, discharging or handling operations. Avoid free fall of liquid. Ground containers when transferring. **Empty container very hazardous! Do not flame cut, saw, drill, braze, or weld. Continue all label precautions!**

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:

Keep in fireproof surroundings. Keep separated from strong oxidants, metals, food & feedstuffs. Keep cool. Keep in the dark. Use ventilation along the floor. See: Section 10, <Materials to Avoid>. When using, loosen bung slowly to relieve pressure. Do not store above 38°C / 100°F. Contact with hot surfaces can produce toxic gases. Keep container tightly closed & upright when not in use to prevent leakage.

7.3 NONBULK: CONTAINERS:

Store containers in a cool, dry locations, away from direct sunlight, sources of intense heat, or where freezing is possible. Material should be stored in secondary containers or in a diked area, as appropriate,. Store containers away from incompatible chemicals (see Section 10, Stability and Reactivity). Post warnings and “NO SMOKING” signs in storage and use areas, as appropriate. Empty containers should be handled with care. Never store food, feed, or drinking water in containers which held this product.

7.4 PROTECTIVE PRACTICES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT:

Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely store until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. **DO NOT PRESSURIZE, CUT, WELD, BRAZE, SLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY BURST AND CAUSE INJUEY OR DEATH.**

SECTION 8 — EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 EXPOSURE LIMITS:

MATERIAL	CAS#	EINECS#	TWA (OSHA)	TLV (ACGIH)
Methylene Chloride	75-09-2	200-838-9	25 ppm	50 ppm A3
Perchloroethylene	127-18-4	204-825-9	75 ppm	25 ppm A3
Ethanol	64-17-5	200-578-6	1000 ppm	1000 ppm A4
n-Propyl Acetate	109-60-4	-	200 ppm	200 ppm
Isopropanol	67-63-0	200-661-7	400 ppm	200 ppm

MATERIAL	CAS#	EINECS#	CEILING STEL (OSHA/ACGIH)	HAP
Methylene Chloride	75-09-2	200-838-9	None Known 125 ppm	Yes
Perchloroethylene	127-18-4	204-825-9	None Known 100ppm	Yes
n-Propyl Acetate	109-60-4	-	None Known 250 ppm	No

BODY PROTECTION:

Use body protection appropriate for task. Cover-all, rubber aprons, or chemical protective clothing made from Impervious materials are generally acceptable, depending on the task.

WORK & HYGIENIC PRACTICES:

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using toilet facilities and at the end of the working period. Provide readily accessible eye wash stations & safety showers. Remove clothing that becomes contaminated. Destroy contaminated leather articles. Launder or discard contaminated clothing.

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Liquid, Water-White
ODOR:	Ester
ODOR THRESHOLD:	No Available
pH (Neutrality):	Not Available
MELTING POINT/FREEZING POINT	Not Available
BOILING RANGE (IBP, 50%, Dry Point)::	38° 45° 122°C / 102° 113° 252°F
FLASH POINT (TEST METHOD)	> 61C° / >141°F (PM)
EVAPORATION RATE (n-Butyl Acetate=1):	4.2
FLAMMABILITY CLASIFICATION:	Class III B
LOWER FLAMMABLE LIMIT IN AIR (% by vol):	2.0 (Lowest Component)
UPPER FLAMMABLE LIMIT IN AIR (% by vol):	Not Available
VAPOR PRESSURE (mm of Hg) @ 20°C	328.2
VAPOR DENSITY (air = 1):	2.9
GRAVITY @ 68/68°F / 20/20°C:	
DENSITY:	1.255
SPECIFIC GRAVITY (Water = 1):	1.257
POUNDS/GALLON:	10.471
WATER SOLUBILITY:	Moderate
PARTICITION COEFFICIENT (n-Octane/Water):	Not Available
AUTO IGNITION TEMPERATURE:	398°C / 750°F
DECOMPOSITON TEMPERATURE:	Not Available
TOTAL VOC's (TVOC)*:	100.0 Vol% / 1257.0 g/L / 10.4Lbs/Gal
NONEXEMPT VOC'S (CVOC)*:	13.0% Vol% / 106.6 g/L / .8 Lbs/Gal
HAZARDOUS AIR POLLUTANTS (HAPS):	92.6 Wt% / 1163.4 g/L / 9.6 Lbs/Gal
NONEXEMPT VOC PARTIAL PRESSURE (mm of Hg @ 20°C:	0.0
VISCOSITY @ 20°C (ASTM D445):	Not Available

* Using CARB (California Air Resources Board Rules).

SECTION 10— STABILITY & REACTIVITY**10.1 REACTIVITY & CHEMICAL STABILITY**

Stable under normal conditions, no hazardous reactions when kept from incompatibles.

10.2 POSSIBILITY OF HAZADOUS REACTIONS & CONDITIONS TO AVOID:

Isolate from oxidizers, heat, & open flame.

10.3 INCOMPATIBLE MATERIALS:

Decomposes on heating on contact with hot surfaces or flames producing, toxic & corrosive fumes including, chlorine phosgene, & hydrogen chloride. Reacts with strong oxidants, strong bases, causing fire & explosion hazard. Reacts with metals such as: aluminium, barium, beryllium, calcium, lithium, strontium. Reacts with amines, metals, such as aluminium powder, and magnesium powder. Reacts slowly with water influenced by light releasing corrosive, hydrochloric acid, trichloroacetic acid. Attacks many plastics, rubber, and coatings.

10.4 HAZARDOUS DECOMPOSITION PRODUCTS

Carbon Monoxide, Carbon Dioxide, Hydrogen Chloride, Phosgene from burning

10.5 HAZARDOUS POLYMERIZATION

Will not occur.

SECTION 11 — TOXICOLOGICAL INFORMATION**11.1 ACUTE HAZARDS****11.1.1 SKIN CONTACT:**

Primary irritation to skin, defatting, dermatitis. Wash thoroughly after handling

11.1.2 EYE CONTACT

Primary irritation to eyes, redness, tearing, blurred vision. Liquid can cause eye burns & skin irritation.

11.1.3 INHALATION:

Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression which can cause death. Vapor harmful. Concentrate vapour in confined areas may be fatal. Exposure increases Carbon Monoxide level of blood. OSHA required periodic vapour monitoring whenever Methylene Chloride vapors may exceed the action level (12.5 parts per million). The odor warning when the exposure limit value is exceeded is insufficient. Use of alcoholic beverages enhances the harmful effect.

11.1.4 SWALLOWING:

Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea. The symptoms of chemical pneumonitis may not show up for a few days.

11.2 SUBCHRONIC HAZARDS/CONDITIONS AGGRAVATED**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:**

Pre-existing disorders of any target organs mentioned in this document can be aggravated by over-exposure by routes of entry to components of this product. Persons with these disorders should avoid use of this product.

11.3 CHRONIC HAZARDS**11.31 CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS:**

Potential Cancer Hazard based on tests with laboratory animals using Methylene Chloride and Perchloroethylene. Kidney, mammary, lung, liver tumors, leukemia have been reported in laboratory mice, rats. Overexposure may Create cancer risk. Usually contains a stabilizer or inhibitor. A stabilizer / inhibitor can influence the toxic properties of this substance. Consult an expert. Depending on degree of exposure, periodic medical examination is indicated.

11.32 **TARGET ORGANS:** May cause damage to target organs, based on animal data.

11.33 **IRRITANCY:** Irritating to contaminated tissue.

11.34 **SENSITIZATION:** No component is known as a sensitizer.

- 11.35 MUTAGENICITY: No known reports of mutagenic effects in humans.
 11.36 EMBRYOTOXICITY: No know reports of embryotoxic effects in humans.
 11.37 TERATOGENICITY: No known reports of teratogenic effects in humans.
 11.38 REPRODUCTIVE TOXICITY: No known reports of reproductive effects in humans.

A MUTAGEN is a chemical which causes permanent changes to genetic material (DNA) such that the changes will propagate across generational lines. An EMBRYOTOXIN is a chemical which causes damage to a developing embryo (such as: within the first 8 weeks of pregnancy in humans), but the damage does not propagate across generational lines. A TERATOGEN is a chemical which causes damage to a developing fetus, but the damage does not propagate across generational lines. A REPRODUCTIVE TOXIN is any substance which interferes in any way with the reproductive process.

11.4 MAMMALIAN TOXICITY INFORMATION

	CAS# / EINECS#	LOWEST KNOWN LETHAL DOSE DATA
Methylene Chloride	75-09-2 / 200-838-9	LOWEST KNOWN LD50 (ORAL): 1900.0 mg/kg (Rabbits)

SECTION 12 — ECOLOGICAL INFORMATION

12.1 ALL WORK PRACTICES MUST BE AIMED AT ELIMATING ENVIRONMENTAL CONTAMINATION

12.2 EFFECT OF MATERIAL ON PLANTS AND ANIMALS:

This product may be harmful or fatal to plant and animal life if released into the environment. Refer to Section 11 (Toxicological Information) for further data on the effects of this product's components on test animals.

12.3 EFFECT OF MATERIAL ON AQUATIC LIFE:

The most sensitive known aquatic group to any component of this product is: Chub 145 ppm or mg/L (48 hour exposure). Keep out of sewers and natural water supplies. The substance is toxic to aquatic organisms. The substance may cause long-term effects in the aquatic environment. Special attention should be given to ground water contamination.

12.4 MOBILITY IN SOIL

This material is a mobile liquid.

12.5 DEGRADABILITY

This product is partially biodegradable.

12.6 ACCUMULATION

This product does not accumulate or biomagnify in the environment.

SECTION 13 — DISPOSAL CONSIDERATIONS

The generation of waste should be avoided or minimized, wherever possible. Dispose of surplus and non recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers and liners may retain some product residues. Vapor from some product residues may create a highly flammable or explosive atmosphere inside the container. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose used containers to heat, flame, sparks, static, electricity, or other sources of ignition. They may burst and cause injury or death. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Processing, use or contamination may change the

waste disposal requirements. Do not dispose of on land, in surface waters, or in storm drains. Waste should be recycled or disposed of in accordance with regulations. Large amounts should be collected for reuse or consigned to licensed hazardous waste haulers for disposal. **ALL DISPOSAL MUST BE IN ACCORDANCE WITH ALL FEDERAL, STATE, PROVINCIAL, AND LOCAL REGULATIONS. IF IN DOUBT, CONTACT PROPER AGENCIES. EPA CHARACTERISTIC: D001, D039**

SECTION 14— TRANSPORTATION INFORMATION

If > 1161 lb/527 KG of this product is in 1 container, it exceeds the RQ of methylene chloride. "RQ" must be put before the dot shipping name.

DOT SHIPPING NAME: UN2810, Toxic Materials, organic, n.o.s.
 (Contains: Methylene Chloride, Perchloroethylene) 6.1, PG-III
 DRUM LABEL: (TOXIC PG-III)
 IATA / ICAO UN2810, Toxic materials, organic, n.o.s.
 (Contains: Methylene Chloride, Perchloroethylene) 6.1, PG-III
 IMO / IMDG: UN2810, Toxic materials, organic, n.o.s.
 (Contains: Methylene Chloride, Perchloroethylene) 6.1, PG-III
 EMERGENCY RESPONSE GUIDEBOOK NUMBER: 153

SECTION 15 — REGULATORY INFORMATION

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5) or processed (as defined in TSCA section 3(13) for consumer paint or coating removal.

15.1 EPA REGULATION:
 SARA SECTION 311/312 HAZARDS: Acute Health, Chronic Health

All components of this product are on the TSCA list. SARA Title III Section 313 Supplier Notification. This product contains the indicated (*) toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right-To-Know Act of 1986 & 40 CFR 372. This information must be included in all MSDS's that are copied and distributed for this material.

SARA TITLE III INGREDIENTS	CAS #	EINECS#	WT. %	(REG. SECTION)	RQ (LBS)
*Methylene Chloride	75-09-2	200-838-9	80 - 90	(311, 312, 313, RCRA)	1000
*Perchloroethylene	127-18-4	204-825-9	0 - 10	(311, 312, 313, RCRA)	100

Any release equal to or exceeding the RQ must be reported to the National Response Center (800-424-8802) and appropriate state and local regulatory agencies as described in 40 CFR 302.6 and 40 CFR 355.40 respectively. Failure to report may result in substantial civil and criminal penalties. State & local regulations may be more restrictive than federal regulations.

15.2 STATE REGULATIONS:
 This product meets requirements of Southern California AQMD Rule 443.1 & similar regulations. CALIFORNIA SAFE DRINKING WATER & TOXIC ENFORCEMENT ACT (PROPOSITION 65): This product contains the following chemicals known to the State of California to cause cancer: Methylene Chloride, Perchloroethylene.

15.3 INTERNATIONAL REGULATIONS:
 The identified components of this product are listed on the chemical inventories of the following countries:
 Australia (AICS), Canada (DSL or NDSL), China (IECSC), Europe (EINECS, ELINCS), Japan (METI/CSCL,

MHLW/ISHL), South Korea (KECI), New Zealand (NZIoC), Philippines (PICCS), Switzerland (SWISS), Taiwan (NECSI), USA (TSCA).

15.4 CANADA: WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

B3: Combustible liquid

D2A: Contains substance known to cause serious chronic toxicity or death.

Methylene Chloride, Perchloroethylene

D2B: Irritating to eyes/skin.

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations (CPR).

This document contains all information required by the CPR.

California Prop. 65 Components: Methylene Chloride, Perchloroethylene



This product can expose you to chemicals including methylene chloride and perchloroethylene which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16 — OTHER INFORMATION

16.1 HMIS RATINGS:

HEALTH (NFPA): 2 HEALTH (HMIS): 2, FLAMMABILITY: 2, PHYSICAL HAZARD: 0

(personal protection rating to be supplied by user based on use conditions)

This information is intended solely for the use of individuals trained in the NFPA & HMIS hazard rating systems.

HMIS KEY:

16.2 EMPLOYEE TRAINING:

See Section 2 (Hazards Identification). Employees should be made aware of all hazards of this material (as Stated in this SDS) before handling it.

16.3 SDS Date: 07/14/2017

Prepared for: Albatross USA Inc.

Telephone number: 718-392-6272

Preparation date: 07/14/2017

Revision Date: 12/21/2022

Reason for revision: Use limitation statements added to sections 1 & 15.

NOTICE:

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process. Unless updated, this Material Safety Data Sheet is valid until 08/12/2022