

COPPERHEAD PRO MINI

Print size : 15 x 15 cm / 6" x 6"

Now print on hoodie with standard pallets



Standard Features:

- ▶ **Newer Improved HMI interface with icon-based logic**
- ▶ **Hoodie printing now possible with the all new standard pallets**
- ▶ **NO Compressor Required**
- ▶ Servo Driven Indexer
- ▶ Flash with upgraded power
- ▶ Plug & Play
- ▶ 3 Point Registration System
- ▶ Individual Off Contact
- ▶ Pre-defined Print Head and Flash Position
- ▶ Heavy Solid Steel Foundation to support speed and reduce vibration.
- ▶ Digital Touch Screen Controls
- ▶ Mechanical Squeegee Pressure Equalizer

FIRST FULLY LOADED MACHINE

This is it !

What's included ?

- ▶ 1 Set of Coated Aluminium Pallets (4.3 x 9" / 11 x 23 cm)
- ▶ 1 Set of Squeegee holder with squeegee rubber 8x30mm (4.25" / 11 cm)
- ▶ 1 Set of Floodbar (6.25" / 16 cm)
- ▶ 1 Set of Frames (11 x 15" / 28 x 38 cm)
- ▶ 1 Set Adaptor kit to accommodate 9x15" (23x38 cm) frames
- ▶ Index & Skip Foot Pedal
- ▶ Optical No Shirt Sensor
- ▶ Programmable Multiple Index Rotation
- ▶ Programmable Squeegee Strokes
- ▶ Multi Print Mode Program
- ▶ Print Stack Mode
- ▶ Laser Registration Guide
- ▶ Pallet Pre-heat mode
- ▶ Maintenance Reminder Mode
- ▶ Caster Wheels
- ▶ Toolkit



Note:

■

- This product has certificate available. 10 Station model not available in UL. ■

Install charges only include labor cost. All other costs like food, travel, airfare, visa charges & miscellaneous costs are at actual.

- *Self-installation is possible with basic technical skills. Contact DCC for more information.

Specifications

	PRO MINI 8/1	PRO MINI 8/2	PRO MINI 8/3	PRO MINI 10/4
Electrical Requirements ¹	208-230 V, 1 ph, 39 A, 50/60 Hz, 7.05 kW (UL) 208-230 V, 1 ph, 39 A, 50 Hz, 7.05 kW (CE)	208-230 V, 1 ph, 39.5 A, 50/60 Hz, 7.15 kW (UL) 208-230 V, 1 ph, 39.5 A, 50 Hz, 7.15 kW (CE)	208-230 V, 1 ph, 40 A, 50/60 Hz, 7.25 kW (UL) 208-230 V, 1 ph, 40 A, 50 Hz, 7.25 kW (CE)	208-230 V, 1 ph, 53 A, 50/60 Hz, 9.6 kW
In-built Flash Cure Units	3	3	3	4
Diameter	128 cm (50.5")	128 cm (50.5")	128 cm (50.5")	146 cm (57.5")
Maximum Frame Size	28 x 38 cm (11" x 15")	28 x 38 cm (11" x 15")	28 x 38 cm (11" x 15")	28 x 38 cm (11" x 15")
Maximum Image Area	15 x 15 cm (6" x 6")	15 x 15 cm (6" x 6")	15 x 15 cm (6" x 6")	15 x 15 cm (6" x 6")
Standard Pallet Size	11 x 23 cm (4.3" x 9")	11 x 23 cm (4.3" x 9")	11 x 23 cm (4.3" x 9")	11 x 23 cm (4.3" x 9")
Machine Weight	262 kg (578 lb)	294 kg (648 lb)	326 kg (719 lb)	400 kg (882 lb)
Stations/Colors	8/1	8/2	8/3	10/4

¹ Use uninterruptible power supply (UPS) to safeguard machine from voltage fluctuation out of main supply. If incoming voltage differs from the voltage(s) listed in the brochure, calculate amperage accordingly

Crate Details

MACHINE NAME	BOX NO.	DESCRIPTION	CRATE DIMENSIONS (LXWXH)	QTY (IN NOS.)	GROSS WEIGHT
Copperhead Pro Mini 8 Station/ 1 Color/ 3 Flash	1	Entire Machine	52 x 52 x 66 (in) 133 x 133 x 168 (cm)	1.00	895 (lb) 407 (kg)
Copperhead Pro Mini 8 Station/ 2 Color/ 3 Flash	1	Entire Machine	52 x 52 x 66 (in) 133 x 133 x 168 (cm)	1.00	966 (lb) 439 (kg)
Copperhead Pro Mini 8 Station/ 3 Color/ 3 Flash	1	Entire Machine	52 x 52 x 66 (in) 133 x 133 x 168 (cm)	1.00	1036 (lb) 471 (kg)
Copperhead Pro Mini 10 Station/ 4 Color/ 4 Flash	1	Entire Machine	59 x 59 x 64 (in) 150 x 150 x 163 (cm)	1.00	1210 (lb) 550 (kg)