



CIRRUS
LED SYSTEMS

CIRRUS SYSTEMS NEW PURCHASE FORM

Sign Information:	
Model (circle one): BladeX	Display Size: _____ H x _____ W Single Sided _____ Double Sided _____
Solo Fire Red	Display Pitch: 9mm 12mm 15mm (Red/White) 16mm 19mm (Circle One)
Solo Ice White	

Sign Shop Info

Name: _____

Address: _____

City: _____ State: _____ Zip: _____

Contact Name: _____ Phone: _____

Project Manager Name: _____ Email: _____

Project Manager Cell: _____

End User Info

Name of Business: _____

Address: _____

City: _____ State: _____ Zip: _____

Contact Name _____ Email: _____

Phone: _____

Projected Install Date _____

To activate your display and system warranty, you must sign and return to sales@martin-supply.com or Fax: 410-366-0134. This information is required for the best customer experience. Prior to install, our Software team will contact the end user and thoroughly train them on our LED Cloud software.



Pre-Installation and Installation Requirements

Please consult Installation Manual for complete details and requirements.

The Basics

Is this a new sign or a retrofit? New_____ Retrofit_____

How will the sign connect to the internet?

Engenius WiFi (supplied)_____ Ethernet Direct_____ Broadband_____

Cirrus does not offer Broadband/4g options at this time.

Is there direct line of sight and no obstructions from the Wifi transmitter to the the sign?

Yes_____ No_____

Obstructions that interfere with direct line of sight between the sign and WiFi transmitter may cause a connectivity issue and an unreliable internet connection. Cirrus cannot be responsible for site conditions that affect internet connectivity.

Type of mounting? Monument_____ Pole_____ Pylon_____ Wall_____ Other_____

Distance from the building to the sign_____ft

Master Controller mounting location_____

The Master Controller for all Cirrus Displays is completely weatherproof and can be located inside or outside of the sign. Avoid placing the controller in direct sunlight. The Master Controller comes with 10' of cable going to each side of your display. Additional 10' cables are available to extend the maximum length the controller can be located away from the display to 20'. Please determine the length of cable needed before install.

Electrical Requirements

Does the display require a new electrical line to be run? Yes_____ No_____

What is the primary line voltage? 110v___ 120v___ 208v___ 220V___ 240v___

Breaker Rating _____amps (Do not load breaker more than 80% of maximum to insure proper performance)

Consult Installation Manual to calculate proper electrical requirements.

LED PANEL	BLADE-19-F1	BLADE-16-F1	BLADE-12-F1	SOLO-15R-F1	SOLO-15W-F1
Color	Full Color (RGB Spectrum)			Red	White
Resolution (Pitch)	19mm	16.97mm	12.7mm	15.25mm	15.25mm
Watts Per Panel	55.4W	55.7W	53.8W	19.5W	16.4W

LED PANEL	BLADE X-16-F1	BLADE X-12-F1	BLADE x-9-F1
Color	Full Color (RGB Spectrum)		
Resolution (Pitch)	16.97mm	12.7mm	9mm
Watts Per Panel	86.1W	88.0W	83.4W

<u>BLADE X</u>		<u>SOLO</u>	
<u>MODULES PER OUTPUT</u>	<u>REQUISITE VOLTAGE</u>	<u>MODULES PER OUTPUT</u>	<u>REQUISITE VOLTAGE</u>
1-13	120 or 240 VAC	1-61	120 or 240 VAC
14-27	240 VAC	62-123	240 VAC
28+	240 VAC w/ power splitter	124+	240 VAC w/ power splitter

As fluctuations in electrical current can cause performance issues, It is the responsibility of the sign installer to insure proper electrical requirements and site conditions are met. The use of surge protectors, electrical line conditioners and step-up/step-down transformers may be required for the display to operate correctly. Cirrus is not responsible for improper electrical service and warranty coverage may be denied if caused by unsuitable electrical conditions.



Internet Requirements

Are there any network restrictions (bandwidth limitations, firewalls, content filters, etc.) that could affect connectivity? Yes _____ No _____

Please note: If network security prevents internet access, a **Static IP Address** may need to be programmed into the controller **BEFORE THE SIGN IS INSTALLED**. Contact Cirrus for details.

****If you are not responsible to set up the network:** _____

Please provide your buyer's information. Cirrus will contact them directly to make sure that we have a complete understanding of the network requirements.

Software Training

Approximately 2 weeks prior to installation, Cirrus will contact the end user to provide software training. Please provide Cirrus with the end users contact information to schedule training. Training must be scheduled in advance and will not be provided at the time of install unless pre- arranged.

*****Your installation is not complete until the display is powered on, connected to an active internet connection, and you have spoken with a Cirrus Representative while still onsite.*****

To Activate display Please call 877-636-2331 x 2 to speak with a Cirrus Representative before leaving the job site.

By signing, buyer acknowledges having read and reviewed this important information for a successful install!

Authorized Signature _____ Date: _____