

PLENUM + LED SIGN WIRE SUNLIGHT RESISTANT CL3P

SPEC

98P143M 1000 ft.

98P143L 500 ft.



Application: Plenum LED Sign Wire, 2 conductor 14 AWG stranded tinned copper 75°C (UL) CL3P FT-6 Made in USA



Rip Strip



RoHS



1.0 CONSTRUCTION

1.1 CONDUCTOR:

- Material: Tinned Copper
- Size: 14 AWG
- Stranding: 19 Strands

1.2 LAY LENGTH:

- This is an integral construction cable

1.3 JACKET:

- Material: Paige Compound #12056
- Wall Thickness: .020"
- O.D.: .240" x .112"
- Marking: "PAIGE WEATHER RESISTANT RIPSTRIP® LED PLENUM + P/N (*SEE BELOW) CONDUIT NOT REQUIRED E191597 14AWG 2C 75°C (UL) CL3P SUNLIGHT RESISTANT FT-6 "ROHS COMPLIANT" MADE IN USA WWW.PAIGECONNECTED.COM" (sequential footage markers) *98P143M - 1,000 ft. reel 98P143L - 500 ft. box
- Color: Light Blue + Light Blue/Red

1.4 TEMPERATURE / VOLTAGE:

- 75°C / 300V

1.5 PACKAGING:

- P/N 98P143M - 1000 ft. reel
- P/N 98P143L - 500 ft. box

1.6 STANDARD:

- NEC/UL compliant for all applications other than "Wet" (direct exposure to the elements)